Product ID:MOBIL AERO HFA MSDS Date:01/05/1993 FSC:9150 NIIN:00-223-4134 MSDS Number: BWSMZ === Responsible Party === Company Name: MOBIL CHEMICAL CO., CHEMICAL COATINGS DIV. Address: RT 27 AND VINEYARD RD. Box:250 City:EDISON State:NJ ZIP:08818-0250 Country:US Info Phone Num:800-662-4525 800-227-0707 X3265 Emergency Phone Num:609-737-4411 OR 800-4 24-9300 Preparer's Name: ENVIR HEALTH & SAFETY DPT CAGE:77988 === Contractor Identification === Company Name: MOBIL CHEMICAL CO., CHEMICAL COATINGS DIV. Address: RT 27 AND VINEYARD RD. Box:250 City:EDISON State:NJ ZIP:08818-0250 Country:US Phone:609-737-4411 OR 800-424-9300 CAGE:77988 Ingred Name:MINERAL OIL

CAS:64742-53-6 RTECS #:PY8036000 Fraction by Wt: >90% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:2-PROPENOIC ACID,2-METHYL-,DODECYL ESTER,POLYMER W/METHYL-2-METHYL-2-PROPENOATE+TETRADECYL-2-METHYL-2-PROPENOATE CAS:68171-50-6 Fraction by Wt: 200F,>93C Lower Limits:0.6 Upper Limits:7.0 Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. WATER OR FOAM MAY CAUSE FROTHING. Fire Fighting Procedures: USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER FOG. **Unusual Fir** e/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS. Spill Release Procedures: ELIMINATE SOURCES OF IGNITION. USE PROPER RESPIRATORY AND PROTECTIVE EQUIPMENT. VENTILATE AREA. SOAK UP WITH A NON-COMBUSTIBLE INERT ABSORBANT(CLAY,SAND);PLACE IN PROPER CONTAINER FOR DISPOSAL.REPORT SPI LLS TO NATIONAL RESPONSE CENTER AT 800-424-8802. ====== Handling Handling and Storage Precautions: STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM HEAT, OPEN FLAMES AND STRONG OXIDANTS. KEEP CONTAINERS TIGHTLY CLOSED. Other Precautions: AVOID EYE AND SKIN CONTACT. DO NOT BREATHE VAPORS. Respiratory Protection:NOT NEEDED IN NORMAL SERVICE. Ventilation: USE GENERAL DILUTION VENTILATION. Protective Gloves: IMPERVIOUS **Eve Protection** :SPLASH GOGGLES IF MISTING. Other Protective Equipment: PROTECTIVE CLOTHING AS REQUIRED TO MINIMIZE EXPOSURE FROM PROLONGED OR REPEATED CONTACT. EYE BATH AND SAFETY SHOWER. Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. DISCARD CONTAMINATED SHOES Supplemental Safety and Health USED GASOLINE MOTOR OILS HAVE BEEN SHOWN TO CAUSE SKIN CANCER WHEN REPEATEDLY APPLIED TO MOUSE SKIN WITHOUT ANY EFFORT TO REMOVE THE

MATERIAL BETWEEN APPLICATIONS. THERE IS NO EVIDENCE OF A CAUSAL REL ATIONSHIP BETWEEN SKIN CANCER IN HUMANSAND EXPOSURE TO USED MOTOR OIL.

HCC:V6 Boiling Pt:B.P. Text:>450F,>232C Melt/Freeze Pt:M.P/F.P Text:-75F,-59C Vapor Pres:1 Spec Gravity:0.86 Viscosity:13 CS @104F Solubility in Water:NEGLIGIBLE Appearance and Odor:LIQUID;RED;MILD ODOR

Stab ility Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION Hazardous Decomposition Products:AIRBORNE SOLID AND LIQUID PARTICULATES, CARBON MONOXIDE, OTHER UNIDENTIFIED HYDROCARBON PRODUCTS.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.MFR STATES THAT IT IS THEIR OPINION THAT THE

UNUSED MATERIAL DOES NO EXHIBIT ANY OF THE CHARACTERISTICS OF RCRA HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and a ssume responsibility for the suitability of this information to their particular situation.