

MSDS Safety Information

FSC: 9150
NIIN: 01-052-4893
MSDS Date: 05/16/1993
MSDS Num: BXGZR
Product ID: 1 FORMULA 15W-50
MFN: 01
Responsible Party
Cage: 3U728
Name: MOBIL OIL CORP
Address: 3225 GALLONS ROAD
City: FAIRFAX VA 22037
Info Phone Number: 800-662-4525
Emergency Phone Number: 800-424-9300(CHEMTREC)
Proprietary Ind: Y
Published: Y

Contractor Summary

Cage: 3U728
Name: MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING
Address: 3225 GALLOWS ROAD
City: FAIRFAX VA 22037
Phone: 800-662-4525/ 856-224-4644

Item Description Information

Item Manager: S9G
Item Name: GREASE,GE
NERAL PURPOSE
Specification Number: NONE
Type/Grade/Class: NONE
Unit of Issue: CO
Quantitative Expression: 00000000035LB
UI Container Qty: 0
Type of Container: PAIL

Ingredients

Name: *** PROPRIETARY ***

Health Hazards Data

LD50 LC50 Mixture: L

D50: >2000 MG/KG
Route Of Entry Inds - Inhalation: NO
Skin: YES
Ingestion: NO
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO

Effects of Exposure: SLIGHT EYE IRRIT. SLIGHT SKIN IRRITATION. CHRONIC: STUDIES HAVE SHOWN THAT MICE DEVELOPED SKIN CANCER AFTER REPEATED APPLICATION OF USED GASOLINE ENGINE OIL TO THE SKIN FOR THE LIFETIME OF THE ANIMALS . NO EFFORT WAS MADE TO WASH THE OIL OFF BETWEEN APPLICATIONS. USED OIL FROM DIESEL ENGINES DID NOT(EFTS OF OVEREXP)

Explanation Of Carcinog
enicity: NOT RELEVANT.

Signs And Symptions Of Overexposure: HLTH HAZS: PRODUCE THIS EFT. BECAUSE THE EFTS OBSERVED IN THE LAB TESTS, SERVICE STATION WORKERS, ENGINE MECHANICS & ALL PERS WHO REGULARLY HANDLE USED MOTOR OIL SHOULD TAKE PRECS TO MINIMIZE CONTACT W/OIL. GOOD PERS HYGIENE PRACS, INCLG WASHING ANY SKIN CONTACT AREAS & REMOVING OIL SOAK CLTHG SHOULD BE FOLLOWED.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYE: FLUSH THOROUGHLY W/WATE
R FOR AT LEAST 15 MINUTES. IF IRRIT

OCCURS, CALL MD. INGEST: IF >1.2 LITER(PINT) INGESTED, IMMED GIVE 1 TO 2 GLASSES OF WATER & CALL MD, HOSPITAL EMER ROOM/POISON CONTROL C ENTER FOR ASSIST. DO NOT INDUCE VOMIT/GIVE ANYTHING BY MOUTH TO AN UNCON PERSON. SKIN: WASH CONTACT AREAS W/SOAP & WATER. INHAL: REMOVE TO FRESH AIR. SUPPORT BREATHING(GIVE O*2/ARTF RESP)(FP N).

=====
Handling and Disposal
=====

=====
Spill Release Procedures: ENVIRON IMPACT: IN CASE OF ACCIDENT/ROAD SPILL NOTIFY CHEMTREC(800)424-9300. REPORT SPILLS AS REQD TO APPROP AUTHS. U.S. COAST GUARD REGS REQ IMMED REPORTING OF SPILLS THAT COULD REACH ANY WATERWAY IN CLG INTERMITTENT DRY CREEKS. REPORT SPILL(SUPDAT)

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: PROD IS SUITABLE FOR BURNING IN ENCLSD, CONTROLLED BURNER FOR FUEL VALUE/DISP BY SUPERVISED INCIN. SUCH BURNING MAY BE LIMITED

PURSUANT TO RCRA. IN ADDN, PROD IS SUITABLE FOR PROCESSING BY AN APPRVD R ECYCLING FACILITY/CAN BE DISP OF AT ANY

Handling And Storage Precautions: NONE SPECIFIED BY MANUFACTURER.

Other Precautions: NONE SPECIFIED BY MANUFACTURER.
=====

Fire and Explosion Hazard Information
=====

Flash Point Method: COC

Flash Point Text: >420F,>216C

Lower Limits: 0.6%

Upper Limits: 7.0%

Extin

guishing Media: CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG.
Fire Fighting Procedures: WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP(FP N). WATER/FOAM MAY CAUSE FROTHING. USE WATER TO KEEP FIRE EXPOSED CNTNRS COOL. WATER SPRAY MAY BE USED(SUPDAT)
Unusual Fire/Explosion Hazard: NONE.

Control Measures

Respiratory Protection: NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE & WITH ADEQUATE VENTILATION. USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN(FP N).
Ventilation: NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.
Protective Gloves: IMPERVIOUS GLOVES(FP N).
Eye Protection: ANSI APPRVD CHEM WORKERS GOGGS(FP N).
Other Protective Equipment: EMERGENCY EYEWASH & DELUGE SHOWER MEETING ANSI DESIGN CRITERIA(FP N).
Work Hygienic Practices: GOOD PERSONAL HYGIENE PRACTICES SHOULD ALWAYS BE FOLLOWED.

Supplemental Safety and Health: USERS OF THE "L" VERSION TO CONSULT THE "LR" VERSION OF FOR FURTHER INFO(FP N). FIRE FIGHT PROC: TO FLUSH SPILLS AWAY FROM EXPOSURE. FOR RUNOFF FROM FIRE CONTROL OR DILUTION FROM ENTERING STREAMS , SEWERS OR DRINKING WATER SUPPLY. SPILL PROC: TO COAST GUARD TOLL FREE #: (800) 424-8802.

Physical/Chemical Properties

B.P. Text: >600F
,>316C
Vapor Pres: <0.1
Spec Gravity: 0.87
Solubility in Water: NEGLIGIBLE
Appearance and Odor: AMBER LIQUID W/MILD ODOR.

Reactivity Data

Stability Indicator: YES
Stability Condition To Avoid: EXTREME HEAT.
Materials To Avoid: STRONG OXIDIZERS.
Hazardous Decomposition Products: CARBON MONOXIDE.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT RELEVA

NT.
=====

Toxicological Information
=====

Ecological Information
=====

MSDS Transport Information
=====

Regulatory Information
=
=====

Other Information
=====

Transportation Information
=====

Responsible Party Cage: 3U728
Trans ID NO: 103313
Product ID: 1 FORMULA 15W-50
MSDS Prepared Date: 05/16/1993
Review Date: 09/15/1995
MFN: 1
Multiple KIT Number: 0
Review IND
: Y
Unit Of Issue: CO
Container QTY: 0
Type Of Container: PAIL
=====

Detail DOT Information
=====

DOT PSN Code: ZZZ
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

Detail IMO Information
=====

IMO PSN Code: ZZZ
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF T

RANSPORTATION

Detail IATA Information

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail AFI Information

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

HAZCOM Label

Product ID: 1 FORMULA 15W-50

Cage: 3U728

Company Name: MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Street: 3225 GALLOWS ROAD

City: FAIRFAX VA

Zipcode: 22037

Health Emergency Phone: 800-424-9300(CHEMTREC)

Label Required IND: Y

Date Of Label Review: 04/24/1995

Status Code: C

Label Date: 04/24/1995

Origination Code: G

Chronic Hazard IND: Y

Eye Protection IND: YES

Skin Protection IND: YES

Signal Wo

rd: CAUTION

Respiratory Protection IND: YES

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: Slight

Reactivity Hazard: None

Hazard And Precautions: COMBUSTIBLE. ACUTE: SLIGHT EYE IRRITATION. SLIGHT SKIN IRRITATION. CHRONIC: STUDIES HAVE SHOWN THAT MICE DEVELOPED SKIN CANCER AFTER RPTD APPLIC OF USED GASOLINE ENGINE OIL TO SKIN FOR THE LIFETIME OF ANIMALS.

Disclaimer (provided with this information by the compiling agencies): T

his

information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who

is not a military or civilian employee of the

United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.