

CARBORUNDUM CO THE, FIBERS DIVISION -- FIBERFRAX ROPE -- 5330-00-872-6982

=====  
Product Identification  
=====

Product ID:FIBERFRAX ROPE

MSDS Date:07/29/1994

FSC:5330

NIIN:00-872-6982

MSDS Number: BXJVM

=== Responsible Party ===

Company Name:CARBORUNDUM CO THE, FIBERS DIVISION

Box:808

City:NIAGARA FALLS

State:NY

ZIP:14302-0337

Country:US

Info Phone Num:716-278-2183

Emergency Phone Num:716-278-6233

C

AGE:10646

=== Contractor Identification ===

Company Name:CARBORUNDUM CO THE

Address:P O BOX 337

Box:City:NIAGARA FALLS

State:NY

ZIP:14302-0337

Country:US

Phone:716-278-6233

CAGE:10646

=====  
Composition/Information on Ingredients  
=====

Ingred Name:REFRACTORY FIBERS, ALUMINOSILICATE (PER

MSDS:ALUMINOSILICATE (VITREOUS))

CAS:142844-00-6

Fraction by Wt: 75-85%

Other REC Limits:NONE RECOMMENDED

Ingred Name:VISCOSE RAYON

CAS:61788-77-0

Fraction by Wt: 15-25%

Other REC Limits:N

# ONE RECOMMENDED

## ===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:UNKNOWN IARC:YES  
Health Hazards Acute and Chronic:WARNING!POSSIBLE CANCER HAZ BY  
INHAL.MAY BE HARMFUL IF INHALED.HAZ DEPENDS ON DURATION/LEVEL OF  
EXPO.MAY BE IRRIT TO SKIN/EYES/RESP TRACT.INGEST:UNLIKELY.IF INGEST  
IN SUFFICIENT QUANT MAY CAUSE GI DIS TURBANCES.SKIN/EYE:SLIGHTLY TO  
MODERATELY IRRIT.IRRIT,INF  
LAMMATION.ABRASIVE ACTION MAY CAUSE  
DAMAGE TO EYES OUTER SURFAC  
Explanation of Carcinogenicity:PER MSDS:IARC CLASSIFIED CERAMIC  
FIBER,FIBROUS GLASSWOOL,MINERAL WOOL AS POSSIBLE HUMAN CARCINOGENS  
(GROUP 2B).CA PROP65  
Effects of Overexposure:INGEST:IRRIT, NAU, VAOMIT, ABDOMINAL PAIN,  
DIARR. SKIN:IRRIT, RASH. EYE:IRRIT. INHAL: RESP TRACT IRRIT.  
Medical Cond Aggravated by Exposure:PRE-EXISTING MED CONDITIONS MAY BE  
AGGRAVATED BY EXPO; SPECIFICALLY BRONCHIAL HYPER-REACTIVITY &  
CHRONIC BRONCHIAL OR LUNG DISEASE.

## ===== First Aid Measures =====

First Aid:INGEST:PREFERRED METHOD OF ELIMINATION IS THRU NATURAL GI  
ELIMINATION.DRINK EXTRA WATER.GI SYMPTOMS DEVELOP GET MED ATTN.  
SKIN:REMOVE CONTAMIN CLOTH.WASH THOROUGHLY W/SOAP/WATER.DO NOT  
RUB/SCRATCH.USI NG SKIN CREAM/LOTION AFT WASHING MAY  
BEHELPFUL.IRRIT PERSISTS GET MED ATTN. EYE:FLUSH IMMED W/LG AMTS OF  
WATER FOR @LEAST 15MINS OPENING EYELIDS.DO NOT RUB.IRRIT  
PERSISTS  
GET MED ATTN. INHAL:(SUPPLE)

## ===== Fire Fighting Measures =====

Flash Point:NON-COMBUSTIBLE  
Autoignition Temp:Autoignition Temp Text:NONE  
Extinguishing Media:USE EXTINGUISHING AGENT SUITABLE FOR TYPE OF  
SURROUNDING FIRE.  
Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER. HOWEVER USE  
APPROPRIATE PPE AS CONDITIONS WARRANTS.  
Unusual Fire/Explosion Hazard:NONE.

## ===== Accidental Release Measures =====

Spill R

cleaning Procedures:USE VAC SUCTION W/HEPA FILTERS.USE WET SWEEPING/DUST SUPPRESSANT WHERE SWEEPING IS NECESSARY.AVOID CLEAN UP PROCEDURES THAT MAY RESULT IN WATER POLLUTION.PERSONAL SAFETY/HNDLG/EXPO RECOMMENDATIONS DESCRIBED IN MSDS WHEN EXPOSED DURING CLEAN UP.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:HNDL W/CAUTION.AVOID UNNECESSARY CUT/TEAR OF MATERIAL TO MINIMIZE AIRBORNE DUST GENERATION.DO NOT TOUCH EYES W/CONTAMINATED BODY PARTS/MATERIAL.PKG MAY CONTAIN RESIDUE.

Other Precautions:PRODUCT UNDERGOES PARTIAL CONVERSION TO CRISTOBALITE(FORM OF CRYSTALLINE SILICA)@>1800F.RX OCCURS @FURNACE LINING HOT FACE-BECOMES MORE FRIABLE.AMT DEPENDS ON TEMP/DURATION.DO NOT USE AIR BLOW/DRY SWEEP SHOULD NOT BE USED.CAN USE DUST SUPPRESSANT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE EXCEEDS RECOMMENDED EXPOSURE GUIDELINE OF 100 FT

PER/CC OF AIR(8HR TWA) & ENGINEER CONTROL NOT FEASIBLE RESPIRATORY PROTECTION MUST BE USED. USE RESPIRATORY PROTECTION IF RESPIRATORY IRRITATION IS EXPERIENCED WHEN AIRBORNE CONCENTRATIONS ARE UNKNOWN/MATERIAL EXPOSURE TO TEMPERATURE >1800F.NIOSH/MSHA (SUPPLEMENTAL)

Ventilation:PROPERLY DESIGNED/OPERATED ENGINEER CONTROL MOST EFFECTIVE METHODS FOR MINIMIZING AIRBORNE DUST/FIBER.

Protective Gloves:GLOVES.

Eye Protection:SAFETY GLASSES,CHEMICAL GOGGLES.

Other Protective Equipment:CONTACT LENSES SHOULD NOT BE WORN UNLESS CHEMICAL GOGGLES ARE WORN.EYEWASH.HATS/FULL BODY COVERING TO PREVENT SKIN CONTACT.

Work Hygienic Practices:WASHABLE/DISPOSABLE CLOTHING MAY BE USED.DON'T TAKE UNWASHED WORK CLOTH HOME & WASH SEPARATELY-RINSE WASH MACHINE AFTER.

Supplemental Safety and Health

1ST AID:REMOVE FROM EXPOSURE TO FRESH AIR.SOME MAY BE SENSITIVE TO FIBER INDUCED RESPIRATORY TRACT IRRITATION.SYMPTOMS DEVELOP SEEK MEDICAL ATTENTION.BREATHING DIFFICULT ADMINISTER OXYGEN TIL MEDICAL ASSISTANCE CAN BE RENDERED. RESPIRATORY PROTECTION:AS PROVED.LEVELS UNKNOWN MINIMUM PROTECTION USE 1/2 MASK AIRPURIFYING RESPIRATORY PROTECTION W/HEPA FILTER

===== Physical/Chemical Properties =====

HCC:N1

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:NONE.

===== Disposal Considerations =====

Was

te Disposal Methods:NO SPECIAL REPORTING RQMTS FOR MATL RELEASES  
UNDER CERCLA 40CFR302/SARA 40CFR355.THERE MAY BE SPECIFIC REPORTING  
RQMTS @LOC/REGIONAL/STATE LEVEL PERTAINING TO RELEASES.AS SUPPLIED  
NOT HAZ WASTE.COULD BECOME HAZ WASTE IF MIXED W/HAZ.CHECK ALL  
REGS/LAW

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.