

ENERGIZER POWER SYSTEMS -- ENERGIZER RECHARGEABLE POWER SYSTEMS BATTERY --
6140-01-165-2073

===== Product Identification =====

Product ID:ENERGIZER RECHARGEABLE POWER SYSTEMS BATTERY

MSDS Date:11/29/1994

FSC:6140

NIIN:01-165-2073

MSDS Number: BXJXR

=== Responsible Party ===

Company Name:ENERGIZER POWER SYSTEMS

Address:US HIGHWAY 441N

City:ALACHUA

State:FL

ZIP:32615

Country:US

Info Phone Num:904-462-3911 OR 216-835-7368

Emergency Phone Num:904-462-3911

Preparer

's Name:JOANN RAULERSON

CAGE:EO263

=== Contractor Identification ===

Company Name:ENERGIZER POWER SYSTEM, DIV. OF EVEREADY BATTERY

Address:US HIGHWAY 441N

Box:City:ALACHUA

State:FL

ZIP:32615

Country:US

Phone:440-835-7368

CAGE:EO263

Box:UNKNOWN

CAGE:ENER1

===== Composition/Information on Ingredients =====

Ingred Name:CADMIUM OXIDE (SARA III) THE CADMIUM INGREDIENTS (1, 2 &
3) TOTAL 13 TO 22%

CAS:1306-19-0

RTECS #:EV1925000

Fraction by Wt: 13-22%

Other REC Limits:NONE RECOM

MENDED
OSHA PEL:0.2 MG (CD)/M3 DUST
ACGIH TLV:0.01 MG(CD)/M3; 9394

Ingred Name:CADMIUM HYDOXIDE
CAS:21041-95-2
Fraction by Wt: SEE #1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.2 MG/M3 (AS CD)
ACGIH TLV:0.01 MG/M3 (AS CD)

Ingred Name:CADMIUM HYDROXIDE
CAS:21041-95-2
Fraction by Wt: SEE #1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.05 MG CD/M3
ACGIH TLV:0.05 MG CD/M3

Ingred Name:COBALT (SARA 313) COBALT INGREDIENTS (4, 5 & 6) TOTAL 0.5
TO 2%.
CAS:7440-48-4
RTECS #:GF8750000
Fraction
by Wt: 0.5-2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG/M3
ACGIH TLV:0.02 MG/M3; A3; 9495

Ingred Name:COBALT HYDROXIDE
CAS:21041-93-0
RTECS #:GG0904500
Fraction by Wt: SEE #4%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.05 MG/M3 (CO)
ACGIH TLV:0.05 MG/M3 (CO)

Ingred Name:COBALT OXIDE
CAS:1307-96-6
RTECS #:GG2800000
Fraction by Wt: SEE #4%
Other REC Limits:NONE RECOMMENDED

Ingred Name:NICKEL (SARA 313) (CERCLA) THE NICKEL INGREDIENTS (7, 8 &
9) TOTAL 20 TO 32%.
CAS:7440-02-0
RTEC

S #:QR5950000
Fraction by Wt: 20-32%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9495

Ingred Name:NICKEL OXIDE
CAS:1313-99-1
RTECS #:QR8400000
Fraction by Wt: SEE #7%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3 AS NI
ACGIH TLV:1 MG/M3 AS NI

Ingred Name:NICKEL HYDROXIDE (SARA 313) (CERCLA)
CAS:12054-48-7
RTECS #:QR7040000
Fraction by Wt: SEE #7%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG(NI)/M3
ACGIH TLV:0.1 MG(NI)/M3; 9495
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10
LBS

Ingred Name:POTASSIUM HYDROXIDE (CERCLA)
CAS:1310-58-3
RTECS #:TT2100000
Fraction by Wt: 0-4%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C 2 MG/M3
ACGIH TLV:C 2 MG/M3; 9495
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:SODIUM HYDROXIDE (CERCLA)
CAS:1310-73-2
RTECS #:WB4900000
Fraction by Wt: 0-4%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:C 2 MG/M3; 9495
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

=

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:UNDER NORMAL CONDITIONS OF USE THE BATTERY IS HERMETICALLY SEALED. BATTERY IS CONSIDERED BY MFR TO BE AN ARTICLE AS DEFINED BY OSHA. IF BATTERY CASE IS BROKEN, CONTENTS MAY CAUSE IRRITATION &/OR BURN S TO BODY TISSUES CONTACTED. CONTENTS CONTAIN TOXIC COMPOUNDS.

Explanation of Carcinogenicity:NICKEL,CADMIUM,COBALT & THEIR COMPOUNDS ARE LISTED AS POSSIBLE CARCINOGENS BY IARC, NTP & OSHA. SEE INDIVIDUAL REPORTS.

Effects of Overexposure:SYMPTOMS OF CONTACT W/BATTERY INTERNALS:
INHALED:COUGHING, WHEEZING, SHORTNESS OF BREATH.
INGESTED:SALIVATION, CHOKING, NAUSEA, PERSISTENT VOMITING, DIARRHEA, ABDOMINAL PAIN, DIZZINESS, FAINTNESS, UNCONSCIOUSNESS.
SKIN:BURNS, ITCHING, REDNESS, SWELLING, RASH. EYES:BURNS, PAIN, REDNESS, TEARING.

Medical Condition Aggravated by Exposure:MFR GAVE NO INFORMATION ON MSDS.

===== First Aid Measures =====

First Aid:INGESTION:DO NOT INDUCE VOMITING NOR GIVE FOOD OR DRINK. GET MEDICAL ATTENTION & CALL NATIONAL BATTERY INGESTION HOTLINE (202-625-3333) COLLECT, DAY OR NIGHT. INHALATION:PROVIDE FRESH AIR AND CALL A DOCTOR. SKIN:REMOVE CONTAMINATED CLOTHING & WASH SKIN WITH SOAP AND WATER. SEEK MEDICAL ATTENTION IF NEEDED. EYE:FLUSH EYES THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NON FLAMMABLE
Extinguishing Media:ANY CLASS OF EXTINGUISHING MEDIUM MAY BE USED. COOL EXTERIOR OF BATTERIES IF EXPOSED TO FIRE TO PREVENT RUPTURE.
Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR SCBA. BURNING NICKEL-CADMIUM BATTERIES CAN PRODUCE TOXIC FUMES INCLUDING, NICKEL, NICKEL OXIDES, CADMIUM, CADMIUM OXIDES & COBALT OXIDE
Unusual Fire/

Explosion Hazard:MFR GAVE NO INFORMATION ON MSDS.

===== Accidental Release Measures =====

Spill Release Procedures:MFR GAVE NO INFORMATION ON MSDS.

Neutralizing Agent:MFR GAVE NO INFORMATION ON MSDS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, WELL VENTILATED AREA.
ELEVATED TEMPERATURES CAN RESULT IN SHORTENED BATTERY LIFE. DO NOT
OBSTRUCT SAFETY RELEASE VENTS ON BATTERIES.

Other Pre

cautions:IF SOLDERING OR WELDING IS REQUIRED, USE OF TABBED
BATTERIES IS RECOMMENDED. IF THIS CANNOT BE DONE, CONSULT YOUR
EVEREADY BATTERY COMPANY REPRESENTATIVE FOR PROPER PRECAUTIONS TO
PREVENT SEAL DAMAGE OR SHORT CIRCUIT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NECESSARY UNDER NORMAL CONDITIONS.

Ventilation:NOT NECESSARY UNDER NORMAL CONDITIONS.

Protective Gloves:NOT NECESSARY UNDER NORMAL CONDITIONS.

Eye Protection:NOT N

CESSARY UNDER NORMAL CONDITIONS.

Other Protective Equipment:MFR GAVE NO INFORMATION ON MSDS. WEAR SAFETY
GLASSES & NEOPRENE OR RUBBER GLOVES WHEN HANDLING LEAKING & OPEN
BATTERIES.

Work Hygienic Practices:MFR:? HMIS:USE GOOD INDUSTRIAL HYGIENE
PRACTICES. DO NOT OBSTRUCT SAFETY RELEASE VENTS ON BATTERIES.

Supplemental Safety and Health

BATTERY IS CAPEABLE OF HIGH SHORT CERCUIT CURRENT & BATTERY MAY BECOME
HOT ENOUGH TO BURN IF SHORTED FOR MORE THAN A SHORT PERIOD. -
BATTERY

IS MADE TO BE RECHARGED. USE RECOMMENDED CHARGER. IMPROPER
CHARGING MAY RESULT IN DAMAGE TO BATTERY &/OR BURNS TO USER. -
DURING CHARGING BATTERIES EVOLVE EXPOLSIVE HYDROGEN.

===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NONE

Appearance and Odor:MFR GAVE NO INFORMATION ON MSDS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.

Stability Condi

on to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:NICKEL, NICKEL OXIDES, CADMIUM,
CADMIUM OXIDES, & COBALT OXIDE FUMES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF I/A/W ALL APPLICABLE FEDERAL, STATE
AND LOCAL REGULATIONS. THIS BATTERY, AS A WASTE, IS REGULATED BY
THE RESOURCE CONSERVATION AND RECOVERY ACT [RCRA] AS A D006
[CADMIUM] HAZARDOUS WASTE.

Disclaimer (provided with this information
by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.