

ALCOTEC WIRE CO SUB OF ALCOA WELD WIRE INC. -- WELDING WIRE, ALLOY 4043 --
3439-00-254-5030

===== Product Identification =====

Product ID:WELDING WIRE, ALLOY 4043
MSDS Date:06/03/1992
FSC:3439
NIIN:00-254-5030
MSDS Number: BXPTC
=== Responsible Party ===
Company Name:ALCOTEC WIRE CO SUB OF ALCOA WELD WIRE INC.
Address:2750 AERO PARK DR.
Box:1320
City:TRAVERSE CITY
State:MI
ZIP:49685
Country:US
Info Phone Num:616-941-4111 / 616-941-9154 (FAX)
Emergency Phone Nu
m:616-941-4111 / 412-553-4001
Preparer's Name:STEPHEN L. ANDERSON,PATNR
CAGE:7Z608

=== Contractor Identification ===

Company Name:ALCOTEC WIRE CO SUB OF ALCOA WELD WIRE INC.
Address:2750 AERO PARK DR.
Box:1320
City:TRAVERSE CITY
State:MI
ZIP:49686
Country:US
Phone:412-553-4649; 616-941-4111
CAGE:7Z608

===== Composition/Information on Ingredients =====

Ingred Name:SILICON
CAS:7440-21-3
RTECS #:VW0400000
Fraction by Wt: 4.5-6.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/

M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9495

Ingred Name:IRON
CAS:7439-89-6
RTECS #:NO4565500
Fraction by Wt: 0.8%
Other REC Limits:NONE RECOMMENDED

Ingred Name:COPPER (SARA 313) (CERCLA)
CAS:7440-50-8
RTECS #:GL5325000
Fraction by Wt: 0.30%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1MG/M3 FUME/1 DUST
ACGIH TLV:0.2 MG/M3 FUME; 9495
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:MANGANESE (SARA 313)
CAS:7439-96-5
RTECS #:OO9275000
Fraction by Wt: 0.05%
Other REC Limits:NONE RECOMMENDED
OS
HA PEL:C 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9495

Ingred Name:MAGNESIUM
CAS:7439-95-4
RTECS #:OM2100000
Fraction by Wt: 0.05%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ZINC (SARA 313) (CERCLA)
CAS:7440-66-6
RTECS #:ZG8600000
Fraction by Wt: 0.10%
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM
CAS:7440-32-6
RTECS #:XR1700000
Fraction by Wt: 0.20%
Other REC Limits:NONE RECOMMENDED

Ingred Name:OTHERS, EACH (INCLUDING BERYLLIUM INGRED #9) (TO

TAL:0.15%)
Fraction by Wt: 0.05%
Other REC Limits:NONE RECOMMENDED

Ingred Name:BERYLLIUM (SARA 313) (CERCLA) SHALL NOT EXCEED 0.0008%.
CAS:7440-41-7
RTECS #:DS1750000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.002 MG/M3, Z-2
ACGIH TLV:.002 MG/M3, A2; 9495

Ingred Name:ALUMINUM (SARA 313)
CAS:7429-90-5
RTECS #:BD0330000
Fraction by Wt: BALANCE
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 DUST
ACGIH TLV:10 MG/M3 DUST; 9495

===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:WELDING FUMES,INTENSE ULTRAVIOLET
RADIATION,WELDING ARCS CAUSES HEALTH HAZ.MUC
MEMB/PULM/EYES/NOSE/THROAT/SKIN IRRIT,PULM
CHANGES,CONGESTION,EDEMA,FLASH BURNS TO EYES/SKIN.FORMATION OF
METHEMOGLOBIN & SUBSEQUENT ACTION ON CNS FRM NITRIC OXIDE.INHAL
>100PPM NITROGEN MONOXIDE CAN BE FATAL.CR CMPDS:NASAL/LUNG
CANCER.(SUP)

Ex
planation of Carcinogenicity:PER MSDS:WELDING FUMES,NICKEL,HEXAVALENT
CHROMIUM CMPDS,BERYLLIUM CMPDS,LEAD,
Effects of Overexposure:IRRIT OF EYE/SKIN/NOSE/THROAT/RESP TRACT.GI
DISTURBANCES.EYE/SKIN FLASH BURNS,CNS EFFECTS,METAL FUME
FEVER,METALLIC TASTE,LOSS OF SLEEP,APPETITE
LOSS,TIREDENSS,IRRITABILITY.PNEUMONITIS(INFLAMM OF LUNG
TISS),BERYLLIOSIS(PROGRESSIVE LUNG
DISEASE),NEUROPATHY,ANEMIA,CHROMOSOMAL CHANGES.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFA

CTURER.

===== First Aid Measures =====

First Aid:INHAL:IMMED REMOVE TO FRESH AIR. BREATH STOPPED PROVIDE OXYGEN & RESPIRATION. CONSULT PHYSICIAN. SKIN/EYES:IRRITATION DEVELOPS CONSULT PHYSICIAN.

===== Fire Fighting Measures =====

Extinguishing Media:USE CLASS D EXTINGUISHING AGENTS OR DRY SAND ON FIRES.

Fire Fighting Procedures:USE COARSE WATER SPRAY ON CHIPS/TURNINGS/ETC.DO NOT USE HALOGENATED EXTINGUISHING AGENTS ON SM CHIPS/FINES.

Unusual Fire/Explosion Hazard:DOES NOT PRESENT FIRE/EXPLO HAZ UNDER NORMAL CONDITIONS.SM CHIPS/FINE TURNINGS/DUST MAY IGN READILY.DUST CLOUDS MAY BE EXPLOSIVE;PREVENT FORMATION OF DUST CLOUD

===== Accidental Release Measures =====

Spill Release Procedures:COLLECT SCRAP FOR REMELTING.

===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE EXPO LIMIT IS OR MAY BE EXCEEDED USE NIOSH APPROVED RESP PROTECTION. SELECT APPROPRIATE RESP (FUME RESP,HIGH EFFICIENCY DUST & FUME RESP,SUPPLIED-AIR RESP,ETC)BASED ON CONCEN OF ACTUAL OR POTENTIAL AIRBORNE CONTAMINANTS PRESENT.

Ventilation:USE W/ADEQUATE VENTILATION TO MEET EXPO LIMITS.FUMES/DUST PROVIDE GEN/LOC EXHA VENTI TO MEET BE PEL R EQMTS.

Protective Gloves:AS REQUIRED FOR WELDING.

Eye Protection:AS REQUIRED FOR WELDING.

Other Protective Equipment:WELDERS SHOULD USE APPROPRIATE EQPMT.REFER TO OSHA 29CFR1910.252.REFER TO 29CFR1910.1025 FOR INDUST HYG STD FOR PB HNDLG

Work Hygienic Practices:ADVISE PERSONNEL ASSIGNED TO LAUNDER BE CONTAMIN CLOTH OF HAZ.PRACTICE GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

DENSITY:0.1LB/IN3. HEALTH HAZ:COPPER:NAU,METAL FUME FEVER,RESP TRACT IRRIT.NICKEL DUST/FUME:PNEUM

OCULOSIS,CANCER.BERYLLIUM:TOXIC BY
INHAL,PNEUMONITIS,BERYLLIOSIS,SYSTEMIC BERYLLIUM DISEASE.LEAD:NEURO
PATHY,GI DISTURB,ANEMIA,CHROMOSOMAL CHANGES.

===== Physical/Chemical Properties =====

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:970F,521C

Solubility in Water:NONE

Appearance and Odor:SILVERY COLOR, SOLID WELDING ELECTRODE, NO ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MA

NUFACTURER.

Stability Condition to Avoid:PREVENT FORMATION OF DUST CLOUD.

Hazardous Decomposition Products:OZONE, OXIDES OF NITROGEN. HEXAVALENT
CHROMIUM CMPDS,

===== Disposal Considerations =====

Waste Disposal Methods:IF MATL IS TO BE DISPOSED TCLP LEACHATE TESTING
FOR CHROMIUM & REACTIVITY, EXPLOSIVE SUCATEGORY TESTING IS
RECOMMENDED TO DETERMINED IF WASTE IS RCRA HAZ.

Disclaimer (provided with this information by the compiling agencies):

This

information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.