View NSN Online: https://aerobasegroup.es/nsn/9150-00-935-4019

## ROYAL LUBRICANTS COMPANY INC. -- ROYCO 13E -- 9150-00-935-4019

Product ID:ROYCO 13E MSDS Date:08/03/1993

FSC:9150

NIIN:00-935-4019

MSDS Number: BXQFS === Responsible Party ===

Company Name: ROYAL LUBRICANTS COMPANY INC.

Address:6 CAMPUS DR

City:PARSIPPANY

State:NJ ZIP:07054 Country:US

Info Phone Num:201-887-7410

Emergency Phone Num:201-887-7411

CAGE:07950 === Cont

ractor Identification ===

Company Name: CONVOY OIL CORP Address: 1410 N FRONT STREET

Box:29366

City:PHILADELPHIA

State:PA ZIP:19125 Country:US

Phone:215-739-5281

CAGE:6A438

Company Name: ROYAL LUBRICANTS COMPANY INC.

Address:215 MERRY LN

Box:518

City: EAST HANOVER

State:NJ ZIP:07936 Country:US

Phone:973-887-7411/7410

CAGE:07950

====== Composition/Information on Ingredients ========

Ingred Name: SILICONE

CAS:63148-52-7

Fraction by Wt: 50-60%

Other REC Limits: NONE RECOMMENDED

Ingred Na

me:POLYTETRAFLUORO ETHYLENE (TEFLON) CAS:116-14-3 RTECS #:KX4025000
Fraction by Wt: 40-45% Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST
Ingred Name:MINOR ADDITIVES Fraction by Wt: 200F,>93C Lower Limits:N/AV Upper Limits:N/AV Extinguishing Media:WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.DO NOT USE DIRECT STREAM OF WATER.PRODUCT FLOATS & REIGNITES ON SURFACE
Fire Fighting Procedures:MATERIAL WILL NOT BURN UNLESS PREHEATED. DO NOT ENTER CON
FINED FIRE SPACE WITHOUT FULL BUNKER GEAR, INCLUDING
POSITIVE PRESSURE NIOSH APPROVED SCBA. Unusual Fire/Explosion Hazard:COOL FIRE EXPOSED CONTAINERS WITH WATER.
======== Accidental Release Measures =========
Spill Release Procedures:MAY BURN ALTHOUGH NOT READILY IGNITABLE.  ***SMALL SPILLS***TAKE UP WITH AN ABSORBANT MATERIAL AND DISPOSE OF PROPERLY.
========== Handling and Storage ============
Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM FLAMES AND HIGH TEMPERATURES Other Precautions:THIS PRODUCT IS CONSIDERED TO BE AN OIL UNDER EPA SECT. 311,SPILL INTO OR LEADING TO SURFACE WATERS THAT CAUSE A SHEEN MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER AT 800-424-8802.
===== Exposure Controls/Personal Protection ========
·
Respiratory Protection:OVEREXPOSURE-USE NIOSH-APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE. IN ACCORD WITH 29CFR1910.

134 USE EITHER AN

ATMOSPHERE SUPPLYING RESPIRATOR OR AN AIR PURIFYING RESPIRATOR FOR ORGANIC VAPORS AND PAR TICULATES.

Ventilation: NONE SPECIFIED BY MANUFACTURER.

Protective Gloves: NITRILE RUBBER GLOVES

Eye Protection: WEAR SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:WEAR GLOVES & OTHER CLOTHING AS REQUIRED TO MINIMIZE CONTACT. HAVE EMERGENCY EYE WASH AND SAFETY SHOWER AVAILABLE.

Work Hygienic Practices:WASH WITH SOAP & WATER BEFORE EATING, DRINKING OR SMOKING. LAUND

ER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

MINIMIZE SKIN AND EYE CONTACT.

========= Physical/Chemical Properties ===========

HCC:V6

Boiling Pt:B.P. Text:N/AV Melt/Freeze Pt:M.P/F.P Text:N/AV Decomp Temp:Decomp Text:N/AV Vapor Pres:N/AV Vapor Density:N/AV

Spec Gravity: