## 

Product ID:01893 TDH-OIL MSDS Date:01/04/1995

FSC:9150

NIIN:01-177-9438

MSDS Number: BXQGQ === Responsible Party ===

Company Name: TEXACO INC CORPORATE HQ

Address:2000 WESTCHESTER AVE

City:WHITE PLAINS

State:NY ZIP:10604 Country:US

Info Phone Num:914-831-3400 ,914-838-7204 Emergency Phone Num:914-831-3400 ,EXT.406

CAGE:59595

=== Contractor Identification ===

Company

Name:TEXACO INC CORPORATE HQ Address:2000 WESTCHESTER AVE

City:WHITE PLAINS

State:NY ZIP:10604 Country:US

Phone:914-253-4000

CAGE:59595

Company Name: TEXACO REFINING AND MARKETING INC

Address:1111 RUSK ST Box:City:HOUSTON

State:TX

ZIP:77002-3310 Country:US

Phone:713-650-5206

CAGE:2R503

======= Composition/Information on Ingredients ========

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT DEWAXED (MILD), HEAVY PARAFFINIC

CAS:64742-65-0

RTECS #:PY8038500 Fraction by Wt: 35 -50%

Other REC Limits: NONE RECOMMENDED

Ingred Name: DISTILLATES, SOLVENT-DEWAXED LIGHT PARAFFINIC

CAS:64742-56-9 RTECS #:PY8039500 Fraction by Wt: 35-50%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:300 PPM ACGIH TLV:300 PPM

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED

(MILD), HEAVY PARAFFINIC

CAS:64742-54-7 RTECS #:PY8035500 Fraction by Wt: 3-10%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:PHOSPHORODITHOIC ACID, O-O-D1

C1-14-ALKYL ESTERS, ZINC

**SALTS (2:1) (ZDDP)** 

CAS:68649-42-3 Fraction by Wt: 1-3%

Other REC Limits: NONE RECOMMENDED

Ingred Name: ADDITIVES Fraction by Wt: 1-3%

Other REC Limits: NONE RECOMMENDED

Ingred Name: MINERAL OIL

CAS:64742-53-6 RTECS #:PY8036000 Fraction by Wt: 1-3%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name: METHACRYLIC ACID, COPOLYMER OF BUTYL, LAURYL & STEARYL

**ESTERS** 

CAS:68516-84-7 Fraction by Wt: 1-3% Other REC Limits:NO

## NE RECOMMENDED

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5.00 G/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: EYES-MAY CAUSE MINIMAL IRRITATION, SKIN-BRIEF CONTACT MAY CAUSE SLIGHT IRRITATION. INHALATION-MAY CAUSE TEMPORARY IRRITATION OF THE NOSE AND THROAT. CHRONIC: NO ADVERSE EFFECTS HAVE BEEN DOCUME NDED IN HUM ANS AS A RESULT OF CHRONIC EXPOSURE. Explanation of Carcinogenicity: NOT CARCINOGENIC. Effects of Overexposure: EYES-MAY EXPERIENCE TEMPORARY DISCOMFORT. SKIN-LOCAL REDNESS AND SWELLING. INHALATION-HEADACHE, NAUSEA AND DROWSINESS. INGESTION-ABDOMINAL DISCOMFORT, NAUSEA AND DIARRHEA MAY OCCUR. Medical Cond Aggravated by Exposure:BECAUSE OF ITS IRRITATING PROPERTIES, REPEATED SKIN CONTACT MAY AGGRAVATE AN EXISTING DERMATITIS. ===== First Aid Measures ==== First Aid: EYES-FLUSH WITH WATER FOR SEVERAL MIN. GET MEDICAL AID. SKIN-WASH SKIN WITH PLENTY OF SOAP & WATER FOR SEVERAL MIN. GET MEDICAL AID. INGESTION-IF MORE THAN SEVERAL MOUTHFULS ARE SWALLOWED, GIVE 2 GLAS SES OF WATER (16 OZ) GET MEDICAL AID. INHALATION-REMOVE TO FRESH AIR. GET MEDICAL AID IF BREATHING BECOMES DIFFICULT OR RESPIRATORY IRRITATION PERSISTS. Flash Point Method:COC lash Point:380F,193C Extinguishing Media: USE WATER SPRAY, DRY CHEMICAL, FOAM, OR CARBON DIOXIDE TO EXTINGUISH FLAMES. USE WATER SPRAY TO COOL FIRE EXPOSED CANS. Fire Fighting Procedures: WATER OR SPRAY MAY CAUSE FROTHING. NO SPECIAL EQUIPMENT OR PROCEDURES REQUIRED FOR FIREFIGHTERS. Unusual Fire/Explosion Hazard: HYDROGEN SULFIDE MAY BE RELEASED IF OVERHEATED. ======== Accidental Release Measures ============

Spill Release Procedures: VENTILATE AREA. AVOID BREATH

ING VAPOR. WEAR APPROPIATE PERSONAL PROTECTIVE EQUIPMENT, INCLUDING RESPIRATORY PROTECTION. CONTAIN SPILL IF POSSIBLE. WIPE UP OR ABSORB ON SUITABLE MATERIAL AND SHOVEL UP PREVENT ENTRY INTO SEWERS & WATERWAYS.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
=========== Handling and Storage =============
Handling and Storage Precautions:MINIMUM FEASIBLE HANDLING TEMPERATURES SHOULD BE MAINTAINED. PERIOIDS OF EXPOSURE TO HIGH TEMPERATURES SHOULD
BE MINIMIZED. AVOID WATER CONTAMINATION. Other Precautions:AVOID CONTACT WITH SKIN, EYES OR CLOTHING.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF EXPOSURE LIMITS ARE EXCEEDED, USE APPROPIATE NIOSH OR MSHA APPROVED AIR PURIFYING OR AIR SUPPLIED RESPIRATOR AFTER DETERMINING THE AIRBORNE CONCENTRATIONN OF THE CONTAMINANT. Ventilation:ADEQUATE TO MEET COMPONENT OCCUPATIONAL EXPOSURE LIMITS. Protective Gloves:WASH EXPOSED SKIN SEVERAL TIMES DAILY.
Eye Protection:SAFETY GLASSES, CHEMICAL TYPE GOGGLES. Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices:SOILED WORK CLOTHING SHOULD BE LAUNDERED OR DRY CLEANED. Supplemental Safety and Health
NONE
======================================
HCC:V6 Spec Gravity:0.8927 Viscosity:9.1 CST Solubility in Water:NOT DETERMINED Appearance and Odor:DARK RED LIQUID. PETROLEUM OIL ODOR.
========= Stability and Reactivity Data
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:TOXIC LEVELS OF CARBON MONOXIDE, CARBON DIOXIDE, IRRITATING ALDEHYDES & KETONES & COMBUSTION PRODUCTS OF ZINC, SULFUR.  ===================================

Waste Disposal Methods:THIS PRODUCT HAS BEEN EVALUATED FOR RCRA CHARACTERISTICS AND DOES NOT MEET THE CRITERIA OF A HAZARDOUS

## WASTE

IF DISCARDED IN ITS PURCHASED FORM. UNDER RCRA IT IS THE RESPONSIBILITY OF THE USER TO DETE RMINE AT THE POINT OF DISPOSAL IF ITS HAZARDOUS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.