

EXIDE CORP -- DRY CHARGE BATTERY -- 6140-00-539-8491

===== Product Identification =====

Product ID: DRY CHARGE BATTERY

MSDS Date: 09/01/1993

FSC: 6140

NIIN: 00-539-8491

MSDS Number: BXXKF

=== Responsible Party ===

Company Name: EXIDE CORP

Address: 9176 RED BRANCH RD

City: COLUMBIA

State: MD

ZIP: 21045-2059

Country: US

Info Phone Num: 301-381-8500

Emergency Phone Num: 301-381-8500 OR 215-378-0757

CAGE: 90660

==

= Contractor Identification =

Company Name: ENERSYS INC

Address: 8306 PATUXENT RANGE RS SUITE 103

Box: City: JESSUP

State: MD

ZIP: 20794-8609

Country: US

Phone: 301-381-8500 OR 215-378-0757

CAGE: 90660

===== Composition/Information on Ingredients =====

Ingred Name: LEAD (SARA III)

CAS: 7439-92-1

RTECS #: OF7525000

Fraction by Wt: 53% %

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 0.05 MG/M3; 1910.1025

ACGIH TLV: 0.15 MG/M3; DUST 9293

EPA Rpt Qty: 1 LB

DOT Rpt Qty: 1 LB

Ingred Name: ANTIMONY (S)

ARA III)
CAS:7440-36-0
RTECS #:CC4025000
Fraction by Wt: 0.2% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.5 MG/M3
ACGIH TLV:0.5 MG SB/M3; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ARSENIC (SARA III)
CAS:7440-38-2
RTECS #:CG0525000
Fraction by Wt: 0.003% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.5 MG/M3 (AS)
ACGIH TLV:0.01,A1 MG/M3; 9394
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:CALCIUM, METAL
CAS:7440-70-2
RTECS #:EV8040000
Fraction by Wt: 0.02% %
Other REC Limits:
NONE RECOMMENDED

Ingred Name:TIN
CAS:7440-31-5
RTECS #:XP7320000
Fraction by Wt: 0.06% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9293

Ingred Name:POLYPROPYLENE RUBBER
CAS:9003-07-0
Fraction by Wt: 5-6% %
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:150 UG/M3 ACGIH TLV FOR LEAD
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:HAZARDOUS EXPOSURE TO LEAD COMPOUNDS CAN OCCUR ONLY WHEN PRODUCT IS HEATED, OXIDIZED OR OTHERWISE PROCESSED OR DAMAGED TO CREATE DUST, VAPOR OR FUME. INHALATION OF LEAD DUST MAY CAUSE RESPIRATORY TRAC T IRRITATION. INGESTION MAY CUASE GASTROINTESTINAL DISTURBANCES. MAY CAUSE EYE IRRITATION.

Explanation of Carcinogenicity:CONTAINS INORGANIC ARSENIC [7440-38-2] AND LEAD WHICH ARE LISTED BY NTP AND IARC AND REGULATED BY OSHA AS CARCINOGENS.

Effects of Overexposure:ACUTE: HEADACHE, FATIGUE, ABDOMINAL PAIN, LOSS OF APPETITE, MUSCULAR ACHES AND WEAKNESS, SLEEP DISTURBANCES AND IRRITABILITY. CHRONIC: ANEMIA, NEUROPATHY--PARTICULARLY OF THE MOTOR NERVES WITH WRIST D ROP, KIDNEY DAMAGE, REPRODUCTIVE CHANGES IN BOTH MALES AND FEMALES.

Medical Cond Aggravated by Exposure:LEAD AND ITS COMPOUNDS CAN AGGRAVATE SOME FORMS OF KIDNEY, LIVER AND NEUROLOGIC DISEASES.

=====
===== First Aid Measures =====
=====

First Aid:INHALATION: REMOVE FROM EXPOSURE. GARGLE, WASH NOSE AND LIPS. CONSULT PHYSICIAN. INGESTION: CONSULT PHYSICIAN IMMEDIATELY. SKIN: WASH IMMEDIATELY WITH SOAP AND WATER. EYES: FLUSH IMMEDIATELY WITH LARG E AMOUNTS OF WATER FOR 15 MINUTES. CONSULT PHYSICIAN.

=====
===== Fire Fighting Measures =====
=====

Flash Point:NONFLAMMABLE

Lower Limits:4.1 % (H2)

Upper Limits:74.2% (H2)

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL

Fire Fighting

Procedures:WEAR FULL BODY PROTECTIVE CLOTHING AND SELF-CONTAINED BREATHING APPARATUS WITH POSITIVE PRESSURE AND FULL FACEPIECE.

Unusual Fire/Explosion Hazard:HIGHLY FLAMMABLE HYDROGEN GAS (H2) IS GENERATED DURING CHARGING AND OPERATION. TO AVOID RISK, KEEP IGNITION SOURCES AWAY FROM BATTERIES.

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:LEAD DUST SHOULD BE VACUUMED OR WET-SWEPT. USE CONTROLS WHICH MINIMIZE FUGITIVE EMISSIONS

. DO NOT USE COMPRESSED
AIR.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE BATTERIES IN COOL, DRY, WELL-
VENTILATED AREAS WITH IMPERVIOUS SURFACES AND ADEQUATE CONTAINMENT
IN THE EVENT OF SPILLS.

Other Precautions:BATTERIES SHOULD BE STORED UNDER ROOF FOR PROTECTION
AGAINST ADVERSE WEATHER CONDITIONS. SEPARATE FROM INCOMPATIBLE
MATERIALS. STORE AND HANDLE ONLY IN
AREAS WITH ADEQUATE WATER
SUPPLY AND SPILL CONTR OL. AVOID DAMAGE TO CONTAINERS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE REQUIRED UNDER NORMAL CONDITIONS.

Ventilation:STORE AND HANDLE IN WELL-VENTILATED AREA.

Protective Gloves:RUBBER OR PLASTIC ACID-RESISTANT

Eye Protection:CHEMICAL GOGGLES/FACE SHIELD

Other Protective Equipment:COVERALLS OR FULL-BODY COVERING DURING USE.
WHEN FILLING BATTERIES USE ACID RESISTANT APRON.

Work Hygi

enic Practices:HANDLE BATTERIES CAUTIOUSLY TO AVOID SPILLS.

MAKE CERTAIN VENT CAPS ARE ON SECURELY. AVOID CONTACT WITH INTERNAL
PARTS.

Supplemental Safety and Health

DO NOT ALLOW METALLIC MATERIALS TO SIMULTANEOUSLY CONTACT NEGATIVE AND
POSITIVE TERMINALS OF CELLS AND BATTERIES. FOLLOW MANUFACTURER'S
INSTRUCTIONS FOR INSTALLATION AND SERVICE.

=====
Physical/Chemical Properties
=====

HCC:N1

Boiling Pt:B.P. Text:>2516F,>138

Melt/Freeze Pt:M.P/F.P Text:

NOT GIVEN

Vapor Pres:NOT GIVEN

Vapor Density:NOT GIVEN

Spec Gravity:9.6 TO 11.3

Evaporation Rate & Reference:NIL

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLUSIH GRAY METAL; NO APPARENT ODOR

Percent Volatiles by Volume:0 %

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS, BASES, HALIDES, HALOGENATES, POTASSIUM NITRATE,
PERMANGANATE, PEROXIDES, REDUCING AGENTS, NASCENT HYROGEN

Stability Condition to Avoi

d:PROLONGED OVERCHARGE, SOURCES OF IGNITION

Hazardous Decomposition Products:TOXIC METAL FUME/VAPOR/DUST; CONTACT WITH STRONG ACID IN PRESENCE OF NASCENT HYDROGEN MAY GENERATE ARSINE GAS.

===== Disposal Considerations =====

Waste Disposal Methods:SEND SPENT BATTERIES TO SECONDARY LEAD SMELTER FOR RECYCLING. PLACE NEUTRALIZED SLURRY INTO SEALED CONTAINERS AND DISPOSE OF AS HAZARDOUS WASTE AS APPLICABLE. WASTE SHOULD BE MANAGED IN ACCORDANCE WITH APPROVED LOCAL, STATE AND FEDERAL REQUIREMENTS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.