

MICANITE & INSULATOR CO LTD -- APIEZON Q COMPOUND -- 8030-00-551-7860

===== Product Identification =====

Product ID:APIEZON Q COMPOUND

MSDS Date:10/01/1989

FSC:8030

NIIN:00-551-7860

MSDS Number: BXXKJ

=== Responsible Party ===

Company Name:MICANITE & INSULATOR CO LTD

Address:510 TOWNSHIP LINE RD

City:BLUE BELL

State:PA

ZIP:19422

Country:US

Info Phone Num:215-646-9200

Emergency Phone Num:215-646-92

00

CAGE:IO686

=== Contractor Identification ===

Company Name:BIDDLE INSTRUMENTS

Address:510 TOWNSHIP LINE RD

Box:City:BLUE BELL

State:PA

ZIP:19422-2701

Country:US

Phone:NOT AVAILABLE

CAGE:07239

Company Name:MICANITE & INSULATORS CO INC

Address:510 TOWNSHIP LINE RD

Box:City:BLUE BELL

State:PA

ZIP:19422

Country:US

Phone:215-646-9200

CAGE:IO686

===== Composition/Information on Ingredients =====

Ingred Name:NON-HAZARDOUS INGREDIENTS

OSHA PEL:N/K

ACGIH TLV:N/K

=====

==== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE & CHRONIC:NONE LISTED BY  
MANUFACTURER.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE KNOWN.

==== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O\*2/ARTF  
RESP) . SKIN:FLUSH W/COPIOUS AMOUNTS OF WATER. CALL MD . EYE:FLUSH  
WITH CLEAN WATER FOR @ LEAST 15 MINUTES. INGEST:DO NOT INDUCE  
VOMIT. OBTAIN MED ATTN.

==== Fire Fighting Measures =====

Flash Point:302F,150C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMIC POWDER, SAND OR EARTH.

Fire Fighting Procedures:NONE. USE NIOSH/MSHA APPROVED SCBA & FULL  
PROTECTIVE EQUIPMENT .

Unusua

I Fire/Explosion Hazard:NONE.

==== Accidental Release Measures =====

Spill Release Procedures:WIPE UP OR ABSORB WITH SAND, EARTH OR SAWDUST.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

==== Handling and Storage =====

Handling and Storage Precautions:NONE.

Other Precautions:NONE.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED. NIOSH/MSHA APPROVED RESPIRATOR  
AP

PROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:NOT REQUIRED.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective Equipment:ANSI APPRVD EMERGENCY EYE WASH & DELUGE  
SHOWER .

Work Hygienic Practices:WASH SKIN AFTER CONTACT AND GENERALLY OBSERVE  
GOOD STANDARDS OF HYGIENE.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Melt/Freeze Pt:M.P/F.P Text:113F,45

C

Vapor Pres:1X10-4@20C

Evaporation Rate & Reference:NEGLIG(BUTYL ACETATE =1)

Solubility in Water:INSOLUBLE

Appearance and Odor:GREY, ODORLESS PUTTY-LIKE SOLID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:NONE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ACCORDING TO  
FEDERAL, STATE AND LOCAL  
REGULATIONS FOR MINERAL OILS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the

suitability of this information to their particular situation.