Product ID:BRONZE PUTTY (BR)-RESIN, PART A. MSDS Date:07/01/1986 FSC:8030 NIIN:00-333-4534 Kit Part:Y MSDS Number: BXZGL === Responsible Party === Company Name: DEVCON CORP Address:30 ENDICOTT ST **City:DANVERS** State:MA ZIP:01923-3753 Country:US Info Phone Num:617-777-1100 Emergency Phone Num:617-777-1100 Preparer's Name:NONE CAGE:16059 === Contractor Identifica tion === Company Name: DEVCON CORP Address:30 ENDICOTT ST Box:City:DANVERS State:MA ZIP:01923-3753 Country:US Phone:1-508-777-1100 CAGE:16059

Ingred Name:BISPHENOL A-DIGLYCIDYL ETHER RESIN CAS:25068-38-6 RTECS #:SL6475000 Fraction by Wt: 10-30% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 11.4 G/KG. Routes of Entry: Inhalation:NO S First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL ATTENTION. SKIN: WASH AREA WITH SOAP AND WARM WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS. INHALATION: MOVE TO FRESH AIR. ADMINISTER OXYGEN IF BREATHING IS DIFFICULT. GET MEDICALATTENTION. INGESTION: DO NOT INDUCE VOMITING. ADMINISTER TWO GLASSES OF WATER. GET MEDICAL ATTENTION.

Flash Point Method:PMCC Flash Point:>400F,>204C Extinguishing Media:CARBON DIOXIDE, DRY CHEMICALS. POLYMER FOAMS FOR LARGE FIRES. Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: PREVENT SKIN AND EYE CONTACT. SCRAPE UP AND DISCARD IN SUITABLE

CONTAINERS. USE ABSORBENT MATERIAL IF

NECESSARY. WASH SPILL AREA WITH INDUSTRIAL CLEANING AGENT. IF SOLVENT IS USED FOR CLEANING, TAKE P RECAUTIONS AGAINST FIRE AND PERSONAL OVEREXPOSURE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:STORE IN COOL, DRY PLACE. HANDLE IN ACCORDANCE WITH POTENTIAL HAZARD OF THE CURING AGENT USED. REMOVE CONTAMINATED CLOTHING AND PROTECTIV E GEAR.

Other Precautions: IF CURED MATERIAL IS SANDED/MACHINED, USE PROPER PRECAUTIONS.WEAR ADEQUATE PROTECTIVE EQUIPMENT TO PREVENT OVEREXPOSURE TO NUISANCE PARTICULATES. SMALL AMOUNTS OF COPPER DUST MAY BE GENERATED.COPPER P OWDER HAS BEEN ISSUED TLV-TWA OF 1MG/M3.

Respiratory Protection:NONE REQUIRED AT NORMAL HANDLING TEMPERATURES. Ventilation:LOCAL EXHAUST IS RECOMMENDED FOR CONFINED AREAS. GENERAL VENTILA

TION IS ADEQUATE FOR NORMAL USE.

Protective Gloves: CHEMICAL RESISTANT RUBBER GLOVES.

Eye Protection: SAFETY GLASSES WITH SIDE SHIELDS.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING AS REQUIRED TO PREVENT SKIN CONTACT.

Work Hygienic Practices: WASH AFTER HANDLING AND BEFORE EATING,

DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health

KEY1:N1. THIS ENTRY DESCRIBES PART A OF A TWO PART KIT. SEE THIS SAME NSN, P/N IND D, FOR PART B DATA. DE

STROY LEATHER ARTICLES, INCLUDING SHOES THAT CANNOT BE DECONTAMINATED.

HCC:C2 Vapor Pres:NIL Vapor Density:>1 Spec Gravity:2.6 pH:7.0 Solubility in Water:NIL Appearance and Odor:BRONZE PASTE. LOW ODOR.

Stability Indicator/Materials to Avoid:YES STRONG ACIDS AND STRONG OXIDIZING AGENTS. Stability Condition to Avoid:OPEN FLAME AND EXCESSIVE HEAT. Hazardou s Decomposition Products:OXIDES OF CARBON, ALDEHYDES AND ACIDS FROM INCOMPLETE CONBUSTION.

Conditions to Avoid Polymerization:WILL NOT OCCUR. HEAT IS GENERATED WHEN MIXED WITH EPOXY HARDENER. USE CAUTION WHEN MIXING LARGE QUANTITIES.

Waste Disposal Methods:REMOVE TO WASTE DISPOSAL FACILITY OPERATING IN COMPLIANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the com piling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.