

DEL PAINT MANUFACTURING COMPANY -- F0201 -- 8010-00-298-2293

=====  
Product Identification  
=====

Product ID:F0201  
MSDS Date:08/30/1993  
FSC:8010  
NIIN:00-298-2293  
MSDS Number: BYCLL  
=== Responsible Party ===  
Company Name:DEL PAINT MANUFACTURING COMPANY  
Address:3105 E. RENO  
City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Info Phone Num:405-672-1431/FAX 405-672-0804  
Emergency Phone Num:800-424-9300 24  
HRS  
Preparer's Name:ONEY FLEMING  
CAGE:EO522  
=== Contractor Identification ===  
Company Name:DEL PAINT MANUFACTURING CORP  
CAGE:EO522  
Company Name:DEL PAINT MFG  
Address:3105 EAST RENO  
Box:City:OKLAHOMA CITY  
State:OK  
ZIP:73117  
Country:US  
Phone:405-672-1431  
CAGE:39934

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM (COAL OIL)  
CAS:8002-05-9  
RTECS #:SE7175000  
Fraction by Wt: 44.89%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM

Ingred

Name:METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 0.33%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:NONHAZARDOUS INGREDIENTS

Fraction by Wt: 54.78%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT EST.

ACGIH TLV:NOT EST.

Ingred Name:VOLATILE ORGANIC COMPOUNDS 3.25 LBS/GL, 390 G/LTR

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT EST.

ACGIH TLV:NOT EST.

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION, REDNESS, TEARING,  
BLURRED VISION. SKIN: POSSIBLE IRRITATION, DEFATTING, DERMATITIS  
W/PROLONGED/REPEATED EXPOSURE. INHALATION: NASAL/RESPIRATORY  
IRRITATION, DIZZINESS, NAUSEA, HEADACH E. INGESTION: POSSIBLE  
GASTROINTESTINALIRRITATION, NAUSEA, VOMITING.

Ef

fects of Overexposure:IF TLV'S EXCEEDED, SKIN CONTACT PRODUCES  
REDNESS. EYES: REDNESS/PAIN. INHALATION: LABORED BREATHING,  
DULLNESS, DROWSINESS. INGESTION: ABDOMINAL PAIN, NAUSEA.

Medical Cond Aggravated by Exposure:RESPIRATORY DISEASES.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH W/LARGE AMOUNT WATER 15 MINUTES OCCASIONALLY  
LIFTING EYELIDS. GET MEDICAL AID. SKIN: REMOVE CONTAMINATED  
CLOTHING. WASH W/SOAP & WATER. INHALATION: GET F

RESH AIR, GIVE

OXYGEN IF NECESSARY. GET MEDICAL AID. INGESTION: KEEP WARM, QUIET.

GET MEDICAL AID. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:100F,38C

Lower Limits:1.1

Upper Limits:6.0

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM. WATER MAY SPREAD FIRE, USE WATER SPRAY ONLY TO COOL CONTAINERS EXPOSED TO FIRE.

Fire Fighting Procedures:SCBA (MSHA/NIOSH OR EQUIV.) & FULL PROTECTIVE G

EAR. PREVENT POSSIBLE PRESSURE BUILD-UP, AUTOIGNITION, EXPLOSION TO EXTREME HEAT BY COOLING W/WATER SPRAY.

Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR. MAY TRAVEL & BE IGNITED BY PILET LIGHTS, OTHER FLAMES, SPARKS, HEATERS, SMOKING, OTHER REMOTE IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. COVER SPILL W/INERT ABSORBENT MATERIAL & SHOVEL W/NON-SPARKING TOOLS INTO CONTAINER. REMOVE CON

TAINER TO SAFE AREA & SEAL.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN CLEAN, DRY AREA. KEEP AWAY FROM SPARKS, FIRE, REMOTE IGNITION SOURCES.

Other Precautions:KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM CHILDREN. ALL EQUIPMENT SHOULD BE GROUNDED TO REDUCE STATIC ELECTRICITY HAZARD. USE NONSPARKING TOOLS.

===== Exposure Controls/Personal Protection =====

Respiratory Prot

ction:IF TLV OF PRODUCT OR ANY COMPONENT EXCEEDED, USE  
RESPIRATOR W/APPROPRIATE CARTRIDGES (NIOSH APPROVED). ENGINEERING  
OR MANAGEMENT CONTROL SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.  
Ventilation:LOCAL EXHAUST MUST BE SUFFICIENT TO KEEP AIRBORNE VAPOR  
CONCENTRATION BELOW TLV.  
Protective Gloves:CHEMICAL RESISTANT  
Eye Protection:SAFETY GLASSES W/SIDE SHIELDS.  
Other Protective Equipment:CLEAN FLUSHING WATER SOURCE SUGGESTED.  
IMPERVIOUS CLOTHING AS NEEDED.  
Supplemental Safety and H  
ealth  
NK

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:303F,151C  
Melt/Freeze Pt:M.P/F.P Text:NA  
Decomp Temp:Decomp Text:752F,400C  
Vapor Pres:2.58  
Vapor Density:>AIR  
Spec Gravity:1.23  
pH:NA  
Viscosity:77-86KU  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:NO  
Appearance and Odor:MAROON LIQUID W/SLIGHT ODOR  
Percent Volatiles by Volume:45.97  
Corrosion Rate:NA

===== Stability and Reactivity Data =====  
==

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid:DO NOT STORE NEAR HEATED SURFACES, OPEN  
FLAMES, IGNITION SOURCES.  
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON  
DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE W/FEDERAL, STATE, LOCAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is fo

rmulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.