

COURTAULDS AEROSPACE,INC -- 823X439 KORO FLEX PRIMER -- 8010-01-213-7898

===== Product Identification =====

Product ID:823X439 KORO FLEX PRIMER

MSDS Date:06/30/1995

FSC:8010

NIIN:01-213-7898

MSDS Number: BYFZY

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE,INC

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Nu

m:800-228-5635,800-424-9300(CHEMTREC)

Preparer's Name:NONE

CAGE:83574

=== Contractor Identification ===

Company Name:DESOTO INC PACIFIC PLANT IS COURTLANDTS AEROSPACE

Address:1608 4TH ST

Box:City:BERKELEY

State:CA

ZIP:94710

Country:US

Phone:800-228-5635 /800-424-9300 CHEMTREC

CAGE:85570

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

===== Composition/Inf

ormation on Ingredients =====

Ingred Name:METHYL N-AMYL KETONE
CAS:110-43-0
RTECS #:MJ5075000
Fraction by Wt: 10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9495

Ingred Name:STRONTIUM CHROMATE (CHROMIC ACID, STRONTIUM SALT), (SARA
313) (CERCLA)
CAS:7789-06-2
RTECS #:GB3240000
Fraction by Wt: 20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C 0.1 MG (CRO3)/M3
ACGIH TLV:0.0005MG(CR)/M3;A295
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:POLYMERIC URETHANE
RESIN
CAS:51855-41-5
Fraction by Wt: 20%
Other REC Limits:NONE RECOMMENDED

Ingred Name:CYCLOHEXANONE (CERCLA)
CAS:108-94-1
RTECS #:GW1050000
Fraction by Wt: 10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9495
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:DIPHENYLMETHANEDIISOCYANATE, (MDI),
(BENZENE,1,1'-METHYLENEBIS [4-ISOCYANATO-, (SARA 313)
CAS:101-68-8
RTECS #:NQ9350000
Fraction by Wt: AIR
Spec Gravity:1.05
Evaporation Rate & Reference:UNAVAIL

ABLE

Appearance and Odor:LIQUID. SOLVENT ODOR.

Percent Volatiles by Volume:71.3

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:AVOID TEMPERATURES ABOVE 120F, HEAT,
ELECTRICAL EQUIPMENT, SPARKS, FLAME, AND OTHER IGNITION SOURCES.
Hazardous Decomposition Products:PRODUCTS OF COMBUSTION ARE HAZARDOUS,
INCLUDING CARBON DIOXIDE AND CARBON MONOXIDE.

Conditions to Avoid

Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:WHEN DISPOSING OF THIS MATERIAL, ENSURE THAT IT
IS PACKAGED, STORED, TRANSPORTED AND OTHERWISE MANAGED IN
ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.