

RUST-OLEUM CORP -- 5269 & 5281 HIGH PERFORMANCE ACRYLIC COATINGS -- 8010-01-380-3283
===== Product Identification =====

Product ID:5269 & 5281 HIGH PERFORMANCE ACRYLIC COATINGS

MSDS Date:10/17/1994

FSC:8010

NIIN:01-380-3283

MSDS Number: BYHBX

=== Responsible Party ===

Company Name:RUST-OLEUM CORP

Address:11 HAWTHORNE PKWY

City:VERNON HILLS

State:IL

ZIP:60061-1583

Country:US

Info Phone Num:708-367-

7700

Emergency Phone Num:708-367-7700

Preparer's Name:NONE

CAGE:08882

=== Contractor Identification ===

Company Name:RUST-OLEUM CORP

Address:11 HAWTHORN PARKWAY

Box:City:VERNON HILLS

State:IL

ZIP:60061-1583

Country:US

Phone:847-367-7700

CAGE:08882

===== Composition/Information on Ingredients =====

Ingred Name:METHYL CARBITOL

CAS:111-77-3

RTECS #:KL6125000

Fraction by Wt: 5%

Other REC Limits:TLV=30PPM (MFR)

Ingred Name:PROPYLENE GLYCOL

CAS:57-55-6

RTECS #:TY2000000

Fraction b

y Wt: 5%
Other REC Limits:TLV=400PPM, (MFR)

Ingred Name:DIBUTYL PHTHALATE (SARA 313) (CERCLA)
CAS:84-74-2
RTECS #:TI0875000
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3; 9495
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:N-BUTOXYPROPANOL
CAS:5131-66-8
RTECS #:UA7700000
Fraction by Wt: 1-2%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHYLENE GLYCOL MONO-2-ETHYLHEXYL ETHER
CAS:1559-35-9
RTECS #:KK9625000
Fraction by Wt: 1-2%
Other REC Limits:NON
E RECOMMENDED

Ingred Name:VOLATILE ORGANIC CONTENT, V.O.C.= 200F,>93C
Fire Fighting Procedures:WATER MAY BE USED TO COOL CLOSED CONTAINERS TO
PREVENT BUILD-UP OF STEAM. IF WATER IS USED, FOG NOZZLES ARE
PREFERRED.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN
EXPOSED TO EXTREME HEAT DUE TO BUILD-UP OF STEAM.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP LIQUID WITH ABSORBENT AND SHOVEL INTO
WASTE CONTAIN
ER. WASH AREA WITH WATER AND FLUSH TO SEWER SERVICED
BY WASTE WATER TREATMENT FACILITY.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:NON-FLAMMABLE. SEE OSHA 1910.106. KEEP
FROM FREEZING.
Other Precautions:USE IN AREAS WITH ADEQUATE VENTILATION TO KEEP TLV OF
HAZARDOUS INGREDIENTS BELOW ACCEPTABLE LIMITS.

===== Exposure Controls/Personal Protection =====

Res

piratory Protection:USE NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR (TC23C) TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY DURING SPRAY APPLICATION.

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV BELOW ACCEPTABLE LIMITS.

Protective Gloves:RECOMMENDED TO PREVENT SKIN CONTACT.

Eye Protection:SAFETY GLASSES TO PREVENT SPLASH IN EYES

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH AFTER HANDLIN

G AND BEFORE EATING,

DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

CALIFORNIA PROPOSITION 65 STATEMENT: THESE PRODUCTS ARE NOT KNOWN TO CONTAIN ANY CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212 TO 385F

Vapor Density:>AIR

Spec Gravity:1.2

pH:8-8.5

Evaporation Rate & Referen

ce: