

SHERWIN-WILLIAMS CO THE SPECIALTY DIV. -- G2W10 KRYLON 1501 GLOSSY WHITE --  
8010-00-079-3762

===== Product Identification =====

Product ID:G2W10 KRYLON 1501 GLOSSY WHITE

MSDS Date:04/10/1989

FSC:8010

NIIN:00-079-3762

MSDS Number: BYSYN

=== Responsible Party ===

Company Name:SHERWIN-WILLIAMS CO THE SPECIALTY DIV.

Address:31500 SOLON RD

City:SOLON

State:OH

ZIP:44146-5000

Country:US

Info Phone Num:800-777-2966

Emergency Phone Num:800-777-2966/216-292-700

CAGE:DO6

42

=== Contractor Identification ===

Company Name:BLICK DICK CO

Address:P O BOX 1267

Box:City:GALESBURG

State:IL

ZIP:61401

Country:US

Phone:309-343-6181

CAGE:06608

Company Name:SAX ARTS & CRAFTS SUB OF BEATRICE COMPANIES INC

Address:2405 S CALHOUN RD

Box:City:NEW BERLIN

State:WI

ZIP:53151

Country:US

Phone:262-784-6880

CAGE:26290

Company Name:SHERWIN-WILLIAMS CO THE SPECIALTY DIV.

Address:6830 COCHRAN RD.

Box:6709

City:SOLON

State:OH

ZIP:44139-3908

Phone:216-292-7400

CAGE:DO642

Company Name:SHERW

IN-WILLIAMS DIVERSIFIED BRANDS, INC.  
Address:26300 FARGO AVENUE  
Box:City:BEDFORD HEIGHTS  
State:OH  
ZIP:44146  
Country:US  
Phone:216-292-7400 OR 216-595-8634  
CAGE:09800

===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA 313) (CERCLA)  
CAS:67-64-1  
RTECS #:AL3150000  
Fraction by Wt: 30-50%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000 PPM  
ACGIH TLV:750PPM/1000STEL;9495  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE  
CAS:74-98-6  
RTECS #:TX227  
5000  
Fraction by Wt: 10-30%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000 PPM  
ACGIH TLV:ASPHYXIAN; 9495

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM  
ACGIH TLV:200 PPM/300STEL;9495  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (HEXONE) (SARA 313) (CERCLA)  
CAS:108-10-1  
RTECS #:SA9275000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOM

MENDEED  
OSHA PEL:100 PPM  
ACGIH TLV:50 PPM/75 STEL; 9495  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE  
CAS:108-65-6  
RTECS #:A18295000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT ESTABLISHED.  
ACGIH TLV:NOT ESTABLISHED.

Ingred Name:TOLUENE (SARA 313) (CERCLA)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM; Z-2  
ACGIH TLV:S, 50 PPM; 9495  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:  
1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 10-30%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM/150STEL;9495  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9495

===== Hazards Identification =====

Routes

of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: INGESTION NOT EXPECTED TO  
HARMFUL UNDER NORMAL CONDITIONS OF USE. INHALATION OF VAPORS/MISTS  
MAY CAUSE RESPIRATORY IRRITATION, CNS DEPRESSION, ASPHYXIATION,  
LIVER/KIDNEY DAMAGE. CONTACT MAY CAUSE SKIN AND EYE IRRITATION.  
CHRONIC:NONE SPECIFIED BY MANUFACTURER.  
Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%  
OR GR  
EATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.  
Effects of Overexposure:INHALED-HEADACHE, DIZZINESS, NAUSEA, VOMITING,  
UNCONSCIOUSNESS, CYANOSIS. SKIN-IRRITATION. EYES-IRRITATION.  
INGESTED-NONE SPECIFIED BY MANUFACTURER.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:IN ALL CASES GET MEDICAL ATTENTION. EYES-IMMEDIATELY FLUSH  
WITH WATER FOR 15 MINUTES, LIFT LIDS. SKIN-REMOVE  
CONTAMINATED  
CLOTHES. FLUSH WITH LOTS OF WATER. INHALED-REMOVE TO FRESH AIR.  
ADMINISTER OXY GEN OR ARTIFICIAL RESPIRATION AS NEEDED. INGESTED-IF  
CONSCIOUS, GIVE LOTS OF WATER AND CONTACT POISON CONTROL CENTER OR  
EMERGENCY ROOM.

===== Fire Fighting Measures =====

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM. WATER MAY BE  
INEFFECTIVE BUT SHOULD BE USED TO COOL FIRE EXPOSED CONTAINERS.  
Fire Fighting Procedures:WEAR SELF-CONTAINED BRE  
ATHING APPARATUS AND  
FULL PROTECTIVE GEAR.  
Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE. VAPOR MAY IGNITE  
EXPLOSIVELY. VAPORS MAY TRAVEL TO DISTANT IGNITION SOURCE AND  
FLASHBACK.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. SOAK UP  
WITH INERT ABSORBENT MATERIAL AND REMOVE TO A CHEMICAL DISPOSAL  
AREA. PREVENT ENTRY INTO BODIES OF WATER.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE BELOW 120F  
AND AWAY FROM SOURCES OF IGNITION AND STRONG OXIDIZING AGENTS.  
Other Precautions:AVOID CONTACT WITH SKIN AND EYES. AVOID BEATHING  
VAPOR OR MIST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE  
OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR  
WITH  
ORGANIC VAPOR CARTRIDGE OR AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS  
REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation:USE EXPLOSION-PROOF ADEQUATE MECHANICAL VENTILATION OR  
LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:BUTYL, PVA.

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. DLA-HMIS:  
EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING,

DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

SAX ARTS & CRAFTS PART NUMBER: 317-0016. CONTRACT NUMBER  
SP0420-95-PA057.

===== Physical/Chemical Properties =====

HCC:V3

Vapor Pres:60 PSIG

Spec Gravity:1 (N-BUTYL ACETATE=1)

Solubility in Water:SLIGHT

Appearance and Odor:WHITE LIQUID IN AEROSOL CAN WITH GAS PROPELLANT.

Percent Volatiles by Volume:89

===== Stability and Reactivity Data =====

==

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER. DLA-HMIS: STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. DLA-HMIS:

AVOID EXPOSURE TO HIGH TEMPERATURES AND STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:OXIDES OF CARBON.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND

FEDERAL ENVIRONMENTAL REGULATIONS. EMPTY CONTAINER MAY CONTAIN  
EXPLSOIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEARBY.  
INCINERATION WILL CAUSE CONTA INER TO BURST VIOLENTLY.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its u  
se. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.