

N/P -- ENAMEL, FLOOR & DECK #16099 GRAY -- 8010-00-285-4859

Product ID:ENAMEL, FLOOR & DECK #16099 GRAY

MSDS Date:01/01/1987

FSC:8010

NIIN:00-285-4859

MSDS Number: BYXSL

=== Responsible Party ===

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS (STODDARD SOLVENT)

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 30.2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:CALCIUM CARBONATE LIMESTONE

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 24.6%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcin

ogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: POSSIBLE EYE/SKIN IRRITATION W/OVEREXPOSURE. CONTINUED BREATHING OF VAPORS MAY IRRITATE RESPIRATORY TRACT. CHRONIC: REPORTS HAVE ASSOCIATED PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS W/PER MANENT BRAIN/NERVOUS SYSTEM DAMAGE.

Effects of Overexposure:HEADACHE, NAUSEA, DIZZINESS.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH IMMEDIATELY W/LOTS WATER 15 MINUTES. CONSULT DR.

SKIN: WASH W/SOAP & WATER. REMOVE CONTAMINATED CLOTHES. INHALATION: GET FRESH AIR. RESTORE RESPIRATION, IF NECESSARY, TREAT SYMPTOMATICALLY . INGESTION: DON'T INDUCE VOMITING. CONTACT DR. IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point:105F,41C; NK

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES, WEAR APPROPRIATE PERSONAL PROTECTION EQUIPMENT & APPROVED RESPIRATOR. CONTAIN SPILL & PUT IN VAPOR TIGHT CONTAINERS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN AREAS TO COMPLY W/ANSI-NFPA 30 FLAMMABLE & COMBUSTIBLE LIQUIDS CODE.

Other Precautions:NA

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA ORGANIC VAPOR RESPIRATOR.

Ventilation:SUFFICIENT, IN VOLUME/PATTERN TO KEEP HAZ MATERIALS BELOW APPLICABLE EXPOSURE LEVELS.

Protective Gloves:NEOPRENE

Eye Protection:SPLASH SHIELDS

Other Protective Equipment:NO INFO FOUND

Work Hygienic Practices:WASH HANDS PROPERLY BEFORE EATING, SMOKING OR USING WASHROOM.

Supplemental Safety and Health

NK

=====
===== Physical/Chemical Properties =====

Viscosity:67-82 KREBS

=====
===== Stability and Reactivity Data =====

Hazardous Decomposition Products:CO & CO2.

=====
===== Disposal Considerations =====

=====

Waste Disposal Methods:IN ACCORDANCE W/FEDERAL, STATE, LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.