

DOW CORNING CORP -- DOW CORNING 3-7132 RTV ADHESIVE SEALANT -- 8040-00-833-9563

===== Product Identification =====

Product ID:DOW CORNING 3-7132 RTV ADHESIVE SEALANT

MSDS Date:07/11/1994

FSC:8040

NIIN:00-833-9563

Kit Part:Y

MSDS Number: BYXTW

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:SOUTH SAGINAW ROAD

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-5900

Eme

rgency Phone Num:517-496-5900

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:METHYLTRACETOXYSILANE

CAS:4253-34-3

RTECS #:VV4500000

Fraction by Wt: 2.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM
ACGIH TLV:10 PPM/STEL 15 PPM

Ingred Name:ETHYLTRIACETOXYSILANE
CAS:17689-77-9
Fraction by Wt: 2.0%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SILICA AMORPHOUS
CAS:112945-52-5
Fraction by Wt: 10.0%
Other REC Limits:*5 MG/M3 RESP FRACTN
OSHA PEL:15 MG/M3,T DUST*
ACGIH TLV:10 MG/M3, T DUST

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports

of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: MOD IRRIT/REDNESS/SWELLING.

SKIN: POSSIBLE MILD/MODERATE IRRITATION DEPENDING ON EXPOSURE > OR
150C IN PRESENCE OF AIR,

PRODUCT CAN FORM FORMALDEHYDE VAPORS WHICH IS POTENTIAL CANCER
HAZARD; KNOWN SKIN/RESPIRATORY SENSITIZER;

EYES/NOSE/THROAT/SKIN/DIGESTIVE SYSTEM IRRITANT. KE EP VAPOR

CONCENTRATIONS WITHIN PERMISSIBLE EXPOSURE LIMIT FOR FORMALDEHYDE
TO MAINTAIN SAFE HANDLING CONDITION

S.

===== First Aid Measures =====

First Aid:EYES: IMMED FLUSH W/WATER 15 MIN. GET MED AID. SKIN: WASH
W/SOAP & WATER OR WATERLESS CLEANSER. GET MED AID IF IRRIT/OTHER
ILL EFFECTS DEVELOP/PERSIST. INHALATION: REMOVE TO FRESH AIR. TREAT
ACCORDING TO PERSON'S CONDITION & SPECIFICS OF EXPOSURE.

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:NA - SOLID
Extinguishing Media:WATER, WATER FOG OR

SPRAY, CO2, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:SCBA & PROTECTIVE CLOTHING SHOULD BE WORN IN FIRES INVOLVING CHEMICALS. IF LARGE AMOUNT CHEMICALS INVOLVED, EVACUATE AREA.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP/CONTAIN FOR SALVAGE/DISPOSAL. OBSERVE ALL PERSONAL PROTECTION EQUIPMENT RECOMMENDATIONS. OBSERVE APPLICABLE SPILL/RELEASE REPORTING REQUIREMENTS.

===== Handling and Storage =====

Handling and Storage Precautions:NO SPECIAL REQ; KEEP VAPOR CONCENTRATIONS WITHIN OSHA PERMISSIBLE EXPOSURE LIMIT FOR FORMALDEHYDE; KEEP CNTNR CLOSED. STORE AWAY FROM WATER/MOISTURE. Other Precautions:AVOID EYE/SKIN CONTACT, BREATHING VAPORS. KEEP CONTAINER CLOSED. USE REASONABLE CARE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE RESP PROT UNLESS ADEQUATE LOCAL EXHAUST VENTILATION IS PROVIDED OR AIR-SAMPLING DATA SHOWS EXPOSURES WITHIN RECOMMENDED GUIDELINES. INDUSTRIAL HYGIENE PERSONNEL CAN ASSIST IN JUDGING ADEQUACY OF EXISTING ENGINEERING CONTROLS. Ventilation:ADEQUATE TO KEEP EXPOSURE