DEFT INC CHEMICAL COATING DIV -- CAT MIL-C-85285B, 34095, TYPE II (04GN005CAT) - 8010-01-292-9618

Product ID:CAT MIL-C-85285B, 34095, TYPE II (04GN005CAT) MSDS Date:11/11/1993 FSC:8010 NIIN:01-292-9618 Kit Part:Y MSDS Number: BYYDC === Responsible Party === Company Name: DEFT INC CHEMICAL COATING DIV Address:17451 VON KARMAN AVE City:IRVINE State:CA ZIP:92714-6205 Country:US Info Phone Num:714-474-0400 **Emergency Phone Num:714** -474-0400/800-424-9300 CHEMTREC Preparer's Name:NORM GAUL CAGE:33461 === Contractor Identification === Company Name: DEFT, INC. Address:17451 VON KARMAN AVE City:IRVINE State:CA ZIP:92614 Country:US Phone:949-474-0400 CAGE:33461 Ingred Name: ALIPHATIC ISOCYANATE CAS:4035-89-6 Fraction by Wt: 65% Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT EST. ACGIH TLV:NOT EST.

Ingred Name: METHYL ISOBUTYL KETONE (HEXONE) (SARA 313) (CERC

LA)(VP =15 @ 68F) CAS:108-10-1 RTECS #:SA9275000 Fraction by Wt: 25% Other REC Limits:NONE RECOMMENDED OSHA PEL:50 PPM/STEL 75 ACGIH TLV:50 PPM/STEL 75 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: ETHYL 3-ETHOXYPROPIONATE (VP = 0.7 @ 68F) CAS:763-69-9 RTECS #:UF3325000 Fraction by Wt: 10% Other REC Limits:50 PPM/STEL 100 Ingred Name: HEXAMETHYLENE DIISOCYANATE (CERCLA) FREE MONOMER CONTENT 3-6 MO. FREE MONOMER MAY RISE* CAS:822-06-0 RTECS #:MO1740000 Other REC Limits: MILES - 0 .02PPM CEIL OSHA PEL:NK *TO MAX 1.6%. ACGIH TLV:0.005 PPM; 9495 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name:VOC = 355 G/L

RTECS #:99999999VO Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT EST. ACGIH TLV:NOT EST.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: VAPORS IRRIT EYES/NOSE/THROAT. INHAL: IRRIT, ACUTE NS DEPRESSI ON. CHRONIC: DEFATTING W/PROLONGED CONTACT. INGEST: IRRIT. POS CHEM PNEUMONITIS W/ASPIRATION RESULT OF PREVIOUS REPEATED OVEREXPOS/ SINGLE LG DOSE, SOME PEOPLE WILL DEVELOP ISOCYANATE SENSITIZATION, WHICH CAUSES THEM REACT TO LATER EXPOSURE OF **

Effects of Overexposure:INHAL: HEADACHE, DIZZINESS, STAGGERING GATE, CONFUSION, UNCONSC OR COMA, DIFFICULT BREATHING, ASTHMA. SKIN: SENSITIZATION, OTHER ALLERGIC RESPONSES, SWELLING, REDNESS, RASH. EYES: TEARING, REDNESS, SW

ELLING W/STINGING SENSATION.

Medical Cond Aggravated by Exposure:ASTHMA & ANY OTHER RESP DISORDERS. SKIN: ALLERGIES, EXCEMA, DERMATITIS. ISOCYANATE SENSITIZATION.

First Aid:INHAL: GET FRESH AIR. RESTORE BREATHING. ASTHMATIC TYPICAL SYMPTOMS MAY DEVELOP, MAY BE IMMED OR DELAYED BY SEVERAL HRS. GET MED AID. SKIN: REMOVE CONTAM CLOTHES. WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/CLEAN LUKE WARM WATER (LOW PRE SSURE) AT LEAST

15 MÍN, LIFTING LIDS. GET MED AID. INGEST: DON'T INDUCE VOMITING. DON'T GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON. GET MED AID.

Flash Point Method:TCC
Flash Point:60.0F,15.6C
Lower Limits:1.05
Upper Limits:8.0
Extinguishing Media:FOAM, ALCOHOL-FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG, WATER SPRAY.
Fire Fighting Procedures:FULL FIRE FIGHT EQUIP W/SCBA, FULL PROTECT CLOTHES. USE H2O TO CO
OL CLOSED CNTNRS/PREVENT PRESSURE
BUILD-UP/AUTOIGNITE/EXPLOSION. HDI/IRRIT VAPORS GENERATED.
Unusual Fire/Explosion Hazard:KEEP CLOSED TIGHT. CLOSED CNTNR MAY EXPLODE W/EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS. POS HEALTH HAZ W/OVEREXPOSURE DECOMP PRODS

Spill Release Procedures: EVACUATE NONESSENTIAL PERSONNEL. REMOVE ALL IGNITION SOURCES. VENT. AREA. CONTAIN/REMOVE W/INERT ABSORBEN

Handling and Storage Precautions:STORE IN BUILDING COMPLYING W/OSHA 1910.106. AVOID STORING NEAR HI TEMP/FIRE/OPEN FLAME/SPARK SOURCES. STORE IN TIGHT CLOSED CNTNR/WELL VENTED AREA.

Other Precautions:KEEP CNTNR TIGHT/UPRIGHT TO PREVENT LEAKAGE. PREVENT PROLONGED BREATHING VAPOR/SPRAY MISTS. POS ALLERGIC REACTION W/PROLONGED OVEREXPOSURE. AVOID SKIN/EYE CONTACT. DON'T TAKE INTERNAL

LY. DON'T HANDLE TIL READ/UNDERSTAND MFG PRECAUTIONS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:ORGANIC VAPOR RESPIRATR (AIR PURIFYING/FRESH AIR) OBSERVE OSHA REGS (RESPIRATR USE). PROVIDE VENT (KEEP EXPOSURE LEVELS