

PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV -- ENAMEL ALKYD, SEMI GLOSS LO VOC
CT GRAY 26492, ID 775655 -- 8010-00-104-8377

===== Product Identification =====

Product ID:ENAMEL ALKYD, SEMI GLOSS LO VOC CT GRAY 26492, ID 775655

MSDS Date:06/14/1995

FSC:8010

NIIN:00-104-8377

MSDS Number: BZJDF

=== Responsible Party ===

Company Name:PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W A ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:N-BUTYL ACETATE (SOLVENT) (VAPOR PRESSURE 10 MM HG @ 20C)
(LFL 1.7; UFL 7.6)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

OSHA

PEL:150 PPM;STEL 200 PPM

ACGIH TLV:150 PPM;STEL 200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (SOLVENT) (SARA III) (VAPOR PRESSURE 5 MM HG @ 20C)
(LFL 1.0; UFL 7.0)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:100 PPM;STEL 150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE (PIGMENT)

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 15%

COMMENDED
OSHA PEL:10 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:SILICA, AMORPHOUS HYDRATED (PIGMENT)
CAS:112945-52-5
RTECS #:VV7310000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:6 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:TALC (PIGMENT)
CAS:14807-96-6
RTECS #:WW2710000
Fraction by Wt: 20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3; 20 MPPCF
ACGIH TLV:2 MG/M3; 15 MPPCF

Ingred Name:SILICA, CRYSTALLINE
CAS:14808-60-7
RTECS #:VV7330000
Fraction by Wt: 115F) AND SOURCES
OF IGN
ITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY
WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE & CARBON
DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, &
LOCAL LAWS OR REGULATIONS. THIS PRODUCT, IF DISCARDED DIRECTLY,
WOULD BE CLASSIFIED A HAZARDOUS WASTE BASED ON ITS IGNITABILITY
CHARACTERISTIC (FLASH POINT 140F OR LESS). PROPER RCRA
CLASSI
FICATION: D001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
p

articular situation.