Product ID:EX,LASERJET 4,R 64-0002-010 MSDS Date:05/01/1996 FSC:6850 NIIN:01-376-1766 MSDS Number: BZNMQ === Responsible Party === Company Name: AMERICAN LASER INC Address:1007 RIPLEY ST City:SILVER SPRING State:MD ZIP:20910 Country:US Info Phone Num:301-588-4850/800-258-6637 Emergency Phone Num:301-588-4850/800-258-6637 CAGE:0S0F8 === Contractor Identificat ion ===Company Name: AMERICAN LASER INC Address:1007 RIPLEY ST Box:City:SILVER SPRING State:MD ZIP:20910 Country:US Phone:301-588-4850 CAGE:0S0F8

Ingred Name:STYRENE ACRYLATE COPOLYMER Fraction by Wt: 55 - 65% Other REC Limits:NONE RECOMMENDED

Ingred Name:IRON OXIDE CAS:1317-61-9 Fraction by Wt: 30 - 40% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG/M3 ACGIH TLV:5 MG/M3

Ingred Name:SALICYLIC ACID CHROMIUM (III) CHELATE C

AS:72869-85-3 Fraction by Wt: 1 - 3% Other REC Limits:0.5 MG/M3 AS CR(MFR)

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: TARGET ORGANS: EYES, RESPIRATORY TRACT. ACUTE- EYES:NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKIN: LOW HAZARD FOR INDUSTRIAL HANDLING. IN HALE: GASPING. ORAL: EXPECTED TO BE A LOW INGESTIO N HAZARD. CHRONIC- UNKNOWN. Explanation of Carcinogenicity:NONE Effects of Overexposure: TRANSIENT EYE IRRITATION, GASPING, COUGHING Medical Cond Aggravated by Exposure: PERSONS WITH PRE-EXISTING EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT. First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:MOVE TO FRESH AIR. EYES: FLUSH WITH PLENTY OF WATER, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:SEEK MEDICAL ATTENTION. Flash Point:NONE Lower Limits:NOT RELEVANT Upper Limits:NOT RELEVANT Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL. Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS . HAZARDOUS DECOMPOSITION PRODUCTS MAY BE FORMED. Unusual Fire/Explosion Hazard: AS WITH ANY FINELY DIVIDED ORGANIC SOLID, DUST MAY BE EXPLOSIVE IF MIXED WITH AIR IN CRITICAL PROPORTIONS AND IN THE PRESENCE OF AN IGNITION SOURCE.

Spill Release Procedures: CAREFULLY, SWEEP MATERIAL ONTO PAPER AND PLACE IN A FIBER CARTON. CLEAN SPILL AREA THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION. DO NOT USE A VACUUM CLEANER TO CLEAN UP SPILL OF POWDERED TONERS. THE VE RY FINE PARTICLES CAN CAUSE A FIRE OR EXPLOSION. Neutralizing Agent:NOT RELEVANT

 Handling and Storage Precautions: KEEP CONTAINER CLOSED. STORE AWAY FROM STRONG OXIDIZING AGENTS. MINIMIZE DUST GENERATION AND ACCUMULATION.
Other Precautions: AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. KEEP OUT OF REACH OF CHILDREN. DO NOT
BREATHE DUST.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE SHOULD BE NEEDED. Ventilation:GOOD GENERAL VENTILATION (TYPICALLY 4-6 RM VALUME/HR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS. Protective Gloves:RUBBER/LATEX FOR REPEATED CONTACT Eye Protection:GOGGLES RECOMMENDED Other Protective Equipment:EYE BATH, WASHING FACILITIES, SAFETY SHOWER Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND R ECOMMENDED PROCEDURES. WASH BEFORE EATING OR DRINKING. Supplemental Safety and Health

HCC:N1 NRC/State Lic Num:NOT RELEVANT Melt/Freeze Pt:M.P/F.P Text:212-302F Spec Gravity:1.4 - 1.5 Viscosity:NOT RELEVANT Evaporation Rate & amp; Reference:NOT RELEVANT Solubility in Water:NEGLIGIBLE Appearance and Odor:BLACK POWDER - SLIGHT PLASTIC ODOR

Stability Indicator/

Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:DUST FORMATION Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF IRON

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE OR LOCAL REGULATIONS. INCINERATE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.