

R M ENGINEERED PRODUCTS, INC. -- RL-2442 GROMMET, P/N 43002060 -- 5330-00-145-8585

=====  
Product Identification  
=====

Product ID:RL-2442 GROMMET, P/N 43002060

MSDS Date:09/30/1992

FSC:5330

NIIN:00-145-8585

MSDS Number: BZQVQ

=== Responsible Party ===

Company Name:R M ENGINEERED PRODUCTS, INC.

Address:4854 O'HEAR AVENUE

City:NORTH CHARLESTON

State:SC

ZIP:29405-4972

Country:US

Info Phone Num:803-744

-6261 X494 FAX 803-744-0461

Emergency Phone Num:803-744-6261

CAGE:10009

=== Contractor Identification ===

Company Name:FENWAY SAFETY SYSTEMS INC

Address:700 NICKERSON RD

Box:City:MARLBOROUGH

State:MA

ZIP:01752

Country:US

CAGE:73168

Company Name:R M ENGINEERED PRODUCTS, INC.

Address:4854 O'HEAR AVENUE

Box:City:NORTH CHARLESTON

State:SC

ZIP:29405

Country:US

Phone:843-744-6261

CAGE:10009

=====  
Composition/Information on Ingredients  
=====

Ingred Name:POLYTETRAFLUOROETHYLENE

CAS:1

16-14-3  
RTECS #:KX4025000  
Other REC Limits:NONE RECOMMENDED

Ingred Name:ASBESTOS, CHRYSOTILE  
CAS:12001-29-5  
RTECS #:CI6478500  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.2 FIBERS/CC  
ACGIH TLV:2 FIBERS/CC,A1; 9495

Ingred Name:ASBESTOS (SARA 313) (CERCLA)  
CAS:1332-21-4  
RTECS #:CI6425000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.2 FIBERS/CC  
ACGIH TLV:0.2 FIBER/CC,A1;9495  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

===== Hazards Identification =====

LD50 LC50 Mixture:  
PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:\*\*TARGET-ORGANS:LUNGS\*\* ACUTE-NONE  
UNDER NORMAL CONDITIONS OF USE. PROCESSING CAN PRODUCE DUST/FIBERS  
THAT MAY CASUE IRRITATION TO SKIN, EYES, RESPIRATORY SYSTEM.  
OVEREXPOSURE TO ASBESTOS DUST/FUMES/ FIOBERS MAY CAUSE CANCER OR  
ASBESTOSIS.  
Explanation of Carcinogenicity:CONTAINS A [1332-21-4]  
WHICH IS  
LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.  
Effects of Overexposure:NONE UNDER NORMAL CONDITIONS OF USE. EXPOSURE  
TO NUISANCE DUST/FIBERS & TEFLON FUMES FROM MACHINING OR HEATING  
CAN PRODUCE FLU-LIKE SYMPTOMS W/FEVER & CHILLS. SYMPTOMS USUALLY  
DISAPPEAR W/IN 36-48 HRS . POSSIBLE IRRITATION TO EYES, NOSE,  
THROAT, UPPER RESPIRATORY TRACT & SKIN.  
Medical Cond Aggravated by Exposure:SKIN & EYE SENSITIVITY, RESPIRATORY  
CONDITIONS, ALLERGIC REACTIONS



ective Gloves:COTTON, LEATHER, RUBBER AS NEEDED

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS.

Other Protective Equipment:CLOTHING SUFFICIENT TO PREVENT SKIN CONTACT FROM DUST/FUMES WHEN NEEDED.

Work Hygienic Practices:AVOID CREATING DUST. FOLLOW GOOD INDUSTRIAL HOUSEKEEPING & PERSONAL HYGIENE PRACTICES. WASH HANDS BEFORE EATING/SMOKING.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:T7

NRC/State Lic Num:NONE

Solubility i

n Water:INSOLUBLE

Appearance and Odor:BRAIDED PACKING W/NO CHARACTERISTIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS & OTHER INTERHALOGEN COMPOUNDS.

Stability Condition to Avoid:TEMPERATURES >500F

Hazardous Decomposition Products:FLUOROCARBON FUMES, CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF I/A/W FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.