

DYNAMOLD, INC. -- DS-104 -- 7930-01-367-0986

===== Product Identification =====

Product ID:DS-104

MSDS Date:12/07/1994

FSC:7930

NIIN:01-367-0986

MSDS Number: BZTCB

=== Responsible Party ===

Company Name:DYNAMOLD, INC.

Address:2905 SHAMROCK AVE

Box:9617

City:FORT WORTH

State:TX

ZIP:76107

Info Phone Num:817-335-0862

Emergency Phone Num:817-335-0862

CAGE:30256

=== Contractor Identification ===

Company Name:DYNAMOLD SOLVENTS, INC.

Address:2905 SHAMROCK AVE

Box:961

7

City:FORT WORTH

State:TX

ZIP:76107

Country:US

Phone:817-335-0862

CAGE:30256

===== Composition/Information on Ingredients =====

Ingred Name:N-BUTYL ACETATE (CERCLA)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 3-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:150 PPM

ACGIH TLV:150 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:HYDROCARBONS

CAS:64742-48-9

Fraction by Wt: 25-32%

Other REC Limits:MFG REC 300 PPM

Ingred Name:PROPYLENE GLYCOL METHYL ETHER ACETATE

CAS

:108-65-6
RTECS #:AI8925000
Fraction by Wt: 65-70%
Other REC Limits:WEEL GUIDE 100PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE OVEREXPOSURE: MAY CAUSE
IRRITATION TO RESPIRATORY TRACT, MUCOUS MEMBRANES. CHRONIC:
PROLONGED/REPEATED SKIN CONTACT MAY CAUSE DRYING, CRACKING,
IRRITATION. PROLONGED INHALATION MAY CAUSE STOMACH UPSET,
IRRITATION TO RESPIRATORY TRACT& MUCOUS MEMBRANES.
Effects of Overexposure:HIGH VAPOR CONCENTRATIONS >1000 PPM ARE
IRRITATING TO EYES, RESPIRATORY TRACT. MAY CAUSE HEADACHES,
DIZZINESS, ANESTHESIA, DROWSINESS.
Medical Cond Aggravated by Exposure:DISORDERS OF CNS, EYES, SKIN.
IRRITATION OF RESPIRATORY TRACT. **1 PT LUKE WARM WATER IF
CONSCIOUS/ALERT.DON'T INDUCE VOMITING; RISK OF LUNG DAMAGE. GET
EMERGENCY MED AID.

===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR IMMED.USE OXYGEN/ARTIF RESP AS
NEEDED.GET MED AID.PROMPT ATTN ESSENTIAL!EYE: IMMED RINSE W/CLEAN
WATER 20-30 MIN.RETRACT LIDS OFTEN.GET MED AID IF
PAIN/BLINKING/TEARS/REDNESS PERSIST.CALL EYE DR.SKIN:REMOVE CONTAM
CLOTHES,WASH WELL W/MILD SOAP/WATER.WASH W/LUKE WARM WATER 15
MIN.IF STICKY USE WATERLESS CLEANER.IF ALLERGIC REACT TREAT
CONVENTIONALLY.INGEST:LG AMTS, GIVE**

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:ABOUT 105F
Autoignition Temp:Autoignition Temp Text: 520F
Lower Limits:2.0
Upper Limits:10.0
Extinguishing Media:DRY CHEMICAL, CO2, WATER SPRAY, ALCOHOL TYPE FOAM,
WATER FOG.
Fire Fighting Procedures:DON'T ENTER AREA W/O PROPER PROTECTION. FIGHT
FIRE AT SAFE DISTANCE/PROTECTED LOCATION. HEAT MAY BUILD
PRESSURE/RUPTURE CLSD CNTNRS SPREADING FIRE/INCREASING*
Unusual Fire/Explosion Hazard:RELEASES VAPORS WHEN

HEATED ABOVE FLASH.

WHEN MIXED W/AIR/EXPOSED TO IGNIT SOURCE VAPORS MAY BURN/EXPLODE.
VAPORS >AIR, TRAVEL DISTANCES BEFORE FLASHING BACK.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNIT SOURCES.USE PROTECT EQUIP.LIMIT
ACCESS TO QUALIFIED PERSONNEL.SOAK UP W/INERT SOLIDS/PLACE IN
LABELED/SEALED CNTNR.PREVENT FLOW TO SEWERS.NOTIFY
FIRE/ENVIRONMENTAL AUTHORITIES.COVER SLIPP ERY SURFACES W/GRANULAR
SOLID.CONTAIN SPIL
LS.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T BREATHE VAPORS.USE ADEQUATE
VENTLTN.STORE ONLY IN TIGHT CLSD CNTNRS/PROPERLY VENTED CABINETS
AWAY FROM IGNIT SOURCES.USE NONSPARKING TOOLS ONLY.
Other Precautions:GROUND CNTNRS BEFORE TRANSFERRING.EMPTY CNTNRS MAY BE
HAZ.ISOLATE/DRAIN/WASH/PERGE SYSTEMS BEFORE
MAINTAINANCE/REPAIR.CHECK ATMOSPHERES FOR EXPLOSIVENESS/OXYGEN
DEFICIENCY.MIST MAY BE COMBUSTIBLE