## 

Product ID:MA212 SOLVENTBORNE NEOPRENE ADHESIVE

MSDS Date:07/08/1994

FSC:8040

NIIN:00-664-4318

MSDS Number: BZYVQ === Responsible Party === Company Name:TACC INTL

Address:AIR STATION INDUSTRIAL PK

Box:535

City:ROCKLAND

State:MA ZIP:02370 Country:US

Info Phone Num:617-878-7015

Emergency Phone Num:617-878-7015

CAGE:GO489

=== Contractor Identification ===

Comp

any Name:TACC INTERNATIONAL CORP Address:AIR STATION INDUSTRIAL PARK

Box:City:ROCKLAND

State:MA ZIP:02370 Country:US

Phone:781-878-7015

CAGE:0HZU1

Company Name: TACC INTL

Address: AIR STATION INDUSTRIAL PK

Box:535

City:ROCKLAND

State:MA ZIP:02370 Country:US

Phone:617-878-7015

CAGE:GO489

======= Composition/Information on Ingredients ========

Ingred Name: TOLUENE (IARC CARC- GROUP 3) \*96-2\*

CAS:108-88-3

RTECS #:XS5250000

Other REC Limits:375 MG/CUM

OSHA PEL:100 PPM ACGIH TLV:100 P PM

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: HEXANE, N-HEXANE

CAS:110-54-3

RTECS #:MN9275000 Fraction by Wt: 20-50% Other REC Limits:50 PPM OSHA PEL:1800 MG/CUM ACGIH TLV:176 MG/CUM

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: ACETONE; DIMETHYL KETONE; 2-PROPANONE

CAS:67-64-1

RTECS #:AL3150000 Fraction by Wt: 5-20% OSHA PEL:2400 MG/CUM ACGIH TLV:750 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE, 2-BUTANONE \*96-2\*

CAS:78-93-3

RTECS #:EL6475000

Fra

ction by Wt: 5-20%

Other REC Limits:590 MG/CUM

OSHA PEL:200 PPM ACGIH TLV:590 MG/CUM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS


========= Hazards Identification ===============

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INHALATION: MAY CAUSE UPPER

RESPIRATORY DRYNESS/IRRITATION, MENTAL DEPRESSION/NARCOSIS.

OVEREXPOSURE TO SOLVENTS COULD LEAD TO PERMANENT EFFECTS TO THE



========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG ACIDS & BASES Stability Condition to Avoid:FIRE, SPARKS, STATIC ELECTRICITY Hazardous Decomposition Products:CO, CO2

======= Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. DRIED ADHESIVE MAY BE DISPOSED OF AS ORDINARY WASTE. FLAMMABLE UN1133.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.