

PARKER-HANNIFIN CORP GREER HYDRAULICS CYLINDER DIV -- A66797-200 ACCUMULATOR
(CONTAINS NITROGEN ALSO) -- 3040-00-004-9182

===== Product Identification =====

Product ID:A66797-200 ACCUMULATOR (CONTAINS NITROGEN ALSO)

MSDS Date:01/01/1985

FSC:3040

NIIN:00-004-9182

MSDS Number: CBQBR

=== Responsible Party ===

Company Name:PARKER-HANNIFIN CORP GREER HYDRAULICS CYLINDER DIV

Address:10711 N 2ND STREET

C

ity:MACHESNEY PARK

State:IL

ZIP:61115

Country:US

Info Phone Num:815-633-0290

Emergency Phone Num:815-633-0290

CAGE:02697

=== Contractor Identification ===

Company Name:GREER HYDRAULICS

Address:30201 AURORA ROAD

Box:City:SOLON

State:OH

ZIP:44139

Country:US

Phone:216-481-6686

CAGE:26337

Company Name:PARKER-HANNIFIN CORP SEAL GROUP O-RING DIVISION

Address:2360 PALUMBO DRIVE

Box:11751

City:LEXINGTON

State:KY

ZIP:40509

Country:US

Phone:606-269-2351

CAGE:02697

===== Composition/Information o

n Ingredients =====

Ingred Name:NITROGEN

CAS:7727-37-9

RTECS #:QW9700000

Fraction by Wt: 100%

ACGIH TLV:ASPHYXIAN; 9192

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:ASPHYXIATION. OVEREXPOSURE TO
HIGH CONCENTRATIONS IN THE ABSENCE OF OXYGEN MAY CAUSE DIZZINESS,
DROWSINESS AND UNCONSCIOUSNESS. CHRONIC: UNKNOWN.

Effects of Overexposure:ASPHYXIATION, DIZZINESS, DROW
SINESS AND
UNCONSCIOUSNESS.

Medical Cond Aggravated by Exposure:LUNG DISEASES.

===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN. GET MEDICAL HEP
IMMEDIATELY.

===== Fire Fighting Measures =====

Extinguishing Media:NONFLAMMABLE GAS. USE MEDIA SUITABLE FOR THE
SURROUNDING FIRE. COOL CYLINDERS BY SPRAYING WATER.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR PROTECTIVE CLOTHING
AND SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:GAS CYLINDERS MAY RUPTURE OR EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE PERSONNEL. VENTILATE AREA. STOP LEAK
IF POSSIBLE.

===== Handling and Storage =====

Handling and Storage Precautions:PROTECT CYLINDERS AGAINST PHYSICAL
DAMAGE. HANDLE WITH CARE.

Other Precautions:STORE BELOW 125F.

===== Exposure C

ontrols/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. USE NIOSH APPROVED
SELF-CONTAINED BREATHING APPARATUS IF TLV IS EXCEEDED OR WHEN USING
IN CONFINED SPACES.

Ventilation:GENERAL

Protective Gloves:LEATHER OR CLOTH

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:NONE

Work Hygienic Practices:KEEP CYLINDERS FASTENED.

Supplemental Safety and Health

CAPACITY: 232 CU IN.= 3.7809 LITERS= 0.72 LBS AT 1000 PSI.

===== Physical/Chemical

Properties =====

HCC:G3

Boiling Pt:B.P. Text:-321F,-196C

Vapor Density:0.97 @70F

Evaporation Rate & Reference:GAS

Solubility in Water:SLIGHT

Appearance and Odor:COLORLESS AND ODORLESS GAS.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:HIGH TEMPERATURES.

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

=====

Waste Disposal Methods:RETURN CYLINDERS TO MANUFACTURER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibi

lity for the suitability of this information to their particular situation.