Product ID:MOBIL JET OIL II MSDS Date:05/21/1993 FSC:9150 NIIN:00-913-9717 MSDS Number: CBQMD === Responsible Party === Company Name: MOBIL OIL CORP Address:3225 GALLONS ROAD City:FAIRFAX State:VA ZIP:22037-0001 Country:US Info Phone Num:800-662-4525/800-227-0707 X3265 Emergency Phone Num:609-737-4411/CHEMTREC 800-424-9300 CAGE:3U728 === Contractor Identification === Compa ny Name: MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING Address:3225 GALLOWS ROAD Box:City:FAIRFAX State:VA ZIP:22037 Country:US Phone:800-662-4525/856-224-4644 CAGE:3U728

Ingred Name:CONTAINS 1 OR MORE OF THE FOLLOWING (INGREDS 2, 3) BASE OILS. Fraction by Wt: >90.00% Other REC Limits:NONE RECOMMENDED

Ingred Name:SYNTHETIC ESTERS, NEW JERSEY TRADE SECRET 003066009-5088P. Other REC Limits:NONE RECOMMENDED

Ingred

Name:SYNTHETIC ESTERS, NJT 003066009-5234P. Other REC Limits:NONE RECOMMENDED

Ingred Name:TRICRESYLPHOSPHATE; (PHOSPHORIC ACID, TRIS(METHYLPHENYL) ESTER). CAS:1330-78-5 RTECS #:TD0175000 Fraction by Wt: 3.00% Other REC Limits:NONE RECOMMENDED Ingred Name: P, P'-DIOCTYLDIPHENYLAMINE; (BENZENEAMINE, 4-OCTYL-N-(4-OCTYLPHENYL)-) CAS:101-67-7 RTECS #:JJ8850000 Fraction by Wt: 246C Autoignition Temp: Autoignition Temp Text: NP Lower Limits:NE **Upper Limits:NE** Extinguishing Media:CARBON DIOXIDE, F OAM, DRY CHEMICAL, WATER FOG. Fire Fighting Procedures:WATER/FOAM CAUSE FROTHING.KEEP FIRE EXPO CNTNR COLL W/WATER.FLUSH SPILLS AWAY FRM EXPO W/WATERSPRAY.FIRE IN ENCLSD AREA MUST USE SCBA.PREVENT RUNOFF(FIRE/EXPO) Unusual Fire/Explosion Hazard:NONE. FIREFIGHTING:FRM FIRE CONTROL/DILUT FRM ENTERING STREAMS/SEWERS/DRINKING WATER SUPPLY. Spill Release Procedures: REPORT AS REQUIRED TO APPROP AUTHORITIES.REPORT SPI

LLS THAT COULD REACH WATERWAY TO US COAST GUARD 800-424-8802.ABSORB ON FIRE RETARDANT TREATRED SAWDUST/DIATOMACEOUS EARTH/ETC.SHOVELUP/DISPO @APPROP WASTE DISPO FACILITY IAW CURR APPLI LAW/REGS/CHARA Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: MOBIL PRODUCTS ARE NOT FORMULATED TO CONTAIN PCBS.

======= Exposure Controls/Personal Protection ==========

Respirat

ory Protection:APPROVED RESPIRATORY PROTECTION EPMT MUST BE USED WHEN MIST CONCENTRATIONS EXCEED SUGGESTED EXPOSURE LIMITS. Ventilation:USE LOCAL EXHAUST IF OIL MISTS EXCEED WORKPLACE AIRBORNE CONCENTRATIONS OF 5MG/M3. Protective Gloves:OIL IMPERVIOUS GLOVES. Eye Protection:SAF GLASSES W/SIDE SHIELDS,CHEM TYP GOGG Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices:GOOD PER HYGIENE PRAC SHOULD ALWAYS BE FOLLOWED.WASH WELL BEF EAT/SMOKE.KEEP AWAY FRM FEE D/FOOD PROD. Supplemental Safety and Health 1STAID:ANYTHING BY MOUTH IF UNCONSC.DOCTOR:PRODUCT CONTAINS TCP WHICH CAN INHIBIT CHOLINESTERASE & MAY PRODUCE DELAYED NEUROTOXICITY.TREAT APPROPRIATELY. DISPO:COMPLIANCE W/APPLICABLE

NEUROTOXICITY.TREAT APPROPRIATELY. DISPO:COMPLIANCE W/APPLICABLE LAWS/REGS/PROD C HARACT @DISPO TIME.UNUSED PROD:NOT SPECLISTED BY EPA AS HAZ WASTE.USED PROD MAY BE REG.NOT APPLICABLE.NO SARA 313 CHEMS

HCC:V6 Boiling Pt:B.P. Text:>600F,>316C Melt /Freeze Pt:M.P/F.P Text:NA Decomp Temp:Decomp Text:NP Vapor Pres: