

DOW CORNING CORP. -- MOLYKOTE(R) 3400A CORROSION PROTECTIVE COATING --
9150-00-948-6912

===== Product Identification =====

Product ID:MOLYKOTE(R) 3400A CORROSION PROTECTIVE COATING

MSDS Date:11/11/1992

FSC:9150

NIIN:00-948-6912

MSDS Number: CBSCW

=== Responsible Party ===

Company Name:DOW CORNING CORP.

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Nu

m:517-496-5900

Emergency Phone Num:517-496-5900

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:ANTIMONY TRIOXIDE (SARA 313) (CERCLA

)
CAS:1309-64-4
RTECS #:CC5650000
Fraction by Wt: 12% %
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.5 MG (SB)/M3
ACGIH TLV:0.5 MG (SB)/M3; 9596
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:BASIC LEAD PHOSPHITE
CAS:12141-20-7
Fraction by Wt: 4% %
Other REC Limits:NONE SPECIFIED
OSHA PEL:RULE IN PROCESS
ACGIH TLV:0.15 MG PB/M3

Ingred Name:TOLUENE (SARA 313) (CERCLA)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 29% %
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM; Z-2
ACGIH TLV:S, 50
PPM; 9596
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 15% %
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300STEL;9596
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 15% %
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9596

Ingred Name:MOLYBDENUM DISULFIDE
CAS:

1317-33-5
RTECS #:QA4697000
Fraction by Wt: 12% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG MO/M3
ACGIH TLV:5 MG MO/M3

Ingred Name:BISPHENOL A EPOXY RESIN
CAS:25036-25-3
Fraction by Wt: 9% %
Other REC Limits:NONE RECOMMENDED

Ingred Name:PHENOL FORMALDEHYDE RESIN
CAS:9003-35-4
Fraction by Wt: 3% %
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NOT GIVEN FOR PRODUCT.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:DIRECT EYE CONTACT IRRITATES. SKIN CONTACT IRRITATES. REPEATED/PROLONGED SKIN CONTACT MAY CAUSE ALLERGIC SKIN SENSITIZATION. INHALATION MAY CAUSE DROWSINESS AND IRRITATE NOSE AND THROAT; MAY INJURE LUNGS, BLOOD, LIVER, KIDNEYS, NERVOUS SYSTEM, HEART, EYES. INGESTION OF SMALL AMOUNTS WILL NOT INJURE. ASPIRATION HAZARD.
Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.
Effects of Overexposure:EYE IRRITATION, REDNESS, SWELLING, SOME CORNEAL INJURY; SKIN IRRITATION, RASH; DROWSINESS, NOSE/THROAT IRRITATION, INJURY TO BLOOD, LUNGS, LIVER, KIDNEYS, NERVOUS SYSTEM, HEART, EYES, NAUSEA, CHEMICAL PNEUMONIA.PROLONGED ETHYL ALCOHOL OVEREXPOSURE HAVE CAUSED HUMAN BIRTH DEFECTS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSIST, GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. IF OCCURS, KEEP HEAD BELOW HIPS. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:50.0F,10.0C
Lower Limits:NOT GIVEN
Upper Limits:NOT GIVEN
Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM
Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR.
Unusual Fire/Explosion Hazard:VAPOR IS FLAMMABLE AND HEAVIER THAN AIR AND MAY TRAVEL TO SOURCE OF IGNITION AND FLASHBACK.

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL. REMOVE ALL SOURCES OF IGNITION AND WEAR PROPER PROTECTION EQUIPMENT.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED AND AWAY FROM HEAT, SPARKS AND OPEN FLAME.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS ADEQUATE OR AIR SAMPLING DATA SHOW EXPOSURES ARE WITHIN TLV AND PEL GUIDELINES. ORGANIC VAPOR TYPE RECOMMENDED.
Ventilation:LOCAL EXHAUST AND MECHANICAL VENTILATION RECOMMENDED.
Protective Gloves:RUBBER OR PLASTIC
Eye Protection:CHEMICAL WORKERS GOGGLES
Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.
Work Hygienic Practices

ractices:WASH HANDS THOROUGHLY WITH SOAP AND WATER
BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.
Supplemental Safety and Health
THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING; USE AT ELEVATED
TEMPEARTURES, OR AEROSOL/SPRAY APPLICATIONS, MAY REQUIRE ADDED
PRECAUTIONS.

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:176F,80C
Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN
Vapor Pres:NOT GIVEN
Vapor Density:3
Spec Gravity:1.16

Evaporation Rate & Reference:NOT GIVEN
Solubility in Water:NOT GIVEN
Appearance and Odor:GRAY-BLACK LIQUID, SOLVENT ODOR
Percent Volatiles by Volume:60 %

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING MATERIALS
Stability Condition to Avoid:STATIC ELECTRICITY MAY ACCUMULATE AND
IGNITE VAPORS. USE BONDING AND GROUNDING.
Hazardous Decomposition Products:METAL OXIDES, SULFUR OXIDES, CARBON
DIOXIDE, TRACES OF INC
OMPLETELY BURNED CARBON PRODUCTS.

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING
ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR
LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in

no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.