

DYNAMOLD, INC. -- MR-502 CATALYST (MAGNETIC RUBBER INSPECTION MATERIAL) --
6850-01-037-9015

===== Product Identification =====

Product ID:MR-502 CATALYST (MAGNETIC RUBBER INSPECTION MATERIAL)

MSDS Date:06/01/1995

FSC:6850

NIIN:01-037-9015

Kit Part:Y

MSDS Number: CBSFQ

=== Responsible Party ===

Company Name:DYNAMOLD, INC.

Address:2905 SHAMROCK AVE

Box:9617

City:FORT WORTH

State:TX

ZIP:76107

Info Ph

one Num:817-335-0862

Emergency Phone Num:817-335-0862

CAGE:30256

=== Contractor Identification ===

Company Name:DYNAMOLD SOLVENTS, INC.

Address:2905 SHAMROCK AVE

Box:9617

City:FORT WORTH

State:TX

ZIP:76107

Country:US

Phone:817-335-0862

CAGE:30256

===== Composition/Information on Ingredients =====

Ingred Name:DIBUTYLTIN DILAURATE

CAS:77-58-7

RTECS #:WH7000000

Fraction by Wt: 0.05-2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.1 MG SN/M3 SKIN

ACGIH TLV:0.1 MG SN/M3

=====

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN CONTACT IS NOT KNOWN TO CAUSE
IRRIT. EYE CONTACT MAY CAUSE TRANSIENT EYE IRRIT.
Explanation of Carcinogenicity:PER MSDS:CHEM/COMPONENT LISTED AS
CARCINOGEN OR POTENTIAL CARCINOGE:NONE.
Effects of Overexposure:TRANSIENT EYE IRRITATION.
Me
dical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR IMMED.GIVE OXY/ART RESP AS
NEEDED.GET EMERG MED ATTN.PROMPT ATTN ESSENTIAL.EYE:IMMED RINSE
W/CLEAN WATER 15-20MINS.RETRACT EYELIDS.IRRIT OCCURS GET EMERG MED
ATTN.SKIN:REMOVE CONTAMIN CLOTH AS NEEDED.WASH SKIN WELL W/MILD
SOAP/WATER.STICKY USE WATERLESS CLEANER 1ST.INGEST:LG QUANT GIVE
LUKEWARM WATER(PINT
) IF COMPLETELY CONSC/ALERT.DON'T INDUC
VOMIT.GETEMERG MED ATTN.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:265F,129C
Autoignition Temp:Autoignition Temp Text:NP
Lower Limits:NP
Upper Limits:NP
Extinguishing Media:DRY CHEMICAL, CO2, WATER SPRAY.
Fire Fighting Procedures:DON'T ENTER FIRE AREA W/O PROPER PROT.FIGHT
FRM SAFE DIST/PROT LOCA.USE H2OSPRAY/FOG FOR COOLING.DRY CHEM CO
PERMISSIBLE.NOTIFY AUTHOR IF ENTER SEWER/PUB
H2O.
Unusual Fire/Explosion Hazard:HEAT MAY BUILD PRESSURE/RUPTURE CLSD
CNTNR SPREAD FIRE INCR RISK OF BURN/INJURY.AVOID EXTREME HEAT/FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:UTILIZE PPE.LIMIT ACCESS TO QUAL PERSON.SOAK
UP W/INERT SOLIDS.PLACE IN LABEL/SEAL CNTNR.PREVENT FLOW TO
SEWERS.NOTIFY FIRE/ENVIRO AUTHORITIES.COVER SLIPPERY SURFACE
W/GRANULAR SOLID.CONTAIN SPILL TO PREVENT ESCAPE INTO ENVIRO.
Neutralizing Agent:N

ONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY AREA.STORE ONLY IN
CLSD CNTNR AWAY FROM IGN SOURCES PRACTICE CAUTION.AVOID SKIN/EYE
CONTACT.

Other Precautions:KEEP CNTNRS CLSD WHEN NOT IN USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NEEDED.

Ventilation:GENERAL.

Protective Gloves:NONE SHOULD BE NEEDED.

Eye Protection:CHEMICAL SPA

LSH GOGG(ANSI Z67.1 1979).

Other Protective Equipment:NONE SHOULD BE NEEDED.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

PER TIR:KIT:1 GALLON OF MAGNETIC RUBBER MATL(BASE),2OZ BTL OF
CATALYST,1OZ BTL OF CURE STABILIZER. MFG HAS SUPPLIED 1 MSDS
W/INGRED FOR BASE & CATALYST;NO MENTION OF CURE STABILIER. THIS
RECORD FOR CA TALYST MATL;BASE RECORD SEE PNIND:D.

===== Physical/Chemical Properties =====

HCC:N1

Boiling

Pt:B.P. Text:>300F,>149C

Melt/Freeze Pt:M.P/F.P Text:NP

Decomp Temp:Decomp Text:NP

Vapor Pres:1 @20C

Vapor Density:NEG

Spec Gravity:1.0

pH:NP

Viscosity:NP

Evaporation Rate & Reference: