CRC CHEMICALS U.S.A./CRC INDUSTRIES, INC. -- 5018, 5018T LECTRA MOTIVE (AEROSOL) -- 6850-01-244-9614

Product ID:5018, 5018T LECTRA MOTIVE (AEROSOL) MSDS Date:05/26/1994 FSC:6850 NIIN:01-244-9614 MSDS Number: CBSJX === Responsible Party === Company Name: CRC CHEMICALS U.S.A./CRC INDUSTRIES, INC. Address:885 LOUIS DRIVE **City:WARMINSTER** State:PA ZIP:18974-2820 Country:US Info Phone Num:215-674-4300 Emergency Phone Num:800-424-930 0(CHEMTREC) Preparer's Name: ADAM SELISKER CAGE:10136 === Contractor Identification === Company Name: CRC INDUSTRIES, INC. Address:885 LOUIS DRIVE Box:City:WARMINSTER State:PA ZIP:18974-2869 Country:US Phone:215-674-4300/ 800-521-3168 CAGE:023V4 Company Name: CRC INDUSTRIES, INC. Address:885 LOUIS DRIVE Box:City:WARMINSTER State:PA ZIP:18974-2820 Country:US Phone:215-674-4300/800-424-9300 CAGE:10136

Ingred Name:METHYLENE CHLORID

E (SARA 313) (CERCLA) (DICHLOROMETHANE) CAS:75-09-2 RTECS #:PA8050000 Fraction by Wt: 1-20% Other REC Limits:NONE RECOMMENDED OSHA PEL:500 PPM; Z-2 ACGIH TLV:50 PPM, A2; 9596 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:PERCHLOROETHYLENE (TETRACHLOROETHYLENE) (SARA 313) (CERCLA) CAS:127-18-4 RTECS #:KX3850000 Fraction by Wt: 70-100% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 PPM, Z-2 ACGIH TLV:25PPM/100STEL,A3; 96 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:CARBON DIOXIDE CAS:124-38-9 RTECS #:FF6400000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED OSHA PEL:5000 PPM ACGIH TLV:5000PPM/30000STEL;96

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:ACUTE:INHAL:HEADACHES, DIZZINESS, ANESTHESIA, UNCONSCIOUSNESS. EYE:CAUSES PAIN, SOME IRRIT.

SKIN:IRRIT ON REPEATED EXPOSURE. CHRONIC:REPEATED OVEREXPO HAVE CAUSED LIVER & KIDNEY EFFECTS IN ANIMALS. Explanation of Carcinogenicity:PER MSDS:NTP/IARC/OSHA:YES.TETRACHLOROETHYLENE,DICHLOROMETHANE.HMIS:OSH A-NONE.NTP/IARC-DICHLOROMETHANE,(SEE OTHER PRECA) Effects of Overexposure:HEADACHES, DIZZINESS, ANESTHESIA, UNCONSCIOUSNESS, EYE PAIN, IRRIT. SKIN IRRIT. Medical Cond Aggravated by Exposure:RISK TO YOUR HEALTH DEPEDNS ON DURATION & LEVEL OF EXPOSURE.

First Aid:IF SYMPTOMS PERSIST CALL PHYSICIAN. INHAL:REMOVE TO FRESH AIR.APPLY ARTIFICIAL RESPIRATION IF NECESSARY. EYE:FLUSH W/LG AMTS OF WATER FOR 15MINS. SKIN:REMOVE CONTAMIN CLOTH.WASH AREA W/SOAP/WATER. ING EST:DO NOT INDUCE VOMIT.CALL PHYSICIAN.

Flash Point Method:TCC Flash Point:NONE Autoignition Temp:Autoignition Temp Text:NP Lower Limits:NA Upper Limits :NA Extinguishing Media:WATER FOG. Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER. Unusual Fire/Explosion Hazard:AEROSOL CONTAINERS MAY EXPLODE WHEN HEATED ABOVE 120F.

Spill Release Procedures:USUALLY NOT A PROBLEM W/AEROSOLS. AREA SHOULD BE VENTILATED & AN ABSORBENT USED TO PICK UP EXCESS MATL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===

Handling and Storage Precautions:STORE IN COOL DRY PLACE.VAPORS ARE HEAVIER THAN AIR.DO NOT USE IN CONFINED SPACE W/OUT ADEQUATE VENTILATION.USE BREATHING APPARATUS IF NECESSARY.

Other

Precautions:CARCINOGEN:NTP-TETRACHLOROETHYLENE;IARC-TETRACHLOROETHY LENE NOT CLASSIFIABLE AS HUMAN CARCI.

Respiratory Protection: ABOVE TLV USE SELF-CONTAINED BREATHING APPARATUS. Ventilation: MAINTAIN VAPOR CONCENTRATION BELOW TLV.USE MECHANICAL MEANS IF NECESSARY.
Protective Gloves:SOLVENT RESISTANT GLOVES.
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:NOT NORMALLY REQUIRED W/AEROSOL PRODUCT USAGE.
Work Hygienic Practices:WASH CONTAMIN CLOTH BEF REUSE.
Supplemental Safety and Health
PER MSDS:GOOD SOLVENT FOR MANY ORGANIC MATLS.

HCC:V2 Boiling Pt:B.P. Text:>250F,>121C Melt/Freeze Pt:M.P/F.P Text:ND Decomp Temp:Decomp Text: NP Vapor Pres:ND Vapor Density:ND Spec Gravity:1.60 @25C pH:NA Viscosity:NP Evaporation Rate & amp; Reference:RAPID, REF NOT GIVEN Solubility in Water:SLIGHT SOLUBILITY Appearance and Odor:COLORLESS LIQUID, IRRIT ODOR @HIGH CONCENTRATIONS. Percent Volatiles by Volume:100 Corrosion Rate:NP

Stability Indicator/Materials to Avoid:YES
AVOID STORAGE IN ALUMINUM CONTAINERS OR CONTACT W/ALUMINUM &/OR ZINC PRODUCTS.
Stability Condition to Avoid:AVOID OPEN FLAMES, ARCS OR HIGH TEMPERATURES.
Hazardous Decomposition Products:THERMAL-HYDROGEN CHLORIDE, CHLORINE, & SOME PHOSGENE.

Waste Disposal Methods:ALL USED & UNSED PRODUCT SHOULD BE DISPOSED OF IN CONFORMANCE W/LOCAL, STATE AND FEDERAL REGULATIONS.CONTAINS CHEM SUBJ TO RELEASE REPORTING UNDER SEC 313 OF SARA TITLE III:DICHLOROMETHANE 1-20%;TETRA CHLOROETHYLENE 70-100%.

Disclaimer (p

rovided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.