View NSN Online: https://aerobasegroup.es/nsn/6525-01-334-8774

Product ID:DENT-X EXCEL X-RAY FIXER (SUPPLEMENTAL) MSDS Date:06/01/1992 FSC:6525 NIIN:01-334-8774 Kit Part:Y MSDS Number: CBSLK === Responsible Party === Company Name: FRC-DIVSION OF CINE MAGNETICS INC Address:524 S COLUMBUS AVE **City: MOUNT VERNON** State:NY ZIP:10550-471 2 Country:US Info Phone Num:914-667-1002 Emergency Phone Num:800-424-9300(CHEMTREC) CAGE:NO452 === Contractor Identification === Company Name: CINE MAGNETICS INC FR CHEMICALS DIV Address:524 S COLUMBUS AVE Box:City:MOUNT VERNON State:NY ZIP:10550-4712 Country:US CAGE:21297 Company Name: DENT-X CORP (914-592-6100) Box:UNKNOW CAGE:4R150 Company Name: FRC-DIVSION OF CINE MAGNETICS INC Address:524 S COLUMBUS AVE Box:City:MOUNT VERNON State:NY ZIP:10550-4712 Country:US Phone:914-667-1002 CAGE:NO452

===

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 60-100% Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM THIOSULFATE CAS:7783-18-8 RTECS #:XN6465000 Fraction by Wt: 7-13% Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM SULFITE CAS:7757-83-7 RTECS #:WE2150000 Fraction by Wt: 3-7% Other REC Limits:NONE RECOMMENDED

Ingred Name:ACETIC ACID (CERCLA) CAS:64-19-7 RTECS #:AF1225000 Fraction by Wt: 3-7% Oth er REC Limits:NONE RECOMMENDED OSHA PEL:10 PPM ACGIH TLV:10 PPM/15 STEL; 9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:VOLITILE ORGANIC CONTENT AS LISTED ON MSDS, VOC=0.15 LBS/GALLON. RTECS #:9999999VC Fraction by Wt: NA Other REC Limits:NONE RECOMMENDED

Ingred Name:VOLATILE ORGANIC CONTENT AS LISTED ON MSDS: 0.10 LB/GAL RTECS #:9999999VC Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYE: IRRIT, BURNING POSSIBLE. HI CONC OF ACETIC ACID VAP CAN CAUSE EXCESS BLINKING, TEAR PRODUCTION, EYE DISCOMFORT.SKIN:IRRIT,BURNING POSSIBLE.INGEST:ACETIC ACID CAN CAUSE BURNING TO MOUTH/THROAT/ESOPHAGU S.ABD PAIN.NAU.VOMIT.SHOCK STATE, COLLAPSE. SODIUM SULFITE MAY CAUSE CIRCULATORY D **ISTURB/CNS** DMG.INHAL: IF HEATED (SUPPLE) Explanation of Carcinogenicity: PER MSDS: CARCENOGENICITY: NOEN OF THE CHEMS USED IN PRODUCT ARE LISTED ON NTP/IARC/OSHA LISTINGS OF HUMAN CARCINOGENS. Effects of Overexposure: EYE: IRRIT, BURN, EXCESS BLINKING, TEAR PRODUCTION, DISCOMFORT. SKIN: IRRIT, BURN. INGEST: MOUTH/THROAT/ESOPHAGUS BURN, ABD PAIN, NAU, VOMIT, SHOCK STATE, COLLAPSE, CIRCULATORY DISTURBANCES/CNS DMG. INHAL: IRRIT THR OAT, IRRIT, COUGH, CHEST PAIN, PAIN/BREATH DIFFICULTY. Medical Cond Aggravated by Exposure:SULFITES MAY CAUSE ALLERGIC REACTIONS IN SOME ASTHMATICS.

First Aid:EYE:FLUSH W/WATER FOR 15MINS.OBTAIN MED ATTN. SKIN:REMOVE CONTAMIN CLOTH.WASH EXPO AREA THOROUGHLY W/WATER.CONTACT PHYSICIAN. INGEST:IF CONSC GIVE 2 GLASSES OF WATER.DO NOT INDUCE VOMIT.OBTAIN PROMPT MED ATTN. INHAL:REMOVE TO FRESH AIR.IF ADVERSE SYMPTOMS DEVELOP CONTACT PHYSICIAN.

======= Fire

Flash Point:NONE Autoignition Temp:Autoignition Temp Text:NP Lower Limits:NA Upper Limits:NA Extinguishing Media:ANY APPLICABLE TO THE PRIMARY CAUSE OF FIRE. Fire Fighting Procedures:EVACUATE PERSONNEL TO SAFE AREA. FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:EXCESSIVE HEAT MAY RELEASE AMMONIA VAPORS.

Spill Release Procedures:USE

APPROPRIATE PROTECTIVE EQPMT.DIKE/SOAK UP W/ABSORBANT MATL.PREVENT LIQ FROM ENTERING SEWERS/WATERWAYS.DISPOSE OF IN ACCORDANCE WITH FED/STATE/LOC REGS. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

 Handling and Storage Precautions:STORE IN WELL VENTI AREA.KEEP CNTNR TIGHTLY CAPPED WHEN NOT IN USE.DO NOT STORE FOOD/DRINK/TOBACCO IN AREAS WHERE CONTAMIN COULD OCCUR W/PRODUCT.
Other Precautions:AVOID BREATH V
AP.AVOID CONTACT EYES/SKIN/CLOTHING.DO

NOT TAKE INTERNALLY.KEEP OUT OF REACH OF CHILDREN.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: FOR POORLY VENTILATED AREAS A NIOSH CARTRIDGE RESPIRATOR IS RECOMMENDED.

Ventilation: TEN ROOM VOLUMES PER HR RECOMMENDED UNDER NORMAL CONDITIONS.

Protective Gloves:LATEX OR NEOPRENE GLOVES.

Eye Protection: CHEM SPLASH GOGGLES.

Other Protective Equipment:LAB COAT, EYE WASH STATION.

Work Hygienic Practices:

WASH CONTAMIN CLOTH BEF REUSE.WASH THOROUGHLY AFTER HNDLG.

Supplemental Safety and Health

CAT#:999-2602-001; 999-2602-201. HEALTH HAZ:HIGHLY IRRIT AMMONIA VAP IRRIT THROAT.HIGH ACETIC ACID CONC IRRIT,COUGH,CHEST PAIN,PAIN/BREATH DIFFI. PER TIR:PKG CONSISTS OF DEVELOPER (SEE PNIND:A) & FIXE R.

HCC:N1 Boiling Pt:B.P. Text:212F,100C Melt/Freeze Pt:M.P/F.P Text:NP Decomp Temp:Decomp Text:NP Vapor Pres:N/AVAI Vapor Density:N/AVAI Spec Gravity:1.10 pH:4.6 Viscosity:NP Evaporation Rate & amp; Reference:N/AVAI Solubility in Water:COMPLETELY. Appearance and Odor:CLEAR, COLORLESS SOLUTION, VINEGAR ODOR. Percent Volatiles by Volume:60-100 Corrosion Rate:NP

Stability Indicator/Materials to Avoid:YES AVOID STRONG ACIDS & STRONG ALKALIS. Stability Condition to Avoid:NONE Hazardous Decomposition Products:SULFUR DIOXIDE AND AMMONIA.

==================

Waste Disposal Methods:DISCHARGE TO SEWER REQUIRES APPROVAL OF PERMITTING AUTHORITY;MAY REQUIRE PRETREATMENT.TREAT/STORAGE/TRASNP/DISPO MUST BE IAW FED/STATE/LOC REGS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.