

MEASUREMENTS GROUP INC -- M-BOND 200 ADHESIVE -- 8040-01-027-1893

===== Product Identification =====

Product ID:M-BOND 200 ADHESIVE

MSDS Date:07/31/1995

FSC:8040

NIIN:01-027-1893

Kit Part:Y

MSDS Number: CBTCV

=== Responsible Party ===

Company Name:MEASUREMENTS GROUP INC

Box:7777

City:RALEIGH

State:NC

ZIP:27611

Country:US

Info Phone Num:919-365-3800

Emergency Phone Num:800-424-9300 CHEMTREC

Prepare

r's Name:R.L. FRIDLEY

CAGE:88952

=== Contractor Identification ===

Company Name:MEASUREMENTS GROUP INC

Address:9517 US 64 HWY

Box:City:WENDELL

State:NC

ZIP:27591

Country:US

Phone:919-365-3800

CAGE:88952

===== Composition/Information on Ingredients =====

Ingred Name:METHYL 2-CYANOACRYLATE

CAS:137-05-3

RTECS #:AS7000000

Fraction by Wt: 80-95%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:2 PPM

ACGIH TLV:2 PPM/4 STEL; 9596

Ingred Name:POLYMETHYLMETHACRYLATE

CAS:9011-14-7

RTECS #:T

R0400000
Fraction by Wt: 5-15%
Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDROQUINONE (SARA 302/313) (CERCLA)
CAS:123-31-9
RTECS #:MX3500000
Fraction by Wt: 0.1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9596
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:ETHYL CYANOACRYLATE
CAS:7085-85-0
Fraction by Wt: 92%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SUPERBOND 496=INGREDIENTS 1,2,3; SICOMET 7000=INGREDIENTS
1,4; METHYL CYANOACRYLATE ADHESIVE=INGREDIENTS
1,2,3.
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:VAPOR IS IRRITATING TO NOSE &
BRONCHIAL PASSAGES. PROLONGED & REPEATED OVER-EXPOSURE TO VAPORS
MAY CAUSE ALLERGIC/ASTHMA-LIKE SYMPTOMS. CONTACT WITH SKIN & EYES
MAY CAUSE BONDING OF SURFACES, MAY CAUSE BURNS UPON
SOLIDIFICATION.
INGESTION MAY CAUSE ADHESION/SOLIDIFICATION IN
MOUTH; LIPS MAY STICK TOGETHER.
Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%
OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:INHALATION-IRRITATION OF BRONCHIAL PASSAGES &
NOSE, ASTHMA-LIKE SYMPTOMS. SKIN-BONDING OF SKIN SURFACES, BURNS.
EYES-BONDING OF EYE SURFACES, BURNS. INGESTION-BONDING OF MOUTH &
LIPS.
Medical Cond Aggravated by Exposure:NONE KNOWN.

=====

===== First Aid Measures =====

First Aid:MOUTH/LIPS/SKIN-IMMERSE BONDED SURFACE IN WARM, SOAPY WATER.
PEEL OR ROLL SURFACES APART; THEN REMOVE ADHESIVE FROM SKIN.
EYES-WASH WITH WARM WATER & APPLY GAUZE PATCH. EYE WILL OPEN IN 1-4
DAYS. DO NOT OPEN THROUGH MANIPULATION. INHALATION-REMOVE TO FRESH
AIR. CALL A PHYSICIAN IF SYMPTOMS PERSIST.INGESTED-DO NOT FORCE
REMOVAL. DO NOT SWALLOW ADHESIVE WHEN IT LOOSENS. SHOULD LIFT IN
12-48 HOURS.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:150F,66C
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED
BREATHING APPARATUS AND FULL FIRE FIGHTER'S PROTECTIVE GEAR.
Unusual Fire/Explosion Hazard:NONE KNOWN.

===== Accidental Release Measures =====

Spill Release Procedures:FLOOD WITH WATER TO POLYMERIZE CYANOCRYLATE
ADHESIVE AND TO
CONTROL PRODUCT VAPORS. SOAK UP WITH INERT
ABSORBENT OR SCRAPE UP CURED PRODUCT.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AT OR BELOW 75F TO MAXIMIZE
SHELF LIFE. AVOID CONTACT WITH SKIN & EYES. AVOID BREATHING VAPORS.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEER
ING CONTROLS FAIL OR NON-ROUTINE USE
OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR WITH
ORGANIC VAPOR CARTRIDGE OR AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS
REQUIRED. USE IAW 29 CFR 1910.134.
Ventilation:POSITIVE DOWN-DRAFT EXHAUST VENTILATION SHOULD BE PROVIDED
TO MAINTAIN VAPOR CONCENTRATION BELOW TLV(S).
Protective Gloves:POLYETHYLENE. DO NOT USE COTTON.
Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.
Other Protective Equipment:POLYETHYLENE APRON RECOMMEN

DED.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

KEY1=F8. ADHESIVE OF 2 PART ADHESIVE KIT. SEE PNI B FOR CATALYST FOR
ADHESIVE. MFR/WRITER OF MSDS ACTUALLY BUYS 3 DIFFERENT PRODUCTS FOR
THE ADHESIVE- SUPER BONDER 496 BY LOCTITE; SICOMET 7000 BY HENK LE
ADHESIVES; METHYL CYANOACRYLATE ADHESIVE BY CHEMENCE INC.

===== Physical/Chemical Properties =
=====

HCC:V4

Boiling Pt:B.P. Text:>150F,>66C

Vapor Pres:1

Spec Gravity:1.09

Evaporation Rate & Reference:NOT DETERMINED

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR LIQUID; PUNGENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER, ALCOHOLS, AMINES, ALKALIES, PEROXIDES, COTTON, WOOL.

Stability Condition to Avoid:HIGH TEMPERATURES (>=150F).

Hazardous Decomposition Products:NONE KNOWN.

Conditions

to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.