

MARATHON POWER TECHNOLOGIES -- NICKEL CADMIUM BATTERY P/N 19205-001 --
6135-01-051-7836

===== Product Identification =====

Product ID:NICKEL CADMIUM BATTERY P/N 19205-001
MSDS Date:11/01/1995
FSC:6135
NIIN:01-051-7836
MSDS Number: CBTDC
=== Responsible Party ===
Company Name:MARATHON POWER TECHNOLOGIES
Address:8301 IMPERIAL DRIVE
Box:8233
City:WACO
State:TX
ZIP:76714-8233
Country:US
Info Phone Num
:817-776-0650
Emergency Phone Num:817-776-0650,800-424-9300(CHEMTREC)
CAGE:74025

=== Contractor Identification ===

Company Name:CAMPBELL INDUSTRIES (209-464-0132)
Box:UNKNOWN
CAGE:1EB31
Company Name:MARATHON POWER TECHNOLOGIES CO
Address:8301 IMPERIAL DR
Box:City:WACO
State:TX
ZIP:76712-6588
Country:US
Phone:254-741-5405
CAGE:74025

===== Composition/Information on Ingredients =====

Ingred Name:CADMIUM (SARA 313) (CERCLA)
CAS:7440-43-9
RTECS #:EU9800000
Other REC Limits:NONE SP

ECIFIED
OSHA PEL:0.2 MG/M3 DUST; Z-2
ACGIH TLV:0.01 MG/M3 DUST;9596
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:CADMIUM HYDROXIDE
CAS:21041-95-2
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.05 MG CD/M3
ACGIH TLV:0.05 MG CD/M3

Ingred Name:NICKEL (SARA 313) (CERCLA)
CAS:7440-02-0
RTECS #:QR5950000
Other REC Limits:NONE SPECIFIED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9596

Ingred Name:NICKEL HYDROXIDE (SARA 313) (CERCLA)
CAS:12054-48-7
RTECS #:QR7040000
Other REC Limits:NONE SPECIFIED
OSHA PEL:
1 MG(NI)/M3
ACGIH TLV:0.1 MG(NI)/M3; 9596
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:POTASSIUM HYDROXIDE (CERCLA)
CAS:1310-58-3
RTECS #:TT2100000
Other REC Limits:NONE SPECIFIED
OSHA PEL:C 2 MG/M3
ACGIH TLV:C 2 MG/M3; 9596
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:UNDER NORMAL

CONDITIONS OF USE, NO
EXPOSURE TO HAZARDOUS COMPOUNDS EXISTS. IF INCINERATED, INHALATION OF FUMES MAY CAUSE RESPIRATORY SYSTEM IRRITATION, FUMES WILL IRRITATE EYE TISSUE (ACUTE) ; CHRONIC EXPOSURE MAY CAUSE KIDNEY DYSFUNCTION AND LUNG INJURY.
Explanation of Carcinogenicity:NICKEL AND CADMIUM ARE LISTED AS POTENTIAL CARCINOGENS BY NTP, IARC AND OSHA.
Effects of Overexposure:IF INCINERATED, CHEST PAIN, COUGHING, SWEATING, CHILLS, SHORTNESS OF BREATH AND WEAKNESS ALONG WITH POSSIBLE EYE IRRITATION.
Medical Cond Aggravated by Exposure:IF INCINERATED, RESPIRATORY SYSTEM DISORDERS, PROSTATE DISORDERS, LIVER AND KIDNEY DISORDERS, VISION PROBLEMS.

===== First Aid Measures =====

First Aid:IF CONTACT WITH POTASSIUM HYDROXIDE ELECTROLYTE, FLUSH WITH WATER FOR 15 MINUTES AND CONTACT PHYSICIAN; IF INHALED, REMOVE FROM EXPOSURE AND CONTACT PHYSICIAN.

===== Fire Fighting Measures =====
=====

Flash Point:NONE.
Lower Limits:NOT GIVEN
Upper Limits:NOT GIVEN
Extinguishing Media:USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR PROPER PROTECTIVE EQUIPMENT AND SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE-PIECE OPERATED IN POSITIVE PRESSURE MODE.
Unusual Fire/Explosion Hazard:CONTACT WITH STRONG OXIDIZERS MAY CAUSE FIRE OR EXPLOSION. CADMIUM AND NICKEL FUMES ARE TOXIC AND CAN CAUSE DEATH.

=====
===== Accidental Release Measures =====

Spill Release Procedures:BATTERY AND CELL CASES WILL NORMALLY CONTAIN MATERIALS OF CONCERN. USE INDUSTRIAL ABSORBENT TO COLLECT LIQUID POTASSIUM HYDROXIDE.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT INVERT. AVOID BREAKING, CRUSHING OR OTHERWISE DESTROYING THE PHYSICAL INTEGRITY OF THE CELL OR BATTERY.
Other

Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:POTASSIUM HYDROXIDE SOLUTION WEAR A DUST OR MIST MASK.

Ventilation:USE ADEQUATE LOCAL EXHAUST VENTILATION WHEN HANDLING THE LIQUID.

Protective Gloves:RUBBER GLOVES FOR HANDLING LEAKERS.

Eye Protection:EYE GOGGLES AND FACE SHIELD FOR LEAKERS.

Other Protective Equipment:FOR HANDLING INGREDIENTS, WEAR CLOTHING TO MINIMIZE SKIN CONTACT.

Work Hygienic P

ractices:WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:B1

Boiling Pt:B.P. Text:NOT GIVEN

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:NOT GIVEN

Vapor Density:NOT GIVEN

Spec Gravity:NOT GIVEN

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:NOT GIVEN

Appearance and Odor:BATTERY. NO ODOR.

Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, NITRATES, NITRIC ACID.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:CELLS AND BATTERIES MAY BE RETURNED AT SENDERS EXPENSE TO MARATHON POWER TECH

NOLOGIES. DISPOSAL SHALL BE BY
APPROVED METHODS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.