

FLAMEMASTER CORP -- CS3202 PART B -- 8030-00-275-8110

===== Product Identification =====

Product ID:CS3202 PART B

MSDS Date:12/30/1994

FSC:8030

NIIN:00-275-8110

Kit Part:Y

MSDS Number: CBTMH

=== Responsible Party ===

Company Name:FLAMEMASTER CORP

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352

Country:US

Info Phone Num:818-982-1650

Emergency Phone Num:800-424-9300(CHEMTREC)

CAGE:14439

=== Contractor Identification ===

Company Name:FLAMEMASTER CORP

THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

===== Composition/Information on Ingredients =====

Ingred Name:LEAD DIOXIDE (IN THIS PRODUCT AIRBORNE PARTICLES WON'T
RESULT FROM NORMAL USE)

CAS:1309-60-0

RTECS #:OG0700000

Fraction by Wt: 64.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.05 MG/M3

ACGIH TLV:0.15 MG/M3

Ingred Name:LEAD OXIDE (IN THIS PRODUCT AIRBORNE PARTICLES WON'T RESULT

FROM NORMAL USE)
CAS:1317-36-8
RTECS #:OG1750000
Fraction by Wt: 6.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.05 MG/M3
ACGIH TLV:0.15 MG/M3

Ingred Name:VOC = 1.0 G/L
RTECS #:9999999VO
Fraction by Wt: NA
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic
:ACUTE: WEAKNESS, STOOPE. CHRONIC:
KIDNEY DAMAGE, ANEMIA, REPRODUCTIVE EFFECTS.
Effects of Overexposure:HEADACHE, MUSCLE, JOINT PAIN. NEUROMUSCULAR
DYSFUNCTION.
Medical Cond Aggravated by Exposure:ANEMIA, KIDNEY DISEASE, PREGNANCY.

===== First Aid Measures =====

First Aid:INGESTION: INDUCE VOMITING. CONSULT DR IMMEDIATELY. EYES:
FLUSH W/LARGE AMTS WATER & CONTACT DR.

===== Fire Fighting Measures =====

Flash
Point Method:TCC
Flash Point:>200F,>93C
Lower Limits:NONCOMBUST
Upper Limits:NONCOMBUST
Extinguishing Media:FOAM, DRY CHEMICAL, CO2, WATER.
Fire Fighting Procedures:USE SCBA W/FULL FACEPIECE IN CONFINED AREAS.
Unusual Fire/Explosion Hazard:FIRE HAZARD EXISTS IF CONTACT
W/OXIDIZABLE MATERIALS AT HIGH TEMPERATURES OCCURS.

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP & TRANSFER TO A SAFETY CONTAINER.

===== Handling and

Storage =====

Handling and Storage Precautions:STORE IN COOL AREA. KEEP CONTAINERS CLOSED.

Other Precautions:WASH HANDS BEFORE EATING, DRINKING, SMOKING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF SOOT FORMED, USE NIOSH APPROVED RESPIRATOR.

Ventilation:LOCAL EXHAUST, AIR HOOD, MECHANICAL FAN.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:APPROPRIATE TO AVOID PROLONGED CONTACT

Work Hyg

ienic Practices:TRAIN PERSONNEL IN THE SAFE HANDLING OF THIS PRODUCT.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:644F,340C

Melt/Freeze Pt:M.P/F.P Text: