

GE SILICONES -- DBT STANNANE, DIBUTYL BIS(1-OXODODECYL) -- 6850-01-119-1932

===== Product Identification =====

Product ID:DBT STANNANE, DIBUTYL BIS(1-OXODODECYL)

MSDS Date:08/22/1995

FSC:6850

NIIN:01-119-1932

Kit Part:Y

MSDS Number: CCBGH

=== Responsible Party ===

Company Name:GE SILICONES

Address:260 HUDSON RIVER RD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone Num:518-237-3330

Emergency Phone Num:518-237-3330

Preparer's Name:CE HANNIGAN

CAGE:GESIL

=== Contractor Identification ===

Company Name:GE SILICONES

Address:260 HUDSON RIVER ROAD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330

CAGE:GESIL

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

===== Composition/Information on Ingredients =====

Ingred Name:STANNANE, DIBUTYLBIS(LAUROYLOXY)-; (DIBUTYL TIN DILAURATE)

CAS:77-

58-7
RTECS #:WH7000000
Fraction by Wt: 80-99%
OSHA PEL:0.1 MG SN/M3 SKIN
ACGIH TLV:0.1 MG SN/M3

===== Hazards Identification =====

LD50 LC50 Mixture:LD50:(ORAL,RAT) 1,470 MG/KG
Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:INGESTION:HARMFUL IF SWALLOWED.
SKIN CONTACT:CAUSES MODERATE SKIN IRRITATION. HARMFUL IF ABSORBED
THRU SKIN. INHALATION:VAPORS GIVEN
OFF BY HEATED PRODUCT MAY BE
HARMFUL. EYE:CAUSES SEVERE EYE IRRITATION. CHRONIC:TARGET ORGAN
EFFECTS:CENTRAL NERVOUS SYSTEM DAMAGE.
Explanation of Carcinogenicity:NOT RELEVANT.
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:CENTRAL NERVOUS SYSTEM DISORDERS.

===== First Aid Measures =====

First Aid:INGEST:DO NOT INDUCE VOMIT. SLOWLY DILUTE WITH 1-2 GLASSES OF
WATER/MILK & SEEK MED ATTN. NEVER GIVE ANYTHING BY M
OUTH TO UNCON
PERSON. SKIN:REMOVE CONTAMD CLTHG & LAUNDER BEFORE REUSE. WASH
W/SOAP & WATER. GET MED ATTN IF IRRIT PERSISTS. INHAL:MOVE PERSON
TO FRESH AIR. EYES:IN CASE OF CONT/SUSPECTED CONTACT, IMMED FLUSH
W/PLENTY OF WATER FOR AT LEAST 15 MINS & GET MED ATTN IMMED AFTER
FLUSHING.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:455F,235C
Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA.
Fire Fighting Procedures:
NONE KNOWN. USE NIOSH/MSHA APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:SENSITIVITY TO STATIC DISCHARGE IS NOT
EXPECTED.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE, SCRAPE OR SOAK UP IN AN INERT MATERIAL &
PUT IN A CNTNR FOR DISPOSAL. WEAR PROPER PROT EQUIP AS SPECIFIED IN
THE PROTECTIVE EQUIPMENT SECTION. WARN OTHER WORKERS OF SPILL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.
AVOID CONTACT WITH SKIN AND EYES.
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE KNOWN. NIOSH/MSHA APPROVED RESPIRATOR
APPROPRIATE FOR EXPOSURE OF CONCERN .
Ventilation:USE ONLY IN WELL VENTILATED AREA.
Protective Gloves:RUBBER GLOVES.
Eye Protection:ANSI APP
RVD CHEM WORKERS GOGGLES .
Other Protective Equipment:RUBBER APRON. ANSI APPRVD EMERGENCY EYE WASH
& DELUGE SHOWER .
Work Hygienic Practices:WASH HANDS BEFORE EATING AND SMOKING.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:400F,204C
Vapor Pres:NEGLIGIBLE
Vapor Density:21.8
Spec Gravity:1.035 (WATER=1)
VOC Pounds/Gallon:27
Evaporation Rate & Reference: