

MSDS Safety Information

FSC: 8030
NIIN: 01-198-6053
MSDS Date: 08/11/1992
MSDS Num: CCJBG
Product ID: 3M BRAND ACRYL-RED PUTTY P/N 5966
MFN: 01
Responsible Party
Cage: 52157
Name: 3M AUTOMOTIVE TRADES DIV
Address: 3M CENTER
City: ST PAUL MN 55144-1000
Info Phone Number: 612-733-1110
Emergency Phone Number
: 612-733-1110
Review Ind: Y
Published: Y

Contractor Summary

Cage: 04963
Name: 3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV
Address: 3M CTR
City: SAINT PAUL MN 55144-1000
Phone: 800-364-3577/651-737-6501(24 HOURS)
Cage: 52157
Name: MINNESOTA MINING AND MFG CO AUTOMOTIVE TRADES DIV
Address: 3M CTR
City: ST PAUL MN 55144-1000
Phone: 612-737-4114
Cage: 050Q3
Name: NAPA, A DIVISIO
N OF LINCOLN AUTOMOTIVE
Address: ONE LINCOLN WAY
City: ST. LOUIS MO 63120-1578
Phone: 414-255-5520

Item Description Information

Item Manager: GSA
Item Name: PUTTY
Specification Number: UNKNOWN
Unit of Issue: TU
Quantitative Expression: 00000000021OZ
UI Container Qty: 0
Type of Container: TUBE

Ingredients

=====

Cas: 14807-96-6
RTECS #: MW2700000
Name: TALC (CONTAINING ASBESTOS)
% Wt: 50-60
Other REC Limits: NONE SPECIFIED
OSHA PEL: 0.2 FIBERS/CC
ACGIH TLV: 0.2 FIBER/CC,A1;9596

Cas: 108-88-3
RTECS #: XS5250000
Name: TOLUENE (SARA 313) (CERCLA)
% Wt: 10-20
Other REC Limits: NONE SPECIFIED
OSHA PEL: 200 PPM; Z-2
ACGIH TLV: S, 50 PPM; 9596
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 123-86-4
RTECS #: AF735000
0
Name: N-BUTYL ACETATE (CERCLA)
% Wt: 5-15
Other REC Limits: 375 MG/CUM
OSHA PEL: 150 PPM
ACGIH TLV: 150 PPM/200STEL;9596
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 117-81-7
RTECS #: TI0350000
Name: DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYLPHTHALATE) (SARA 313) (CERCLA)
% Wt: 1-10
Other REC Limits: 150 PPM
OSHA PEL: 5 MG/M3
ACGIH TLV: 5 MG/M3; 9596
EPA Rpt Qty: 100 LBS
DOT Rpt Qty: 100 LBS

Cas: 9004-70-0
RTECS #: QW0970000
Name:

COLLODION (WET NITROCELLULOSE)

% Wt: 1-10

Other REC Limits: 100 PPM

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Cas: 1309-37-1

RTECS #: NO7400000

Name: IRON OXIDE

% Wt: 1-5

Other REC Limits: NONE SPECIFIED

OSHA PEL: 10 MG/M3 (FE)

ACGIH TLV: 5MG(FE)/M3FUME,B2;96

Cas: 68038-41-5

Name: MALEIC MODIFIED RESIN ESTER

% Wt: 1-5

Other REC Limits: NONE SPECIFIED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

Cas: 67-63-0

RTECS #: NT8050000

Name: ISOPROPYL ALCOHOL (SARA 313)

% Wt: 1-5

Other REC Limits: 5 MG/CUM

OSHA PEL: 400 PPM

ACGIH TLV: 400 PPM/500STEL;9596

RTECS #: 9999999VO

Name: VOL ORGANIC CMPD: 454.05 GMS/LITER SCAQMD RULE 443.1, CALCULATED

=====

Health Hazards Data

=====

LD50 LC50 Mixture: NOT GIVEN FOR PRODUCT

Route Of Entry Inds - Inhalation: YES

Ski

n: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: EYES: MODERATE IRRITATION. SKIN: MILD IRRITATION.

INHALATION: CNS DEPRESSION, IRRITATION TO UPPER RESPIRATORY SYSTEM.

INGESTION: MAY CAUSE IRRITATION OF GASTROINTESTINAL TISSUES W/ VOMITUS &

IN FECES. ASPIRATION PNEUMONITIS AND PNEUMONIA, WHICH CAN BE FATAL.

Explanation Of Carcinogenicity: THIS COMPOUND CONTAINS NO INGREDIENTS AT
CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPE

CT

CARCINOGENS.

Signs And Symptions Of Overexposure: EYES: REDNESS, SWELLING, PAIN, TEARING, HAZY VISION. SKIN: REDNESS, SWELLING, ITCHING. INHALATION: HEADACHE, DIZZINESS, DROWSINESS, INCOORDINATION, SLURRED SPEECH, GIDDINESS, UNCONSCIOUSNESS, SORE THR OAT/NOSE, COUGHING, SNEEZING. INGESTION:PAIN, VOMITING, ABDOMINAL TENDERNESS, NAUSEA, MUSCULAR WEAKNESS, FATIQUE

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYES: IMMEDIATELY FLUSH W/PLENTY OF WATER.

SKIN: FLUSH W/PLENTY OF

WATER. INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE CPR.

INGESTION: ONLY INDUCE VOMITING AT THE INSTRUCTION OF A PHYSICIAN . NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Handling and Disposal

=====
Spill Release Procedures: WEAR PROPER PERSONAL PROTECTIVE EQUIPMENT. VENTILATE AREA. EXTINGUISH ALL IG

NITION SOURCES. COLLECT SPILLED MATERIAL. PLACE IN DOT-APPROVED CONTAINER AND SEAL.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: MIX W/FLAMMABLE MATERIAL & INCINERATE IN A PERMITTED HAZARDOUS WASTE FACILITY IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. DISPOSE OF DRIED SOLIDS IN A SANITARY LANDFILL. D001 IGNITABLE.

Handling And Storage Precautions: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.

Other Precautions: KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME & OTHER IGNITION SOURCES. WASH EXPOSED AREAS THOROUGHLY WITH SOAP AND WATER. DO NOT INGEST.

=====
Fire and Explosion Hazard Information

=====
Flash Point Method: SCC

Flash Point Text: 48.0F,8.9C

Lower Limits: 1.27

Upper Limits: 7

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Proced

ures: FIRE FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL TANKS AND CONTAINERS EXPOSED TO FIRE WITH WATER.

Unusual Fire/Explosion Hazard: VAPORS MAY TRAVEL LONG DISTANCES ALONG THE GROUND/FLOOR TO AN IGNITION SOURCE & FLASH BACK.

Control Measures

Respiratory Protection: DO NOT INHALE VAPORS. AVOID INHALATION OF DUST CREATED BY CUTTING

G, SANDING OR GRINDING. WEAR NIOSH APPROVED RESPIRATORS BASED ON AIRBORNE CONCENTRATION OF CONTAMINANTS & IN ACCORDANCE W/OSHA REGULATIONS: HALF-MASK DUST RESPIRATOR.

Ventilation: LOCAL EXHAUST FOR GRINDING, CUTTING/SANDING CURED MATERIAL/ APPROPRIATE RESPIRATORY PROTECTION IF EXHAUST NOT ADEQUATE.

Protective Gloves: POLYETHYLENE/ETHYLENE VINYL ALCOHOL

Eye Protection: SAFETY GLASSES W/SIDESHIELDS

Other Protective Equipment: VENTED GOGGLES, POLYTETRAFLUOROETHYLENE/ FLUOROELASTOMER GLOVES

Work Hygienic Practices: WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health: NONE SPECIFIED BY MANUFACTURER.

Physical/Chemical Properties

HCC: F2

B.P. Text: NOT GIVEN

M.P/F.P Text: NOT GIVEN

Decomp Text: NOT GIVEN

Vapor Pres: NOT GIVEN

Vapor Density: 4

Spec Gravity: 1.51-1.56

Evaporation Rate &

p; Reference: NOT GIVEN

Solubility in Water: INSOLUBLE

Appearance and Odor: RED PASTE WITH SOLVENT ODOR.

Percent Volatiles by Volume: 28-30

Corrosion Rate: UNKNOWN

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: HEAT, SPARKS, OPEN FLAME & OTHER IGNITION SOURCES

Materials To Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: CARBON DIOXIDE,

CARBON MONOXIDE, TOXIC
VAPORS, GASES/PARTICULATES
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NONE. WILL NOT OCCUR.

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Infor
mation
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
HAZCOM Label
=====

Product ID: 3M BRAND ACRYL-RED PUTTY P/N 59
66
Cage: 52157
Company Name: MINNESOTA MINING AND MFG CO AUTOMOTIVE TRADES DIV
Street: 3M CTR
City: ST PAUL MN
Zipcode: 55144-1000
Health Emergency Phone: 612-733-1110
Label Required IND: Y
Date Of Label Review: 06/12/1999
Status Code: A
Origination Code: G
Hazard And Precautions: EYES: MODERATE IRRITATION. SKIN: MILD IRRITATION.
INHALATION: CNS DEPRESSION, IRRITATION TO UPPER RESPIRATORY SYSTEM.
INGESTION: MAY CAUSE IRRITATION OF GASTROINTESTINAL TISSUES W/ VOMITUS &
IN FECES. ASPIRA
TION PNEUMONITIS AND PNEUMONIA, WHICH CAN BE FATAL.

=====
Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information to have any application, use or
viability by or to any person or persons outside the Department of Defense
nor

any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.