

CAAP CO INC -- CAAPCOAT POLYURETHANE CURING AGENT -- 8010-01-235-0827

===== Product Identification =====

Product ID:CAAPCOAT POLYURETHANE CURING AGENT

MSDS Date:01/01/1994

FSC:8010

NIIN:01-235-0827

Kit Part:Y

MSDS Number: CCJCB

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPES FARM RD

City:MILFORD

State:CT

ZIP:06460-3670

Country:US

Info Phone Num:203-877-0375

Emergency Phone Num

:203-877-0375

CAGE:60922

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC AMINE

Fraction by Wt: 65%

Other REC Limits:NONE RECOMMENDED

Ingred Name:METHYL ISOBUTYL KETONE (HEXONE) (SARA 313) (CERCLA)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 35%

Other REC Limits:NONE RECOMMENDED

OSHA PEL

:100 PPM
ACGIH TLV:50 PPM/75 STEL; 9596
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: CONTACT MAY DAMAGE EYES,
IRRITATE SKIN & CAUSE RESPIRATORY IRRITATION UPON INHALATION.
CHRONIC: REPEATED/PROLONGED EXPOSURE MAY CAUSE DEFATTING OF THE
SKIN, DERMATITIS AND POSSIBLE SENS
ITIZATION. INHALATION OF VERY
HIGH VAPOR CONCENTRATIONS ABOVE PEL MAY CAUSE NEURAL IMPAIRMENT,
KIDNEY & LIVER DAMAGE.
Explanation of Carcinogenicity:THE PRODUCT GIVES A NEGATIVE AMES SCREEN
TEST RESULT; NONE OF THE INGREDIENTS ARE LISTED AS CARCINOGENS.
Effects of Overexposure:VAPOR EXPOSURE-BURNING EYES, HEADACHE,
DIZZINESS, THROAT IRRITATION, LOSS OF APPETITE, NAUSEA.
CONTACT-CORROSIVE ACCORDING TO D.O.T. CORROSIVITY TEST. MAY CAUSE
IRRITATION OF SKIN, BURNING OF SKIN
OR EYES.
Medical Cond Aggravated by Exposure:PRE-EXISTING ALLERGIES, EYE, SKIN
AND RESPIRATORY DISORDERS.

===== First Aid Measures =====

First Aid:EYES-FLUSH WITH WATER FOR 15 MIN. GET IMMEDIATE MEDICAL
ATTENTION. SKIN-WASH WITH SOAP & WATER, REMOVE CONTAMINATED
CLOTHING. IF IRRITATION PERSISTS, GET IMMEDIATE MEDICAL ATTENTION.
INHALATION-REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NOT
BREATHING. IF BREATHING IS DIFFICULT GIVE
OXYGEN. GET IMMEDIATE
MEDICAL ATTENTION. INGESTION-DO NOT INDUCE VOMITING. GET IMMEDIATE
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:74.0F,23.3C
Lower Limits:1.2
Upper Limits:8.0
Extinguishing Media:CARBON DIOXIE, FOAM, DRY CHEMICAL.
Fire Fighting Procedures:USE FULL PROTECTIVE GEAR, INCLUDING A
SELF-CONTAINED BREATHING APPARATUS AND CHEMICAL PROTECTIVE SUIT FOR
AMINE/AMMONIA TYPE CORROSIVE VAPORS.

KEEP UPWIND FIRE.

Unusual Fire/Explosion Hazard:NONE, THE PRODUCT IS A FLAMMABLE LIQUID.

THE RPRODUCT BECOMES A CORROSIVE LIQUID UPON THE ADDITION OF WATER.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION & DO NOT SMOKE IN AREA. WEAR PROTECTIVE EQUIPMENT. CONTAIN THE SPILL WITH ABSORBENT MATERIAL. CLEAN UP THE ABSORBENT & CONTAIN SECURELY. SWEEP AND WET MOP THE AFFECTED AREA WITH SOAP & WATER. VENTILATE

THE AREA.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.

Other Precautions:THIS PRODUCT IS NOT USED ALONE; IT IS USED IN CONJUNCTION WITH CAAPCOAT FLUOROELASTOMER COATING. A SPRAY BOOTH IS REQUIRED FOR SPRAY APPLICATION. VENTILATION SYSTEMS SHOULD BE DESIGNED TO DRAW AIR PAST THE OPERATOR, SOURCE & THEN TO EXHAUST

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF USE CONDITIONS GENERATE VAPORS OR MISTS WEAR A NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EMISSIONS LEVELS AT POINT OF USE. APPROPRIATE RESPIRATORS INCLUDE A FULL FACEPIECE OR A PURIFYING CARTRIDGE RESPIRATOR EQUIPPED FOR ORGANIC VAPOR

Ventilation:THE EXHAUST VENTILATION SHOULD BE SUFFICIENT TO KEEP THE AIRBORNE CONCENTRATIONS BELOW THE PEL'S.

Protective Gloves:SOLVENT RESISTANT GLOVES.

Eye Protection:SOLVENT

RESISTANT SAFETY GLASSES.

Other Protective Equipment:SOLVENT RESISTANT APRON SHOULD BE WORN. DO NOT WEAR CONTACT LENSES WHEN USING THIS PRODUCT.

Work Hygienic Practices:AN EYE WASH & SAFETY SHOWER SHOULD BE NEARBY & READY TO USE. WASH WELL WITH SOAP & WATER AFTER HANDLING THE PRODUCT.

Supplemental Safety and Health

KEY1: F3.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:241F,116C

Vapor Pres:15 MMHG

Vapor Density:3.5

Spec Gravity:

0.83

Evaporation Rate & Reference:1.6 (N-BUTYL ACETATE=1)

Solubility in Water:SLIGHT

Appearance and Odor:CLEAR YELLOW LIQUID WITH PUNGENT ODOR (CURING AGENT)

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

THIS PRODUCT IS INCOMPATINLE WITH STRONG OXIDIZING AGENTS AND STRONG ACIDS.

Stability Condition to Avoid:THIS PRODUCT IS STABLE, BUT SHOULD BE KEPT AWAY FROM ALL IGNITION SOURCES. DO NOT SMOKE IN AREA WHERE PRODUCT IS USED.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, NITROGEN OXIDES AND AMMONIA MAY BE RELEASED DURING COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION IN AN APPROPRIATELY DESIGNED AND LICENSED INCINERATOR IS PREFERRED; THIS IS A RCRA HAZARDOUS IGNITABLE WASTE. REGULATIONS MAY VARY FROM STATE TO STATE; DISPOSE OF ACCORDING TO STATE, LOCAL AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.