

TADIRAN ELECTRONICS INDUSTRIES INC -- TADIRAN LITHIUM INORGANIC 3.6V BATTERY --
6135-01-304-8652

===== Product Identification =====

Product ID:TADIRAN LITHIUM INORGANIC 3.6V BATTERY
MSDS Date:11/22/1995
FSC:6135
NIIN:01-304-8652
MSDS Number: CCJFD
=== Responsible Party ===
Company Name:TADIRAN ELECTRONICS INDUSTRIES INC
Address:350 5TH AVE
City:NEW YORK
State:NY
ZIP:10118-0001
Country:US
Info Phon
e Num:408-727-0300
Emergency Phone Num:516-621-4980, 214-221-7523
CAGE:4J947
=== Contractor Identification ===
Company Name:TADIRAN ELECTRONICS INC.
Address:350 5TH AVENUE
Box:City:NEW YORK
State:NY
ZIP:10118-0001
Country:US
Phone:212-947-4600
CAGE:4J947

===== Composition/Information on Ingredients =====

Ingred Name:THIONYL CHLORIDE
CAS:7719-09-7
RTECS #:XM5150000
Fraction by Wt: 40%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C 1 PPM
ACGIH TLV:C 1 PPM; 9495

Ingred Name:LITHI

UM HYDRIDE (SARA 302)
CAS:7580-67-8
RTECS #:OJ6300000
Fraction by Wt: 5% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.025 MG/M3
ACGIH TLV:0.025 MG/M3; 9596

Ingred Name:CARBON
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ALUMINUM CHLORIDE, ANHYDROUS
CAS:7446-70-0
RTECS #:BD0525000
Fraction by Wt: 6% %
Other REC Limits:NONE RECOMMENDED

Ingred Name:LITHIUM CHLORIDE
CAS:7447-41-8
RTECS #:OJ5950000
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED

Ingred Name:NICKEL PLATE
D IRON
Fraction by Wt: 39% %
Other REC Limits:NONE RECOMMENDED

Ingred Name:STAINLESS STEEL
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED

Ingred Name:GLASS SEPARATOR
Fraction by Wt: 1% %
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NOT GIVEN FOR PRODUCT AS A WHOLE
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:WHEN E

XPOSED TO INTERNAL CONTENT,
VAPORS ARE VERY IRRITATING TO EYS, MUCOUS MEMBRANE AND SKIN.
OVEREXPOSURE CAN CAUSE SYMPTOMS OF NONFIBROTIC LUNG INJURY AND
MEMBRANE IRRITATION.
Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT
CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT
CARCINOGENS.
Effects of Overexposure:WHEN EXPOSED TO INTERNAL CONTENTS: DISTINCT
ODOR, COUGHING, ACIDIC TASTE, EYE AND MUCOUS IRRITATION.
Medical Cond Aggravated by
Exposure:LUNG INJURIES, ASTHMA, OTHER
RESPIRATORY DISORDERS AND MEMBRANE IRRITATION.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS
OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING.
WASH WITH SOAP AND WATER. IF IRRITATION PERSIST, GET MEDICAL
ATTENTION. INH ALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET
MEDICAL
ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE
Lower Limits:NOT GIVEN
Upper Limits:NOT GIVEN
Extinguishing Media:LIT-X-EXTINGUISHER (TRADEMARK FOR A GRAPHITE-BASED
POWDER)
Fire Fighting Procedures:DO NOT USE WATER, SAND, CARBON DIOXID,
SODA-ACID OR HALOGENATED HYDROCARBONS EXTINGUISHERS. WEAR
PROTECTIVE BREATHING APPARATUS. COVER WITH LIT-X POWDER.
Unusual Fire/Explosion Hazard:DO NOT EXPOSE TO TEMPERATURES ABOVE 1
50C,
INCINERATE, PUNCTURE, CRUSH, RECHARGE, OVERCHARGE OR SHORT CIRCUIT.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE THE CONTAMINATED AREA. DO NOT BREATH
VAPORS OR TOUCH CELL CONTENT WITH BARE HANDS.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:FOLLOWING SPECIFIED BY UL:" WARNING:
FIRE, EXPLOSION AND SEVERE HAZARD. D

O NOT RECHARGE, DISASSEMBLE,
HEAT ABOVE 100C, INCINERATE OR EXPOSE TO WATER."
Other Precautions:DO NOT STORE BATTERIES FOR LONG PERIODS IN HIGH
HUMIDITY. DO NOT SHORT CIRCUIT, RECHARGE, OVERDISCHARGE, EXPOSE TO
TEMPERATUREE ABOVE 150C, CRUSH OR PUNCTURE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ACID GAS FILTER MASK
Ventilation:LOCAL EXHAUST RECOMMENDED.
Protective Gloves:BUTYL RUBBER GLOVES
Eye Protection:CHEMICAL WORKER SAFETY GOGG
LES.
Other Protective Equipment:CHEMICAL LABORATORY GARMENTS AS NECESSARY TO
PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE
AVAILABLE.
Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER
BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:Z6
Boiling Pt:B.P. Text:NOT GIVEN
Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:NOT GIVEN
Vapor Density:NOT GIVEN
Spec Gravity:NOT GIVEN
Evaporation Rate & Reference:NOT GIVEN
Solubility in Water:NOT GIVEN
Appearance and Odor:NOT GIVEN

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
FIRE, HEAT OVER 150C, FORCE OPENING, RECHARGING, INCINERATING, EXPOSURE
TO WATER OR HIGH HUMIDITY.
Stability Condition to Avoid:THE BATTERY INGREDIENTS CAN FORM HCL, SO2
AND H2 UPON CONTACT WITH WATER (ONLY

WHEN FORCED OPEN).

Hazardous Decomposition Products:SULFUR DIOXIDE, HYDROGEN CHLORIDE,
HYDROGEN

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING
ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR
LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elemen

ts of the Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.