

NILES CHEMICAL PAINT CO -- N-6238B HAZE GRAY: COMP. B -- 8010-01-302-6838

===== Product Identification =====

Product ID:N-6238B HAZE GRAY: COMP. B

MSDS Date:01/10/1996

FSC:8010

NIIN:01-302-6838

Kit Part:Y

MSDS Number: CCKHC

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-3377

Emergency Phone Num:219-236-5856

Preparer's Name:MIKE LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

===== Composition/Information on Ingredients =====

Ingred Name:EPOXY RESIN

CAS:25068-38-6

RTECS #:KC2100000

Fraction by Wt: 53.0%

Other REC Limits:NONE RECOMMENDED

Ingred Name:TALC

CAS:14807-96-6

RTECS #:MW2700000

Fraction by Wt: 26.0%

Other REC Limits:NONE RECOMMENDED

Ingred Name:#100 SOLVEN

T (VP = 4.4 @ 20C)  
CAS:64742-95-6  
Fraction by Wt: 19.0%  
Other REC Limits:NONE RECOMMENDED  
ACGIH TLV:50 PPM

Ingred Name:RHEOLOGICAL ADDATIVE  
Fraction by Wt: 1.0%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:PROPRIETARY INGREDIENT  
Fraction by Wt: BALANCE  
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC = 2.04 LB/GL  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT RELEVANT  
ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

Routes of En  
try: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYE:SEVERE  
IRRIT,LACRIMATION,REDNESS,BLURRED VISION. SKIN:REDNESS & IRRIT,  
DEFATTING LEADING TO DERMATITIS. INHAL:NASAL & RESPIRATORY IRRIT.  
CNS DEPRESSION (DIZZY,DROWSY,WEAK,FATIGUE,CONFUSION) NAUSEA ,  
HEADACHE, VERTIGO, UNCONSCIOUSNESS, ASPHYXIATION. INGEST:GI IRRIT,  
ABDOMINAL PAIN, NAUSEA, VOMITTING, DIARRREA.  
Effects of Overexposure:DUST MAY CA  
USE PNUEMOCONIOSIS & PLEURAL  
THICKENING.TARGET ORGANS: LUNGS.  
Medical Cond Aggravated by Exposure:NONE KNOWN

===== First Aid Measures =====

First Aid:INHAL: MOVE TO FRESH AIR IMMED. IF BREATH STOPPED, GIVE ARTIF  
RESP. GET MED AID ASAP. SKIN: IMMED FLUSH W/PLENTY WATER. IF MAT'L  
PENETRATES CLOTH, IMMED REMOVE CONTAM CLOTHING & FLUSH SKIN  
W/WATER.GET MED AID. EYE: IMMED FLUSH W/WATER AT LEAST 15 MIN,  
LIFTING LIDS. GET MED AID IMMED. INGE

ST: DRINK 1-2 GLASSES OF  
WATER, DONT INDUCE VOMIT. CALL DR/POISON CONTROL IMMED. TREAT  
SYMPTOMATICALLY.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:107F,42C  
Autoignition Temp:Autoignition Temp Text:NE  
Lower Limits:1.0  
Upper Limits:0.0  
Extinguishing Media:DRY CHEMICAL, FOAM, CO2  
Fire Fighting Procedures:WEAR SCBA W/FULL FACEPIECE (POSITIVE PRESSURE  
MODE) & FULL PROTECT CLOTH. USE WATER TO COOL CLOSED CNTNR TO  
PREVENT PR  
ESSURE BLDUP/AUTO IGNIT/EXPLOSION W/HEAT.  
Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD.VAPOR HEAVY,TRAVEL ON  
GRND TO IGNIT.KEEP FROM HEAT/IGNIT.CLSD CNTNR EXPLODE W/HEAT.APPLIC  
TO HOT SRFCS REQ SPCL CAUTN.DECOMP PRODUCT-HEALTH HZD.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNIT SOURCES. MINIMIZE BREATHING  
VAPOR/AVOID SKIN CONTACT.ABSORB W/INERT MAT'L (CLAY,SOIL,COMMERCL  
ABSORBNT) . SMALL: SHOVEL RECLAIMED LIQ/ABSORB  
ENT INTO  
RECOVERY/SALVAGE DRUMS. LARGE: DIKE .RECLAIM INTO RECOVERY/SALVAGE  
DRUMS OR TANK TRUCK.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE IN HIGH TEMPERATURE  
AREAS OR NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NOT  
IN USE. AVOID ROUGH HANDLING.  
Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN  
EMPTY. DO NOT WELD OR FLAME CUT ON EMPTY DRUMS. SHOCK FROM DROPPING  
MAY SPLIT C  
ONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR APPROPRIATE (TYPE TC-23C-75) FITTED  
HALF-MASK OR FULL FACEPIECE RESPIRATOR DURING/AFTER APPLICATION  
UNLESS AIR MONITORING DEMONSTRATES VAPOR LEVELS BELOW APPLICABLE  
LIMITS. FOLLOW RESPIRATOR MANU FACTURER'S DIRECTIONS FOR USE.  
Ventilation:KEEP CONCEN