

TEXACO REFINING AND MARKETING INC. -- 00751 MILITARY SYMBOL 2075 T-H [TURBINE OIL] --
9150-00-985-7231

===== Product Identification =====

Product ID:00751 MILITARY SYMBOL 2075 T-H [TURBINE OIL]

MSDS Date:12/05/1995

FSC:9150

NIIN:00-985-7231

MSDS Number: CCMRR

=== Responsible Party ===

Company Name:TEXACO REFINING AND MARKETING INC.

Address:1111 RUSK STREET

Box:4427

City:HOUSTON

State:TX

ZIP:77002-

3310

Country:US

Info Phone Num:713-650-5206

Emergency Phone Num:713-650-5206, CHEMTREC 800-424-9300

Preparer's Name:MANAGER,PROD SAFETY

CAGE:2R503

=== Contractor Identification ===

Company Name:ALBRIGHT AND WILSON AMERICAS INC

Address:100 LAKERIDGE PKY

Box:26229

City:ASHLAND

State:VA

ZIP:23005

Country:US

CAGE:0DPR6

Company Name:TEXACO REFINING AND MARKETING INC

Address:1111 RUSK ST

Box:City:HOUSTON

State:TX

ZIP:77002-3310

Country:US

Phone:713-650-5206

CAGE:2R503

===== Composition/Infor

mation on Ingredients =====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES,HYDROTREATED
(MILD),HEAVY PARAFFINIC
CAS:64742-54-7
RTECS #:PY8035500
Fraction by Wt: 90-95%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

===== Hazards Identification =====

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5MG/M3
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:MAY CAUSE MINIMAL
IRRITATION.SKIN:PROLONGED EXPOSURE MAY CAUSE IRRITATION OR
DEFATTING.HIGH PRESSURE INJECTION MAY CAUSE NECROSIS.INGEST:MAY
CAUSE GI TRACT IRRITATION.INHAL:MAY CAUSE RESPIRATORY IRRITATION.
Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%
WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.
Effects of Overexposure:SKIN:REDNESS.THE SYMPTOMS FROM HIGH PRESSURE
INJECTION MAY SEEM MINOR,BUT THIS IS A TRUE
MEDICAL EMERGENCY.
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
CONDITIONS(EG.DERMATITIS) MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND
WATER.HIGH PRESSURE INJECTION IS A MEDICAL EMERGENCY.EYES:FLUSH
WITH WATER FOR 15 MINUTES.GET MEDICAL ATTENTION OF IRRITATION
OCCURS.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL
RESPIRATION IF NEEDED.INGEST:GET PROMPT QUALIFIED MEDICAL
ATTENTION.IF MORE THAN 2 MOUTHFULS SWALLOWED,GIVE 2 GLASSES OF
WATER.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:370F,188C
Extinguishing Media:WATER SPRAY,DRY CHEMICAL,CARBON DIOXIDE,FOAM.WATER
OR FOAM MAY CAUSE FROTHING.
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND
FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER
FOG.

Unu

ual Fire/Explosion Hazard:MANUFACTURER STATES NONE.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER RESPIRATORY AND PROTECTIVE EQUIPMENT.VENTILATE AREA.SOAK UP WITH A NON-COMBUSTIBLE INERT ABSORBANT(CLAY,SAND);PLACE IN PROPER CONTAINER FOR DISPOSAL.AVOID CONTAMINATION OF GROUND OR WATERWAYS.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:

STORE IN A COOL, DRY, WELL-VENTILATED

PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY FROM INCOMPATIBLE MATERIALS.AVOID WATER CONTAMINATION.

Other Precautions:FOLLOW LABEL DIRECTIONS.AVOID BREATHING VAPORS.AVOID SKIN AND EYE CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE EITHER A SELF-CONTAINED BREATHING APPARATUS OR A NIOSH/MSHA APPROVED RESPIRATOR

FOR ORGANIC VAPORS,DEPENDING ON

THE AIRBORN CONCENTRATION AND BREATHING OXYGEN AVAILABLE.

Ventilation:LOCAL VENTILATION AT THE WORKSITE;MECHANICAL(GENERAL) VENTILATION TO MAINTAIN TLV/PEL.

Protective Gloves:USE HAND WASHINGS.

Eye Protection:SAFETY GOGGLES OR FACESHIELD.

Other Protective Equipment:PROVIDE A LOCAL EYE WASH STATION.

Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.

Supplemental Safety and Health

HIGH PRESSURE

INJECTION OF THIS MATERIAL IS A SERIOUS INJURY.FAILURE TO

DEBRIDE THE WOUND MAY RESULT IN DISFIGUREMENT OR MAY REQUIRE AMPUTATION.

===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity:.9665

Viscosity:32CST@104F

Appearance and Odor:LIGHT PALE LIQUID,MILD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER

RER.

Hazardous Decomposition Products: CARBON DIOXIDE, CARBON MONOXIDE, IRRITATING ALDEHYDES AND KETONES.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.