

KRYLON HARDWARE -- 1605 DOVE GRAY, K01605 -- 8010-00-584-3151

=====
Product Identification
=====

Product ID:1605 DOVE GRAY, K01605

MSDS Date:08/22/1996

FSC:8010

NIIN:00-584-3151

MSDS Number: CCVLY

=== Responsible Party ===

Company Name:KRYLON HARDWARE

Address:31500 SOLON RD

City:SOLON

State:OH

ZIP:44139

Country:US

Info Phone Num:800-832-2541

Emergency Phone Num:216-566-2917

CAGE:JO346

=== Contract

or Identification ===

Company Name:KRYLON HARDWARE

Address:31600 SOLON RD

Box:City:SOLON

State:OH

ZIP:44139

Country:US

Phone:800-832-2541

CAGE:JO346

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE

Box:City:BEDFORD HEIGHTS

State:OH

ZIP:44146

Country:US

Phone:216-292-7400 OR 216-595-8634

CAGE:09800

=====
Composition/Information on Ingredients
=====

Ingred Name:PROPANE VP:760

CAS:74-98-6

RTECS #:TX2275000

Fraction by Wt: 14%

OSHA PEL:1000 PPM

AC

GIH TLV:ASPHYXIAN

Ingred Name:BUTANE VP:760
CAS:106-97-8
RTECS #:EJ4200000
Fraction by Wt: 6%
OSHA PEL:800 PPM
ACGIH TLV:800 PPM

Ingred Name:BENZENE, ETHYL-; (ETHYLBENZENE) (SARA 313) VP:7.10
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 2%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/125STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENE (SARA 313) (CERCLA) VP:5.90
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 10%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA 313) (CERCLA) VP:180.00
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 40%
OSHA PEL:1000 PPM
ACGIH TLV:750PPM/1000STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:2-BUTANONE; (METHYL ETHYL KETONE) (MEK) (SARA 313) (CERCLA)
VP:70.00
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 4%
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:2-PENTANONE, 4-METHYL-; (METHYL ISOBUTYL KETONE) (HEXONE)
(S

ARA 313) (CERCLA) VP:16.00
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 2%
OSHA PEL:100 PPM
ACGIH TLV:50 PPM/75 STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ACETIC ACID, 2-METHOXY-1-METHYLETHYL ESTER;
(1-METHOXY-2-PROPANOL ACETATE) VP:1.80
CAS:108-65-6
RTECS #:AI8925000
Fraction by Wt: 7%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:TITANIUM OXIDE; (TITANIUM DIOXIDE)
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 3%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST

Ingred Name:
e:EFTS OF OVEREXP:EXPOSED TO TITANIUM DIOXIDE DUST AT 250
MG/M3 DEVELOPED LUNG CANCER, HOWEVER, SUCH EXPOS LEVELS (ING 11)
RTECS #:9999999ZZ

Ingred Name:ING 10:ARE NOT ATTAINABLE IN WORKPLACE. RPTS HAVE ASSOC
RPTD & PRLNGD OVEREXP TO SOLVS W/PERM BRAIN & NERV SYS DMG.
RTECS #:9999999ZZ

Ingred Name:OTHER PRECS:MAY IGNITE EXPLOSIVELY. DURING USE & UNTIL ALL
VAPS ARE GONE:KEEP AREA VENTD-DO NOT SMK-EXTING ALL (ING 13)
RTECS #:9999999ZZ

Ingred Name:ING 12:FLAMES, PILOT LIGHTS & HEATER
S, TURN OFF STOVES,
ELEC TOOLS & APPLIANCES, & ANY OTHER IGNIT SOURCES. (ING 14)
RTECS #:9999999ZZ

Ingred Name:ING 13:CONSULT NFPA CODE. USE APPRVD BONDING & GROUNDING
PROCEDURES. CONTENTS UNDER PRESS. DO NOT PUNCTURE, (ING 15)
RTECS #:9999999ZZ

Ingred Name:ING 14:INCIN/EXPOSE TO TEMPS ABOVE 120F. HEAT FROM
SUNLIGHT, RADIATORS, STOVES, HOT WATER, & OTHER HEAT SOURCES (ING
16)
RTECS #:9999999ZZ

Ingred Name:ING 15:COULD CAUSE CNTNR TO BURST. DO NOT TAKE INTERNALLY.
KEEP OUT

OF REACH OF CHILDREN. INTENTIONAL (ING 17)
RTECS #:9999999ZZ

Ingred Name:ING 16:MISUSE BY DELIBERATELY CONCENTRATING AND INHALING
THE CONTENTS CAN BE HARMFUL OR FATAL.
RTECS #:9999999ZZ

Ingred Name:RESP PROT:DUST WHICH MAY BE GENERATED FROM THIS PRODUCT,
UNDERLYING PAINT, OR THE ABRASIVE.
RTECS #:9999999ZZ

Ingred Name:RESP PROT: GENERATED FROM THIS PRODUCT, UNDERLYING PAINT,
OR THE ABRASIVE.
RTECS #:9999999ZZ

===== Hazards Identification =====

L
D50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EXPOS MAY BE BY INHAL &/OR SKIN/EYE
CONT, DEPENDING ON CNDTNS OF USE. TO MIN EXPOS, FOLLOW RECS FOR
PROPER USE, VENT, & PERS PROT EQUIP. EFTS:IRRIT OF EYES, SKIN &
RESP SYS. MAY CAUSE NERV SYS DEPRESS . EXTREME OVEREXP MAY RSLT IN
UNCON & POSS DEATH. SIGNS & SYMPS:HDCH, DIZZ, NAUS & LOSS OF C
OORD

ARE (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZS:INDICATIONS OF EXCESSIVE EXPOS TO
VAPS/SPRAY MISTS. REDNESS & ITCHING/BURNING SENSATION MAY INDICATE
EYE/EXCESSIVE SKIN EXPOS. CHRONIC:METHYL ETHYL KETONE MAY INCR NERV
SYS EFTS OF OTHER SOL VS. PRLNGD OVEREXP TO SOLVS INGS MAY CAUSE
ADVERSE EFTS TO LIVER, URINARY, BLOOD FORMING & REPRO SYS. RATS
(ING 10)

Medical Cond Aggravated by Exposure:NNE GENERALLY RECOGNIZED.

=

===== First Aid Measures =====

First Aid:INHALATION:REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM
AND QUIET. SKIN:WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER.
REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. EYES:FLUSH
WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MED ATTN.
INGEST:NEVER GIVE ANYTHING BY MOUTH TO UNCON PERSON. DO NOT INDUCE
VOMIT. GIVE CONSCIOUS PATIENT SEVERAL GLASSES OF WATER. SEEK MED
AT

TN.

===== Fire Fighting Measures =====

Flash Point: