HYDROTEX INDUSTRIES INC -- NTP-60 ULTRA EP ALL NIGI GRADES, PN:60-0 -----MSDS Safety Information ______ FSC: 9150 NIIN: 01-353-2249 MSDS Date: 08/10/1995 MSDS Num: CDJVD Product ID: NTP-60 ULTRA EP ALL NIGI GRADES, PN:60-0 MFN: 02 Responsible Party Cage: 53933 Name: HYDROTEX INDUSTRIES INC Box: 560707 City: DALLAS TX 75356 Info Phone Number: 214-638-7400 **Emergency Phone Number: 800-52** 7-9439 Preparer's Name: (MSDS#:G-03) Proprietary Ind: Y Review Ind: Y Published: Y ______ **Contractor Summary** ______ Cage: 53933 Name: HYDROTEX INDUSTRIES INC Address: 1165 EMPIRE CENTRAL PL Box: 560707 City: DALLAS TX 75247-0707 Phone: 214-638-7400/FAX: 214-630-4786 ______ Item Description Information ______ ====== Item Manager: S9G Item Name: GREASE, GENERAL PURPOSE Specification Number: UNKNOWN Unit of Issue: BX Quantitative Expression: 00000000060EA UI Container Qty: 1 Type of Container: CARTRIDGES ______ Ingredients ______

Name: *** PROPRIETARY ***

Health Hazards Data

========

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: NO

Skin: YES Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: ACUTE/CHRONIC:NONE KNOWN.

Explanation Of Carcinogenicity: PER MSDS:INDIVIDUAL COMPONENTS ARE NOT KNOWN

CARCINOGENS & amp; PRODUCT IS NOT CONSIDERED TOXIC.

Signs And Symptions Of Overexposure: EYE CONTACT: MAY CAUSE TEMP

IRRIT, REDNESS.NO PERMANENT INJURY EXPECTED. SKIN CONTACT: FREQUENT OR

PROLONGED

CON

TACGT MAY IRRIT & DERMATITIS.OCCASIONAL BRIEF CONTACT WILL NOT RESULT IN SIGNIFICANT I RRITATION.INHAL:NONE.INGEST:MAY RESULT IN NAUSEA, VOMITING, CATHARAIS.

Medical Cond Aggravated By Exposure: NO INFO.

First Aid: EYE:FLUSH W/LG AMTS OF WATER TIL IRRIT SUBSIDES.IRRIT PERSISTS SEEK MED ATTN. SKIN:WASH THOROUGHLY W/SOAP/WTER.REMOVE CONTAMIN CLTOH. INHAL:REMOVE TO FRESH AIR.SYMPTOMS PERSIST SEEK MED ATTN. INGEST:D O NOT INDUCE VOMIT.SYMPTOMS PERSIST SEEK MED ATTN.

Handling and Disposal

Spill Release Procedures: CONTAIN MATL & DISPO IAW ALL APPLICABLE FED/STATE/LOC REGULATIONS.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: DISPO OF RECOVERED MATL/ABSORBENT MATL AS INDUSTRIAL WASTE IN MANNER ACCEPTABLE TO GOOD WASTE MANAGEMENT PRACTICE & amp; IN COMPL

IANCE W/APPLICABLE LOC/STATE/FED REGS.LANDFILL OR INCINERATION ACCEPTABLE IF IN COMPLIANCE WITH ABOVE.

Handling And Storage Precautions: STORE AWAY FROM OPEN FLAMES & DRIP STRONG OXIDIZERS.

Other Precautions: NONE.

Fire and Explosion Hazard Information

Flash Point Method: COC Flash Point Text: 450F,232C Lower Limits: NO INFO Upper Limits: NO INFO

Extinguishing Media: HALON, DRY CH

| EMICAL, FOAM, CO2, & DE MANUFACTURER. Fire Fighting Procedures: COOL CONTAINERS EXPOSED TO HEAT W/WATER. Unusual Fire/Explosion Hazard: NONE SPECIFIED BY MANUFACTURER. |
|---|
| Control Measures |
| Respiratory Protection: NONE SPECIFIED BY MANUFACTURER. Ventilation: NONE REQUIRED. Protective Gloves: PLASTIC GLOVES. Eye Protection: SAFETY GLASSES. Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices: LAUNDER CONTAMIN CLOTH BEF REUSE. |
| Physical/Chemical Properties |
| HCC: V6 B.P. Text: 650F,343C M.P/F.P Text: NA Vapor Pres: NA Vapor Density: NA Spec Gravity: 0.91000 Evaporation Rate & amp; Reference: NA Solubility in Water: NIL. Appearance and Odor: PINK, TACKY SOLID, SLIGHT ODOR. |
| Reactivity Data |
| Stability Indicator: YES Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER. Materials To Avoid: STRONG OXIDIZERS. Hazardous Decomposition Products: OXIDES O ANTIMONY, SULFUR, NITROGEN, CARBON. Hazardous Polymerization Indicator: NO |
| Toxicological Information |
| Ecological Information |
| MSDS Transport Information |
| Regulatory Information |
| ====================================== |

______ Transportation Information _____ Responsible Party Cage: 53933 Trans ID NO: 128429 Product ID: NTP-60 ULTRA EP ALL NIGI GRADES, PN:60-0 MSDS Prepared Date: 08/10/1995 Review Date: 03/24/1997 MFN: 2 Net Unit Weight: 13.5 LBS Multiple KIT Number: 0 Review IND: Y Unit Of Issue: BX Container QTY: 1 Type Of Container: CARTRIDGES Additional Data: PER MSDS:DOT:HAZ CLASS:NOT REGULATED,DOT ID#:NA. _____ Detail DOT Information _____ DOT PSN Code: ZZZ DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION _____ **Detail IMO Information** _____ IMO PSN Code: ZZZ IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION _____ Detail IATA Information ______ IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail AFI Information

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

HAZCOM Label

===========

Product ID: NTP-60 ULTRA EP ALL NIGI GRADES, PN:60-0

Cage: 53933

Company Name: HYDROTEX INDUSTRIES INC

Street: 1165 EMPIRE CENTRAL PL

PO Box: 560707 City: DALLAS TX Zipcode: 75247-0707

Health Emergency Phone: 800-527-9439

Label Required IND: Y

Date Of Label Review: 03/24/1997

Status Code: C

Label Date: 03/24/1997
Origination Code: F
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: CAUTION
Health Hazard: Slight
Contact Hazard: Slight
Fire Hazard: None

d: None

Reactivity Hazar

Hazard And Precautions: EYE:TEMP IRRIT, REDNESS.NO PERM INJURY

EXPECTED.FREQA/PROL SKIN CONTACT MAY IRRIT, CAUSE DERM. OCCASIONAL BRIEF CONTACT WILL NOT RESULT IJN SIGNIFICANT

IRRIT.INHAL:NONE.INGEST:NAU,VOMIT,CATHARSIS.TARGET ORGANS:EYE/SKIN.STORE AWAY FROM OPEN FLAMES & STRONG OXIDIZERS. FIRST AID: EYE:FLUSH W/LG AMTS OF WATER TIL IRRIT SUBSIDES.IRRIT PERSISTS SEEK MED ATTN. SKIN:WASH THOROUGHLY W/SOAP/WTER.REMOVE CONTAMI N CLTOH. INHAL:REMOVE TO FRESH AIR.SYMPTOMS PERS

IST SEEK MED ATTN. INGEST:DO NOT INDUCE VOMIT.SYMPTOMS PERSIST SEEK MED ATTN.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense

nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense

