COURTAULDS AEROSPACE, INC -- POLYSULFIDE RUBBER COMPOUND, PRO SEAL 890 B2 #0890B201 -- 8030-01-387-3196

============ Product Identification =========================

Product ID:POLYSULFIDE RUBBER COMPOUND, PRO SEAL 890 B2 #0890B201

MSDS Date:05/28/1996

FSC:8030

NIIN:01-387-3196

Kit Part:Y

MSDS Number: CDJWQ === Responsible Party ===

Company Name: COURTAULDS AEROSPACE, INC

Address:5430 SAN FERNANDO RD.

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Info Phone Num:818-240-2060

Emerge

ncy Phone Num:800-424-9300 (CHEMTREC)

CAGE:83574

=== Contractor Identification ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Phone:818-240-2060

CAGE:83574

======= Composition/Information on Ingredients ========

Ingred Name: CALCIUM CARBONATE LIMESTONE (AIRBORNE CONTAMINANT, FULLY

ENCAPSULATED)

CAS:1317-65-3

RTECS #:EV9580000 Fraction by Wt: 25.0%

Other REC Limits: NONE RE

COMMENDED OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name: POLYSULFIDE POLYMER, (NONHAZARDOUS)

CAS:68611-50-7

Other REC Limits: NONE RECOMMENDED

Ingred Name: SILICA DERIVITIVES, (NONHAZARDOUS)

CAS:67762-90-7

Other REC Limits: NONE RECOMMENDED

Ingred Name: PHENOLIC RESIN POWDER (NONHAZARDOUS)

Other REC Limits: NONE RECOMMENDED

Ingred Name:TOLUENE (SARA 313) (CERCLA) (VP = 23)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 5.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM; STEL 150

ACGIH TLV :50 PPM

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7 RTECS #:XR2275000

Fraction by Wt: 120F. GROUNDING/BONDING PROCEDURE SHOULD BE FOLLOWED WHEN

TRANSFERRING MATRIAL.

Other Precautions: EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DON'T CUT.

PUNCTURE, WELD ON/NEAR DRUM. VAPORS >AIR MAY COLLECT IN LOW/CONFINED AREA.

====== Exposure Controls/Personal Protection ========

Respiratory Protection:WHEN APPLYING IN ANY CIRCUMSTANCES LIKEL Y TO

PRODUCE AIRBORNE LEVEL OF HAZARDOUS INGREDIENTS IN EXCESS OF TLV, USE ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR.

Ventilation: GENERAL TO MAINTAIN VAPORS AIR

Spec Gravity:1.501 VOC Pounds/Gallon:51

Evaporation Rate & Department of the Reference: NOT AVAILABLE Appearance and Odor: WHITE THIXOTROPIC PASTE

Percent Volatiles by Volume:12.0

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Hazardous Decomposit

| TRACES OF HYDROGEN SULFIDE. | |
|--|--|
| ========= Disposal Considerations ============= | |
| Waste Disposal Methods:NOT A HAZARDOUS WASTE ACCORDING TO EPA REGULATIONS. CONSULT STATE REGULATIONS PRIOR TO DISPOSAL OF SPILL. | |

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of De

ion Products: OXIDES OF CARBON, SULFUR DIOXIDE,

fense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.