

ASPEN PAINTS -- STAIN, OIL TYPE, WOOD INTERIOR MAPLE -- 8010-00-281-2077

===== Product Identification =====

Product ID:STAIN, OIL TYPE, WOOD INTERIOR MAPLE

MSDS Date:11/01/1996

FSC:8010

NIIN:00-281-2077

MSDS Number: CDVHV

=== Responsible Party ===

Company Name:ASPEN PAINTS

Address:1128 S.W. SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Info Phone Num:206-682-4603

Emergency Phone Num:80

0-424-9300 (CHEMTREC)

Preparer's Name:D KIER

CAGE:0ALO9

=== Contractor Identification ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Phone:800-424-9300 CHEMTREC

CAGE:0ALO9

Company Name:ASPEN PAINTS/ASAMIPEN AMERICA INC

Address:1128 SPOKANE STREET

Box:City:SEATTLE

State:WA

ZIP:98134-1187

Country:US

Phone:303-573-1014(MED ONLY)

CAGE:0ALO9

===== Composition/Information on Ingredients =====

Ingred Name:SK SOLVENT ORAL RAT L

D50 8 ML/KG DERMAL LD50 74 MG/KG INHAL  
LD50 71400 PPM 4HR  
CAS:8052-41-3  
RTECS #:WJ8925000  
Fraction by Wt: 67.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:525 MG/M3  
ACGIH TLV:100 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE; INHAL: NASAL & RESP IRRIT,  
DIZZY, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUS,

ASPHYXIATION. EYE: SEVERE IRRIT, RED, TEAR, BLURRED VISION. INGEST:  
GI IRRIT, NAUSEA, VOMIT, DIARRHEA. ASPIRATION INTO LUNGS CAN CAUSE  
CHEMICAL PNEUMONITIS (CAN BE FATAL). SKIN: CHRONIC: DEFATING,  
DRYING (IRRIT & DERMITITIS).

===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR AND RESTORE BREATHING IF REQUIRED.  
EYE: FLUSH W/WATER FOR >15 MINUTES, HOLDING EYELIDS OPEN. SKIN:  
WASH W/MILD SOAP & WATER. INGESTION: DONT INDUCE  
VOMITING. GET MED  
AID IMMEDIATELY. NOTE: THE MAIN HAZARD FOLLOWING ACCIDENTAL  
INGESTION IS ASPIRATION OF LIQUID INTO LUNGS PRODUCING CHEMICAL  
PNEUMONITIS. CARDIAC ARRHYTHMIA AS HAVE BEEN REPORTED W/SOLVENT  
EXPOSURE.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:44.0F,6.7C  
Lower Limits:0.8  
Upper Limits:5.0  
Extinguishing Media:DRY CHEMICAL, CO2, FOAM, AND WATER FOG  
Fire Fighting Procedures:FLAMMABLE. DONT ENTER CONFINED

## FIRE SPACE W/O

PROTECTIVE CLOTH & POS PRESSURE SCBA. EXCLUDE AIR. DONT USE WATER EXCEPT AS FOG (USE TO COOL FIRE EXPOSED CNTNRS)

Unusual Fire/Explosion Hazard:AVOID EXCESSIVE HEAT, OPEN FLAMES AND ALL IGNITION SOURCES. VAPOR FORMS AN EXPLOSIVE MIXTURE WITH AIR BETWEEN UPPER AND LOWER FLAMMABLE LIMITS.

## ===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNIT SOURCE. VENT AREA. ABSORB

SPILL W/ABSORBENT (SAWDUST, SAND, VERMIC

ULITE), PLACE IN CLOSD

CNTNR. LARGE: DIKE AREA TO PREVENT MATERIAL FROM ENTERING WATER SYSTEMS/SEWERS. WEAR PROTECTIVE CLOTHES. NOTIFY ENVIRONMNTL AGENCIES IF >220 LBS.

## ===== Handling and Storage =====

Handling and Storage Precautions:FLAMMABLE LIQUID. STORE IN COOL, DRY, WELL-VENTED AREA, AWAY FROM HEAT & IGNITION SOURCES. AVOID PROLONGED/REPEATED CONTACT WITH SKIN. AVOID BREATHING

Other Precautions:WASH CONTAM CLOTHES PRIOR TO REUSE. US

E GOOD PERSONAL

HYGIENE. GROUND CNTNR WHEN POURING & LIMIT FREE FALL (MINIMIZE STATIC BLDUP). EMPTY CNTNRS HAZARDOUS FROM RESIDUES. DONT TAKE INTERNALLY. CLOSE CN TNR AFTER USE. KEEP AWAY FROM CHILDREN.

## ===== Exposure Controls/Personal Protection =====

Respiratory Protection:A CANISTER TYPE RESPIRATOR MUST BE WORN TO PREVENT THE INHALATION OF VAPOR OR SPRAY MISTS WHEN TLV PEL IS EXCEEDED.

Ventilation:GENERAL VENT REQUIRED DURING NORMAL USE. LOCAL VENTILATION

MAY BE REQUIRED TO KEEP EXPOSURE LEVEL BELOW LIMITS.

Protective Gloves:NITRILE, NEOPRENE, RUBBER

Eye Protection:WEAR FACE SHIELD OR CHEMICAL GOGGLES

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATION/SAFETY SHOWER SHOULD BE AVAILABLE.

Supplemental Safety and Health

NK

## ===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:301 TO 402F

Vapor Pres:>7.0

Vapor Density:4.8

Spec Gravity:0.87

VOC Pounds/Gallon:594

pH:NA  
Viscosity:10-25 #4 FC  
Evaporation Rate & Reference:SLOWER THAN N-BUTYL AC  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:THIN LIQUID, MILD ODOR  
Percent Volatiles by Volume:65-69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
AVOID CONTACT WITH STRONG OXIDIZING AGENTS, LEWIS OR MINERAL ACIDS.  
Stability Condition to Avoid:EXCESSIVE HEAT  
Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE ARE  
PRODUCED ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:IF NOT POSSIBLE TO RECLAIM, TREAT AS HAZARDOUS  
WASTE (EPA WASTE #D001) BASED ON IGNITABILITY. ALL DISPOSAL  
PROCEDURES MUST COMPLY WITH LOCAL, STATE AND FEDERAL REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.