

COURTAULDS AEROSPACE, INC -- PRO-SEAL 501, PART A (EPOXY RESIN COMPOUND) --
8040-00-126-7798

===== Product Identification =====

Product ID:PRO-SEAL 501, PART A (EPOXY RESIN COMPOUND)

MSDS Date:07/07/1993

FSC:8040

NIIN:00-126-7798

Kit Part:Y

MSDS Number: CFCZW

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE, INC

Address:5430 SAN FERNANDO RD.

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:800-424-

9300 (CHEMTREC)

Preparer's Name:A.F.S.

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

===== Composition/Information on Ingredients =====

Ingred Name:EPOXY RESIN

CAS:25036-25-3

Fraction by Wt: 80%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT EST.

ACGIH TLV:NOT EST.

===== Hazards Id

entification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: MILD IRRITATION. DIRECT CONTACT
CAN CAUSE BURNS. SKIN: PROLONGED/REPEATED EXPOSURE CAN CAUSE MILD
IRRITATION. DIRECT CONTACT CAN CAUSE BURNS. MAY CAUSE ALLERGIC RASH
IN SENSITIZED INDIVIDUALS. I NHALATION: PROLONGED EXPOSURE CAN
CAUSEHEADACHE & THROAT IRRITATION. INGESTION: HARMFUL IF SWALLOWED.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/ LUKE WARM WATER 15 MINUTES. IF SYMPTOMS
PERSIST, CONSULT PHYSICIAN. SKIN: WASH W/ SOAP/WATER. IF SYMPTOMS
PERSIST CONSULT PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. IF
SYMPTOMS PRESENT CONSULT PHYSICIAN. INGESTION: CONSULT PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:NOT FLAMMABLE
Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER FOG.
Fire
Fighting Procedures:USE COMPLETE PERSONAL PROTECTION. USE WATER TO
COOL HEAT EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:STRONG OXIDIZERS

===== Accidental Release Measures =====

Spill Release Procedures:COVER W/ ABSORBANT. SCOOP INTO CONTAINERS.
CLEAN UP RESIDUE W/ SUITABLE SOLVENT.

===== Handling and Storage =====

Handling and Storage Precautions:WASH THOROUGHLY AFTER HANDLING &
BEFORE SMOKING/EATING.
Other Pr
ecautions:AVOID INGESTION.

===== Exposure Controls/Personal Protection =====

Ventilation:GENERAL VENTILATION TO MAINTAIN VAPOR BELOW PEL.
Protective Gloves:SOLVENT RESISTANT.
Eye Protection:SAFETY GLASSES.
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NA
Spec Gravity:1.15
Evaporation Rate & Reference:NA
Solubility in Water:NEGLIGIBLE
Appearance and Odor:AMBER LIQUID

===== Stabili

ty and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products: OXIDES OF CARBON

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF SPILLAGE IN COMPLIANCE W/
FEDERAL/STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of

Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.