

GRIGGS PAINT -- MIL-L-81352A, #37038 FLAT BLACK, #700B04 -- 8010-00-830-1822

=====
Product Identification
=====

Product ID:MIL-L-81352A, #37038 FLAT BLACK, #700B04

MSDS Date:02/17/1996

FSC:8010

NIIN:00-830-1822

MSDS Number: CFDCN

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phone Num:8

00-424-9300 CHEMTREC

Preparer's Name:ROBERT COMMISSO

CAGE:DO312

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

Company Name:GRIGGS PAINT

Address:3602 S 16TH PL

City:PHOENIX

State:AZ

ZIP:85040-1319

Phone:602-243-3293

CAGE:DO312

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENES (SARA 313) (CERCLA) (VP = 5.1 @ 68F)

CAS:1330-20-7

RTECS #:ZE21000

00

Fraction by Wt: 4.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:N-BUTYL ALCOHOL (SARA 313) (CERCLA) (VP = 4.3 @ 68F)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 3.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL METHACRYLATE RESIN (SARA 313)

CAS:80-62-6

RTECS #:OZ5075000

Fraction by Wt: 35.0%

Other REC Limits:NONE RECOMMENDED

EP

A Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYLENE GLYCOL MONOBUTYL ETHER (SARA 313) (VP = 4.6 @ 68F)

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 6.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:50 PPM

ACGIH TLV:75 PPM

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)
(VP = 70 @ 68F)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 7.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:M

AGNESIUM SILICATE

CAS:14807-96-6

RTECS #:MW2700000

Fraction by Wt: 35.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3

Ingred Name:CYCLOHEXANONE (SARA 313) (VP = 2 @ 65F)

CAS:108-94-1

RTECS #:GW1050000

Fraction by Wt: 1.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:25 PPM

ACGIH TLV:25 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL N-AMYL KETONE (SARA 313) (VP = 2.1 @ 68F)

CAS:110-43-0

RTECS #:MJ5075000

Fraction by Wt: 3.0%

Other REC Limits:100 PPM

====

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL: DROWSINESS, DIZZINESS, FATIGUE,
COMA, LUNG CHANGES, NAUSEA, VOMITING, COUGH, PULMONARY IRRITATION,
CNS DEPRESSION. EYE: IRRITATION. SKIN: IRRITATION &/OR DERMITITIS,
ABSORPTION (IRRITATION, DEF ATTING & DERMITITIS). INGEST:
PNEUMONITIS, PULMONARY EDEMA, HEMORRAGE, GI
DISTURBANCE.

Medical Cond Aggravated by Exposure:DISEASES OF SKIN, CENTRAL NERVOUS
SYSTEM, LIVER AND KIDNEYS.

=====
===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH W/LARGE AMOUNTS WATER FOR 15 MINUTES.
SEEK MED AID. SKIN: WASH THOROUGHLY W/SOAP & WATER. SEEK MED AID.
INGEST: IMMEDIATELY SEEK MED AID. DONT INDUCE VOMITING. DONT GIVE
ANYTHI NG BY MOUTH TO UNCONSCIOUS PERSON.

=====
===== Fire Fighting Measures =====

=====

Flash Point Method:TCC

Flash Point:24.0F,-4.4C

Autoignition Temp:Autoignition Temp Text:NA

Lower Limits:1.0

Upper Limits:7.9

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:APPROVED GAS MASK REQUIRED FOR FIRE FIGHTING PERSONNEL. WATER MAY BE INEFFECTIVE, MAY BE USED TO COOL CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM IGNITION SOUCES. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK IF NO RISK INVOLVED. REMOVE ALL SOURCES OF IGNITION. STAY UPWIND. ABSORB WITH INERT MATERIAL. FLUSH AREA W/WATER. VENTILATE AREA FOR AT LEAST 24 HOURS OR UNTIL AREA HAS BEEN DECLARED SAFE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED & UPRIGHT TO PREVENT LEAK

AGE. AVOID IGNITION SOURCES.

Other Precautions:MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS, TANKS OR PITS WITHOUT ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE MSHA/NIOSH APPROVED UNITS. USE UNITS PER CURRENT 29 CFR 1910.134 REGULATIONS & FOLLOW MANUFACTURERS' INSTRUCTIONS & WARNINGS. AIR PURIFYING OV/FILTER UNITS MAY BE ACCEPTABLE.

Ventilation:LOCAL AND MECHANICAL EXHAUST.

Protective Gloves

:RUBBER GLOVES

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:EYE BATH AND SAFETY SHOWER.

Work Hygienic Practices:MAINTAIN GOOD PERSON HYGIENE. DO NOT USE IN CONFINED AREAS WITHOUT ADEQUATE VENTILATION.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:172 TO 336F

Decomp Temp:Decomp Text:NA

Vapor Density:>AIR

Spec Gravity:1.3

VOC Grams/Liter:2.52

Viscosity:NA

Evaporation Rate &

Reference:SLOWER THAN ETHER
Solubility in Water:ESSENTIALLY NIL
Appearance and Odor:VISCOUS LIQUID, W/TYPICAL PAINT ODOR.
Percent Volatiles by Volume:41.5
Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:IGNITION SOURCES.
Hazardous Decomposition Products:CO & CO2.

===== Disposal Considerations =====

Waste Disposal Methods:USE I
NERT ABSORBENT MATERIAL ON SPILLS. DISPOSE
IN ACCORDANCE WITH ALL FEDERAL, STATE & LOCAL REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.