

GRIGGS PAINT -- MIL-L-81352A, #36440 GRAY, #700A29 -- 8010-00-935-7060

===== Product Identification =====

Product ID:MIL-L-81352A, #36440 GRAY, #700A29

MSDS Date:05/01/1995

FSC:8010

NIIN:00-935-7060

MSDS Number: CFDDG

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phone Num:800-424-9300

CHEMTREC

Preparer's Name:ROBERT COMMISSO

CAGE:DO312

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

Company Name:GRIGGS PAINT

Address:3602 S 16TH PL

City:PHOENIX

State:AZ

ZIP:85040-1319

Phone:602-243-3293

CAGE:DO312

===== Composition/Information on Ingredients =====

Ingred Name:XYLENE (SARA 313) (CERCLA) (VP = 5.1 @ 68F)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction b

y Wt: 21.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYLENE GLYCOL MONOBUTYL ETHER (SARA 313) (VP = 0.6 @ 68F)  
CAS:111-76-2  
RTECS #:KJ8575000  
Fraction by Wt: 5.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:50 PPM  
ACGIH TLV:75 PPM

Ingred Name:METHYL METHACRYLATE RESIN (SARA 313) (CERCLA)  
CAS:80-62-6  
RTECS #:OZ5075000  
Fraction by Wt: 35.0%  
Other REC Limits:NONE RECOMMENDED  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LB  
S

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 10.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:5 MG/M3 TDUST

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHAL: DROWSINESS, DIZZINESS, FATIGUE,  
COMA, LUNG CHANGES, NAUSEA, VOMITING, COUGH, PULMONARY IRRITATION,  
CNS  
DEPRESSION. EYE: IRRITATION. SKIN: IRRITATION &/OR DERMITITIS,  
ABSORPTION (IRRITATION, DEF ATTING & DERMITITIS). INGEST:  
PNEUMONITIS, PULMONARY EDEMA, HEMORRAGE, GI DISTURBANCE.  
Medical Cond Aggravated by Exposure:DISEASES OF SKIN, CENTRAL NERVOUS  
SYSTEM, LIVER AND KIDNEYS.

===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH W/LARGE AMOUNTS WATER FOR 15 MINUTES.  
SEEK MED AID. SKIN: WASH THOROUGHLY W/SOAP & WATER. SEEK MED AID.

INGEST: IMMEDIATELY SEEK MED AID. DONT INDUCE VOMITING. DONT GIVE ANYTHI NG BY MOUTH TO UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:61.0F,10.0C

Autoignition Temp:Autoignition Temp Text:474F

Lower Limits:1.0

Upper Limits:NA

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:APPROVED GAS MASK REQUIRED FOR FIRE FIGHTING PERSONNEL. WATER MAY BE INEFFECTIVE, MAY BE USED TO COOL

CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM IGNITION SOUCES. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK IF NO RISK INVOLVED. REMOVE ALL SOURCES OF IGNITION. STAY UPWIND. ABSORB WITH INERT MATERIAL. FLUSH AREA W/WATER. VENTILATE AREA FOR AT LEAST 24 HOURS OR UNTIL AREA HAS BEEN DECLARED SAFE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED & UPRIGHT TO PREVENT LEAKAGE. AVOID IGNITION SOURCES.

Other Precautions:MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS, TANKS OR PITS WITHOUT ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE MSHA/NIOSH APPROVED UNITS. USE UNITS PER CURRENT 29 CFR 1910.134 RE

GULATIONS & FOLLOW MANUFACTURERS'

INSTRUCTIONS & WARNINGS. AIR PURIFYING OV/FILTER UNITS MAY BE ACCEPTABLE.

Ventilation:LOCAL AND MECHANICAL EXHAUST.

Protective Gloves:RUBBER GLOVES

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS OR GOGGLES

Other Protective Equipment:EYE BATH AND SAFETY SHOWER.

Work Hygienic Practices:MAINTAIN GOOD PERSON HYGIENE. DO NOT USE IN CONFINED AREAS WITHOUT ADEQUATE VENTILATION.

Supplemental Safety and Health

NK

===== Physical/Chemical Propertie

S =====

Boiling Pt:B.P. Text:280 TO 336F  
Decomp Temp:Decomp Text:NA  
Vapor Density:>AIR  
Spec Gravity:1.3  
pH:NA  
VOC Grams/Liter:2.9  
Viscosity:16-22 #3 FC  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:ESSENTIALLY NIL  
Appearance and Odor:VISCOUS LIQUID WITH STRONG SOLVENT ODOR  
Percent Volatiles by Volume:39.74  
Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGEN  
TS.  
Stability Condition to Avoid:IGNITION SOURCES.  
Hazardous Decomposition Products:CO & CO2.

===== Disposal Considerations =====

Waste Disposal Methods:USE INERT ABSORBENT MATERIAL ON SPILLS. DISPOSE  
IN ACCORDANCE WITH ALL FEDERAL, STATE & LOCAL REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.