

MSDS Safety Information

FSC: 8030
NIIN: 00-251-5048
MSDS Date: 06/16/1996
MSDS Num: CFMYT
Product ID: CORROSION PREVENTIVE PETROLATUM SPRAYING APPLICATION
MFN: 05
Responsible Party
Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134
Info Phone Number: 314-522-3141
Emerge
ncy Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141
Preparer's Name: GREGORY M MCGOWAN
Review Ind: Y
Published: Y

Preparer Co. when other than Responsible Party Co.

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134

Contractor Summary

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134
Phone: 314-522-3141

Item Description Information

Item Manager: GSA
Item Name: CORROSION PREVENTIVE COMPOUND
Unit of Issue: GL
UI Container Qty: 4

Ingredients

Cas: 64475-85-0
RTECS #: PY8

240000
Name: MINERAL SPIRITS (STODDARD)
% Wt: 57.58
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 100 PPM
ACGIH TLV: 100 PPM
=====

Health Hazards Data
=====

Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO
Effects of Exposure: EYE IRRIT. SKIN: HARMFUL ABSORPTION, DEFATTING AND IRRITATION. INGEST: CNS/CARDIOPULMONARY EFFECTS (METABOLIC ACIDOSIS) & KIDNEY FAILURE. INHAL: IRRITATION & OTHER EFFECTS.
Medical Cond Aggravated By Exposure: LESIONS AND ABRASIONS.
First Aid: SKIN OR CLOTHES, WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER FOR 15 MINUTES AND CALL DR/OPHTHALMOLOGIST. IGEST: GIVE LARGE AMOUNTS OF WATER OR MILK AND GET IMMEDIATE MEDICAL AID.
=====

Handling and Disposal
=====

Spill Release Procedures: PICK UP SPILL WITH ABSORBENT MATERIAL. FLUSH AREA WITH WATER.
Waste Disposal Methods: IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE, AND LOCAL REGULATIONS.
Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN. STORE IN DRY COOL PLACE.
Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION. DO NOT CONTAMINATE FOOD, FEED OR WATERWAYS.
=====

Fire and Explosion Hazard Information
=====

Flash Point Method: TOC
Flash Point Text: 118F,48C
Lower Limits: 0.7
Upper Limits: 6.0
Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE, HALON, FOAM, WATER SPRAY.
Fire Fighting Procedures: KEEP FIRE EXPOSED CONTAINER COOL W/WATER SPRAY. AVOID SPREADING BURNING LIQUID W/WATER. USE SCBA & SHIELDING TO PROTECT AGAINST BURSTING, RUPTURING, VENTING.
Unusual Fire/Explosion Hazard: MATERIAL COMBUSTIBLE & MAY BE IGNITED BY HEAT, SPARKS, FLAME, OTHER IGNITION SOURCES. VAP

ORS MAY TRAVEL CONSIDERABLE
DISTANCE TO IGNITION SOURCES AND FLASH BACK

=====

Control Measures

=====

Respiratory Protection: NONE NEEDED.
Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE.
Protective Gloves: NEOPRENE GLOVES
Eye Protection: CHEMICAL SPLASH GOGGLES
Other Protective Equipment: SAFETY SHOWERS AND EYEWASH STATIONS.
Work Hygienic Practices: DO NOT CONTAMINATE FOOD, FEED OR WATER. WASH HANDS
AFTER HANDLING PRODUCT.

=====

Physical/Chemical Properties

=====

B.P. Text: 310 TO 400F
M.P/F.P Text: NE
Vapor Pres: 3.1 @ 25C
Vapor Density: NE
Spec Gravity: 0.818 (WATER=1)
PH: NA
Evaporation Rate & Reference: 0.12 (BUAC=1)
Solubility in Water: NEGLIGIBLE
Appearance and Odor: OPAQUE AMBER LIQUID W/PETROLEUM ODOR
Corrosion Rate: NA

=====

=====

Reactivity Data

=====

Stability Indicator: YES
Materials To Avoid: OXIDIZING MATERIALS, STRONG ACIDS AND BASES.
Hazardous Decomposition Products: CARBON DIOXIDE & CARBON MONOXIDE.
Hazardous Polymerization Indicator: NO

=====

Toxicological Information

=====

=====

Ecological Information

=====

=====

MSDS Transport Information

=====

=====

Regulatory Information

=====

=====

Other Information

=====

=====

=====

Transportation Information

=====

Responsible Party Cage: 0FTT5

Trans ID NO: 61334

Product ID: CORROSION PREVENTIVE PETROLATUM SPRAYING APPLICATION

MSDS Prepared Date: 06/16/1996

Review Date: 10/31/1997

MFN: 5

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: GL

Container QTY: 4

=====

Detail DOT Information

=====

===

DOT PSN Code: DNL

DOT Proper Shipping Name: COATING SOLUTION

DOT PSN Modifier: (INCLUDES SURFACE TREATMENTS OR COATINGS USED FOR INDUSTRIAL
OR OTHER PURPOSES SUCH AS VEHICLE UNDERCOATING, DRUM OR BARREL LINING)

Hazard Class: 3

UN ID Num: UN1139

DOT Packaging Group: III

Label: 3

Special Provision: B1,T7,T30

Packaging Exception: 150

Non Bulk Pack: 203

Bulk Pack: 242

Max Qty Pass: 60 L

Max Qty Cargo: 220 L

Vessel Stow Req: A

=====

Detail IMO I
nformation

=====

IMO PSN Code: ENF

IMO Proper Shipping Name: COATING SOLUTION o

IMO PSN Modifier: (INCLUDES SURFACE TREATMENTS OR COATINGS USED FOR INDUSTRIAL
PURPOSES SUCH AS VEHICLE UNDER-COATING, DRUM OR BARREL LINING)

IMDG Page Number: 3321

UN Number: 1139

UN Hazard Class: 3.3

IMO Packaging Group: III

Subsidiary Risk Label: -

EMS Number: 3-05

MED First Aid Guide NUM: 310

=====

Detail IATA I

nformation

=====

IATA PSN Code: GZN
IATA UN ID Num: 1139
IATA Proper Shipping Name: COATING SOLUTION +
IATA PSN Modifier: (INCLUDES SURFACE TREATMENTS OR COATINGS USED FOR INDUSTRIAL
OR OTHER PURPOSES SUCH AS VEHICLE UNDERCOATING, DRUM OR BARREL LINING)
IATA UN Class: 3
IATA Label: FLAMMABLE LIQUID
UN Packing Group: III
Packing Note Passenger: 309
Max Quant Pass: 60L
Max Quant Cargo: 220L
Packaging Note Cargo: 310

=====

=====

Detail AFI Information

=====

AFI PSN Code: GZN
AFI Proper Shipping Name: COATING SOLUTION
AFI Hazard Class: 3
AFI UN ID NUM: UN1139
AFI Packing Group: III
Special Provisions: P5
Back Pack Reference: A7.3

=====

HAZCOM Label

=====

Product ID: CORROSION PREVENTIVE PETROLATUM SPRAYING APPLICATION
Cage: 0FTT5
Company Name: L
HB INDUSTRIES
Street: 8833 FLEISCHER PLACE
City: ST. LOUIS MO
Zipcode: 63134
Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141
Label Required IND: Y
Date Of Label Review: 10/12/1999
Status Code: A
Origination Code: G
Hazard And Precautions: EYE IRRIT. SKIN: HARMFUL ABSORPTION, DEFATTING AND
IRRITATION. INGEST: CNS/CARDIOPULMONARY EFFECTS (METABOLIC ACIDOSIS) &
KIDNEY FAILURE. INHAL: IRRITATION & OTHER EFFECTS.

=====

Disclaim

er (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.