

PRATT AND LAMBERT INC -- PRIMER EPOXY COATING CORRINHIB, LEAD #724700 --
8010-01-187-9820

===== Product Identification =====

Product ID:PRIMER EPOXY COATING CORRINHIB, LEAD #724700

MSDS Date:10/31/1995

FSC:8010

NIIN:01-187-9820

Kit Part:Y

MSDS Number: CFNCM

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info

Phone Num:316-733-1361

Emergency Phone Num:316-733-1361

Preparer's Name:W. A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA 313) (CERCLA) (VP = 22 @ 20C

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 10.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM/STEL 150

ACGIH

TLV:50 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 20.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER (VP = 11 @ 20C
CAS:107-98-2
RTECS #:UB7700000
Fraction by Wt: 5.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/STEL 150

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)
(VP = 70 @ 20C

CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 15.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM/STEL 300
ACGIH TLV:200 PPM/STEL 300
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TALC
CAS:14807-96-6
RTECS #:MW2700000
Fraction by Wt: 15.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3

Ingred Name:SILICA, CRYSTALLINE - QUARTZ
CAS:14808-60-7
RTECS #:VV7330000
Fraction by Wt: 15 MINUTES, LIFT LIDS. GET
MED AID. SKIN: FLUSH W/LARGE AMOUNTS OF WATER. REMOVE

CONTAM
CLOTHES, CALL DR.

===== Fire Fighting Measures =====

Flash Point:24.0F,-4.4C

Autoignition Temp:Autoignition Temp Text:572F

Lower Limits:1.4

Upper Limits:11.2

Extinguishing Media:CLASS B EXTINGUISHERS (CO2, DRY CHEMICAL, ALCOHOL FOAM) FOR FLAMMABLE LIQUID. POLYMER FOAM PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE, USE H2O (FOG NOZZLES PREFERRED) TO COOL FIRE EXPOSED CONTAINERS, PREVENT PRESSURE BUILDUP/AUTO

IGNITION/EXPLOSION.

Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY BE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. GET MED AID.

===== Accidental Release Measures =====

Spill Release Procedures:EVAC AREA. ELIMINATE IGNITS. DIKE/ABSORB W/INERT MATERIAL. TRANSFER TO COVERED METAL CONTAINER W/NONSPARDING TOOLS. DONT CONTAM SEWERS/STREAMS/GROUNDWATER.

===== Handling and Storage =====

Handling and Storage Precautions:DONT STORE >115F. CLOSE CONTAINER AFTER USE. KEEP AWAY FROM CHILDREN. DONT REUSE CONTAINER FOR ANY PURPOSE. GROUND/BOND TO RECEIVING CNTNR WHEN **

Other Precautions:** TRANSFERRING. DONT WELD/BRAISE/CUT ON EMPTY CONTAINER. DONT PRESSURE TO EMPTY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH CHEMICAL CARTRIDGE RESPIRATOR. FOR SPRAYING USE MECHANICAL PREFILTER.

IN CONFINED AREA USE AIR SUPPLIED RESPIRATOR.

Ventilation:LOCAL EXHAUST.

Protective Gloves:IMPERMEABLE.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWER.

Supplemental Safety and Health
MORE INFORMATION ON FILE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175 TO 248F

Melt/Freeze Pt:M.P/F.P Text:-50F18C

Decomp Temp:Decomp Text:1832F,1000C

Vapor Pres:70.0

Vapor Density:>AIR.

Spec Gravity:1.3

pH:4-7

Viscosi

ty:63-73 KU

Evaporation Rate & Reference:115F) AND SOURCES

OF IGNITION.

Hazardous Decomposition Products:SMOKE, CARBON MONOXIDE & CARBON
DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE W/FEDERAL, STATE & LOCAL
REGULATIONS. EPA #D-001.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of Ame

rica in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.