

CROSSFIELD PRODUCTS CORP -- DEX-O-TEX QUICK SET PASTE -- 5610-00-618-0258

=====  
Product Identification  
=====

Product ID:DEX-O-TEX QUICK SET PASTE

MSDS Date:01/01/1992

FSC:5610

NIIN:00-618-0258

MSDS Number: CFQWM

=== Responsible Party ===

Company Name:CROSSFIELD PRODUCTS CORP

Address:3000 E HARCOURT ST

City:COMPTON

State:CA

ZIP:90221

Country:US

Info Phone Num:310-886-9100

Emergency Phone Num:310-88

6-9100

CAGE:60782

=== Contractor Identification ===

Company Name:CROSSFIELD PRODUCTS CORP.

Address:3000 EAST HARCOURT ST.

Box:City:COMPTON

State:CA

ZIP:90221

Country:US

Phone:310-886-9100

CAGE:60782

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CARBOXYLATED SBR LATEX

CAS:30174-67-5

OSHA PEL:N/K

ACGIH TLV:N/K

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO

Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE:MAY CAUSE EYE AND SKIN  
IRRITATION. CHRONIC:NOT ESTABLISHED.  
Explanation of Carcinogenicity:NOT RELEVANT  
Effects of Overexposure:SEE HEALTH HAZARDS.  
Medical Cond Aggravated by Exposure:NOT ESTABLISHED.

=====  
===== First Aid Measures =====

First Aid:INHAL:MOVE SUBJECT TO FRESH AIR. EYES:FLUSH W/WATER FOR AT  
LEAST 15 MINUTES & CALL MD. SKIN:WA  
SH AFFECTED AREAS W/SOAP &  
WATER. REMOVE CONTAMINATED CLOTHING. INGEST:INDUCE VOMITING & CALL  
MD AT ONCE.

=====  
===== Fire Fighting Measures =====

Flash Point:>212F,>100C  
Extinguishing Media:WATER, CO\*2, DRY CHEMICAL.  
Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE  
EQUIPMENT .  
Unusual Fire/Explosion Hazard:NONE KNOWN.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP W/WATER & ALLOW  
TO DRY. SODIUM OR  
CALCIUM CHLORIDE CAN BE SPRINKLED ON SPILL WHICH WILL COAGULATE  
LATEX, THEN FLUSH W/WATER.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:AVOID BREATHING SPRAY MISTS OR HEATED  
VAPORS. KEEP PRODUCT FROM FREEZING TO AVOID COAGULATION.  
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Exposure Controls/Personal Protection =====

Respirato

ry Protection:NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED

- IF NOT, USE A NIOSH APPROVED RESPIRATOR.

Ventilation:LOCAL EXHAUST &/OR MECHANICAL (GENERAL) VENTILATION.

Protective Gloves:CHEMICAL RESISTANT OR RUBBER GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .

Other Protective Equipment:ANSI APPROVED EYE WASH FOUNTAIN & DELUGE  
SHOWER . OTHER PROTECTIVE EQUIPMENT AS REQUIRED TO PREVENT SKIN  
CONTACT.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Saf

ety and Health

SPEC GRAV:1.01-1.02 (H\*2O=1).

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:AS WATER

Vapor Density:AS WATER

Spec Gravity:SUPP DATA

Evaporation Rate & Reference:AS WATER

Solubility in Water:DISPERSIBLE

Appearance and Odor:MILKY WHITE LIQUID EMULSION W/SLIGHT STYRENE ODOR.

Percent Volatiles by Volume:70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YE

S

Stability Condition to Avoid:NON-REACTIVE, MAY COAGULATE IF FROZEN AT  
32F.

===== Disposal Considerations =====

Waste Disposal Methods:MAY BE INCINERATED OR DISPOSED OF IN SANITARY  
LANDFILL I/A/W PROCEDURES USED W/LATEX PRODUCTS & W/LOCAL, STATE &  
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of Americ

a in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.