

3M GENERAL OFFICES -- 80-6106-2549-5, ADHESIVE FOR 1600 HAT HALT (S

=====  
MSDS Safety Information  
=====

FSC: 6060

NIIN: 01-366-1780

MSDS Date: 11/11/1991

MSDS Num: CFQZC

Product ID: 80-6106-2549-5, ADHESIVE FOR 1600 HAT HALT (SUP DAT)

MFN: 01

Responsible Party

Cage: 1BY21

Name: 3M GENERAL OFFICES

Address: 3M CENTER

City:

ST PAUL MN 55144-1000

Info Phone Number: 612-733-1110

Emergency Phone Number: 612-733-1110

Proprietary Ind: Y

Published: Y

=====  
Contractor Summary  
=====

Cage: 76381

Name: MINNESOTA MINING AND MFG CO, DBA 3M

Address: 3M CENTER BLDG 224-5S-04

City: SAINT PAUL MN 55144-1000

Phone: 866-556 5712 / 612-733-1110

Cage: 1BY21

Name: MINNESOTA MINING AND MFG CO ENGINEERING DOCUMENT SYSTEMS DIV

Address: 3M

CTR

City: SAINT PAUL MN 55144-1000

Phone: 612-737-4114

=====  
Item Description Information  
=====

Item Name: CONNECTOR,PLUG,FIBER OPTIC

=====  
Ingredients  
=====

Name: \*\*\* PROPRIETARY \*\*\*  
-----

=====  
Health Hazards Data  
=====

=====  
LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Explanation Of Carcinogenicity: NOT RELEVANT.

Signs And Symptoms Of Overexposure: SEE HEALTH HAZARDS.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYES: IMMEDIATELY FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINUTES

& CALL MD. SKIN: HOT MATERIAL: I

MMEDIATELY FLUSH W/COLD WATER & COVER

W/CLEAN DRESSING. DO NOT ATTEMPT TO REMOVE MATERIAL. HAVE BURN T REATED BY

MD. INHAL: POTENTIAL FOR VAPOR RELEASE WHEN CONNECTORS ARE HEATED IS MINIMAL.

SHOULD SYMPTOMS OCCUR, REMOVE TO FRESH AIR. IF SYMPTOMS CONTINUE, CALL MD.

INGEST: CALL MD IMMED (FP N).

=====  
Handling and Disposal

=====  
Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste

Disposal Methods: DISPOSE OF WASTE MATERIAL AND USED CONNECTORS IN A  
SANITARY LANDFILL. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL  
REGULATIONS (FP N).

Handling And Storage Precautions: AVOID CONTACT WITH HOT MATERIAL. KEEP OUT OF  
REACH OF CHILDREN. FOR INDUSTRIAL USE ONLY.

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

=====  
Fire and Explosion Hazard Information

=====  
Exting

ushing Media: CARBON DIOXIDE, FOAM, WATER, DRY CHEMICAL.

Fire Fighting Procedures: NONE. WEAR NIOSH APPROVED SCBA & FULL PROTECTIVE  
EQUIPMENT (FP N).

Unusual Fire/Explosion Hazard: NONE.

=====  
Control Measures

=====  
Respiratory Protection: USE NIOSH APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE  
OF CONCERN (FP N).

Ventilation: NONE SPECIFIED BY MANUFACTURER.

Protective Gloves: IMPERVIOUS G

LOVES (FP N).

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES (FP N).

Other Protective Equipment: EMERGENCY EYEWASH AND DELUGE SHOWER MEETING ANSI DESIGN CRITERIA (FP N).

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health: TRADE NAME/PART #: FIBER OPTIC CONNECTOR. USERS OF THE "L" VERION OF SHOULD CONSULT "LR" VERSION FOR ADDITIONAL INFORMATION (FP N).

=====  
Physical/Chemical Properties  
=====

Spec Gravity: 0.960 (H\*2O=1)

Solubility in Water: NIL

Appearance and Odor: SOLID, BLUE, MILD RESINOUS ODOR

Percent Volatiles by Volume: 0.00  
=====

Reactivity Data  
=====

Stability Indicator: YES

Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: MATERIAL WILL GENERATE CARBON MONOXIDE, CARBON DIOXIDE, NITROGEN O

XIDES AND SMOKE PARTICLES WHEN SUBJECTED TO FLAME.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT.  
=====

Toxicological Information  
=====

Ecological Information  
=====

MSDS Transport Information  
=

Regulatory Information  
=====

Other Information  
=====

Transportation Information  
=====

Responsible Party Cage: 1BY21

Trans ID

NO: 129695  
Product ID: 80-6106-2549-5, ADHESIVE FOR 1600 HAT HALT (SUP DAT)  
MSDS Prepared Date: 11/11/1991  
Review Date: 12/16/1997  
MFN: 1  
Multiple KIT Number: 0  
Review IND: Y

=====  
Detail DOT Information  
=====

DOT PSN Code: ZZZ  
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

=====  
Detail IMO Information  
=====

=====  
IMO PSN Code: ZZZ  
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION  
=====

=====  
Detail IATA Information  
=====

IATA PSN Code: ZZZ  
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

=====  
Detail AFI Information  
=====

AFI PSN Code: ZZZ  
AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

=====  
HAZCOM Label  
=====

Product ID: 80-6106-2549-5, ADHESIVE FOR 1600 HAT HALT (SUP DAT)  
Cage: 1BY21  
Company Name: MINNESOTA MINING AND MFG CO ENGINEERING DOCUMENT SYSTEMS DIV  
Street: 3M CTR  
City: SAINT PAUL MN  
Zipcode: 55144-1000  
Health Emergency Phone: 612-733-1110  
Label Required IND: Y  
Date Of Label Review: 09/25/

1997

Status Code: C

Label Date: 09/25/1997

Origination Code: G

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: WARNING

Respiratory Protection IND: YES

Health Hazard: Moderate

Contact Hazard: Moderate

Fire Hazard: None

Reactivity Hazard: None

=====  
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America in

no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice t

o verify

and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.