Product ID: P/N 9044-RB RB-44 SAFETY STRIP MSDS Date:09/01/1995 FSC:6850 NIIN:01-394-0168 **MSDS Number: CFRKD** === Responsible Party === Company Name: ROTH MANUFACTURING CO. Box:700146 **City:SAN ANTONIO** State:TX ZIP:78270 Country:US Info Phone Num:210-598-7064 Emergency Phone Num:210-598-7684 (MEDS ONLY) CAGE:08YV6 === Contractor Identification === Compan y Name: ROTH MANUFACTURING CO. Box:700146 **City:SAN ANTONIO** State:TX ZIP:78270 Country:US Phone:210-598-7064 CAGE:08YV6

Ingred Name:DIETHYLENE GLYCOL MONOBUTYL ETHER CAS:112-34-5 RTECS #:KJ9100000 Fraction by Wt: 20-50% Other REC Limits:NONE RECOMMENDED

Ingred Name:N-METHYLPYRROLIDONE CAS:872-50-4 RTECS #:UY5790000 Fraction by Wt: 50-80% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SERIOUS INJURY WILL RESULT FROM INGESTION OF THIS PRODUCT. MAY CAUSE SEVERE EYE IRRITATION, PERMANENT TISSUE DAMAGE. PROLONGED SKIN CONTACT MAY CAUSE IRRITATION. INHALATION OF CONCENTRATED VAPORS/MIST S MAY CAUSE RESPIRATORY IRRITATION. CHRONIC: NONE KNOWN. Explanation of Car cinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN. Effects of Overexposure: EYES-SEVERE IRRITTAION, TISSUE DAMAGE. SKIN-IRRITATION, REDDENING, ITCHING, DRYING. INHALED-NONE STATED. INGESTED-SERIOUS INJURY. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. First Aid:IN ALL CASES GET MEDICAL ATTENTION. EYES-FLUSH WITH WATER FOR 15 MINUTES, LIFT LIDS. REMOVE CONTACT LENSES. SKIN-REMOVE CONTAMINATED CLOTHES. FLUSH WITH RUNNING WATER. INHALED-REMOVE TO FRESH AIR. ING ESTED-IF CONSCIOUS, RINSE MOUTH THEN GIVE 1-2 GLASSES WATER. INDUCE VOMITING IF LARGE QUANTITIES ARE INGESTED. Flash Point Method:TCC Flash Point:220F,104C Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL FIRE FIGHTER'S PROTECTIVE GEAR. USE WATER TO COOL FIRE EXPOSED CONTAINERS. Unusual Fire/Explosion Hazard:NEVER US EWELDING OR CUTTING TORCH ON OR NEAR DRUM, EVEN WHEN EMPTY.

Spill Release Procedures: ABSORB WITH SOLID ABSORBENT AND SHOVEL INTO CONTAINERS FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and St

orage Precautions:STORE BETWEEN 40F & 120F. Other Precautions:NONE SPECIFIED BY MANUFACTURER.

Respiratory Protection:NONE NORMALLY REQUIRED. IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR AN AIR-SUPPLIED RESPIRATOR OR SCB A, AS REQUIRED. USE IAW 29 CFR 1910.134.
Ventilation:LOCAL EXHAUST RECOMMENDED.
Protective Gloves:NE
OPRENE OR BUTYL RUBBER.
Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. DLA-HMIS: EYE WASH STATION, WASHING FACILITIES.
Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

HCC:N1 Boiling Pt:B.P. Text:>400F,>204C Vapor Pres:3 Spec Gravity:0.99

Evaporation Rate & amp; Reference: