

DEL PAINT CORP. -- TT-E-527D BROWN #30372 -- 8010-00-116-0867

===== Product Identification =====

Product ID:TT-E-527D BROWN #30372

MSDS Date:08/05/1997

FSC:8010

NIIN:00-116-0867

MSDS Number: CFWTW

=== Responsible Party ===

Company Name:DEL PAINT CORP.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Info Phone Num:405-672-1431/FAX 405-672-0804

Emergency Phone Num:800-424-9300 24 HRS

Preparer's Name:ONEY FLEMING

CAGE:JO954

=== Contractor Id

entification ===

Company Name:DEL PAINT CORP.

Address:3105 E. RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431/FAX 405-672-0804

CAGE:JO954

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:MEDIUM ALIPHATIC SOLVENT NAPHTHA

CAS:64742-88-7

Fraction by Wt: 32.4%

Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-

## HAZARDOUS INGREDIENTS

Fraction by Wt: 67.6%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

Ingred Name:VOC = 2.97 LBS/GL

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

### ===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: REDNESS, PAIN. SKIN: REDNESS.

INHAL: LABORED BREATHING, DULLNESS, DROWSINESS. INGEST: ABDOMINAL

PAIN, NAUSEA. CHRONIC: EYE: IRRITATION, REDNESS, TEARING, BLURRED

VISION. SKIN: IRRITATION, DEFATTI NG, DERMATITIS. INHAL:

NASAL/RESPIRATORY IRRIT, DIZZINESS, NAUSEA, HEADACHE. INGEST: GI

IRRITATION, NAUSEA, VOMITING.

Medical Cond Aggravated by Exposure:RESPIRATORY SYSTEM DISEASES.

### ===== First Aid Measures =====

First Aid:EYE: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINUTES

, LIFT

LIDS, GET MED AID. SKIN: REMOVE CONTAM CLOTHES, WASH BEFORE REUSE.

WASH SKIN W/SOAP & WATER. INHAL: REMOVE TO FRESH AIR. GIVE OXYGEN

IF NEEDED. GET MED AID. INGEST: KEEP WARM/QUIET. GET MED AID. DONT

INDUCE VOMIT.

### ===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:100F,38C

Autoignition Temp:Autoignition Temp Text:540F

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:CO2, DRY CHEMICAL, FOAM.

Fire Fighting Procedure

s:USE SCBA & FULL PROTECTIVE GEAR. USE WATER  
SPRAY TO COOL CONTAINERS. (PREVENT PRESSURE  
BUILDUP/AUTOIGNITION/EXPLOSION).

Unusual Fire/Explosion Hazard:WATER MAY SPREAD FIRE. VAPORS >AIR, MAY  
TRAVEL TO IGNITION SOURCE & FLASH BACK.

===== Accidental Release Measures =====

Spill Release Procedures:VENT AREA. COVER W/INERT ABSORBENT. SHOVEL  
W/NONSPARKING TOOLS INTO CONTAINER. REMOVE TO SAFE AREA & SEAL.

===== Handling and Storage =====  
=====

Handling and Storage Precautions:STORE IN CLEAN, DRY AREA. KEEP AWAY  
FROM IGNITION SOURCES.

Other Precautions:KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM  
CHILDREN. GROUND EQUIPMENT TO REDUCE STATIC ELECTRICITY HAZARD. USE  
NONSPARKING TOOLS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A RESPIRATOR W/APPROPRIATE CARTRIDGES (NIOSH  
APPROVED).

Ventilation:LOCAL EXHAUST.

Protective Gloves:CHEMICAL RESISTANT.

Eye

Protection:SAFETY GLASSES W/SIDE SHIELDS.

Other Protective Equipment:EYEWASH STATION, SAFETY SHOWER & IMPERVIOUS  
CLOTHING.

Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Text:752F,400C

Vapor Pres:2.58

Vapor Density:>AIR

Spec Gravity:1.1

pH:NA

Viscosity:65-72 KU

Evaporation Rate & Reference: